Declare.SM

Ultima® Ceiling Panels
Armstrong World Industries, Inc.

Final Assembly: Pensacola, Florida, USA; Marietta, Pennsylvania, USA
Life Expectancy: 30 Year(s)
Embodied Carbon: 0.449 kg CO2eq
Declared Unit: 1ft2
End of Life Options: Take Back Program (Armstrong Ceiling Recycling Program), Recyclable (100%)

Ingredients:

Mineral Wool; Perlite; Clay; Corn Starch; Cellulose; Calcium Carbonate; Limestone; Aluminum hydroxide; Calcium carbonate; Dolomite; Glass, oxide, chemicals; Polyvinyl acetate; Kaolin; Titanium dioxide; Amorphous Silica; Acrylic Acid; Propanol; 1,2-Ethanediamine, N-[3-(trimethoxysilyl)propyl]-; Aluminum Trihydrate; Zinc borate; Polyvinyl alcohol; Quartz; Fatty acids, coco, polymers with benzoic acid, pentaerythritol and phthalic anhydride; White Tint; Polyethylene; Paraffin Wax; Polyethylene Wax; Benzenesulfonic acid, 5-benzoyl-4-hydroxy-2-methoxy-; Sodium Salt; Styrene Polymer; Silisic Salt; Water; Citric Acid; Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol; Ester; Methyl Polymer; Attapulgite Clay; Ethyl Acetate; Hydrogenated Naphtha; Proenoate

Living Building Challenge Criteria: Compliant

I-13 Red List:

- ■ LBC Red List Free
- ☐ LBC Red List Approved
- ☐ Declared

% Disclosed: 100% at 100ppm
VOC Content: Not Applicable

I-10 Interior Performance: CDPH Standard Method v1.2-2017
I-14 Responsible Sourcing: Not Applicable

ARM-0026
EXP. 01 JUL 2025
Original Issue Date: 2016