

ULTIMA®

Vector®
fine texture



SUSTAIN®
High Performance
Sustainable
Ceiling Systems

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit




DESIGNFlex®
A New World of Choice
for Ceiling Systems



Ultima® Vector® panels with Prelude® XL® 15/16" suspension system

plus capabilities
to do more



armstrongceilings.com/capabilities
See more photos at:
armstrongceilings.com/photogallery

Smooth-texture panels with a 1/4" reveal and downward accessibility; Ideal for projects where plenum space is limited. Offer both Sustain® and Total Acoustics® panel performance for flexible spaces.

KEY SELECTION ATTRIBUTES

- DesignFlex® options include made-to-order sizes available to ship in 3 weeks
- Ultima® Vector® panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Mold- and mildew-resistant surface
- Smooth, clean, durable finish – Washable, Scratch-resistant, Soil-resistant
- 1/4" reveal resulting in a monolithic appearance
- Trim Kit for Vector® in Blizzard White finish for easy installation and bright visual
- Downward accessible for minimal plenum height (Vector)
- USDA-Certified Biobased Product – 95%
- Visual coordinates with Optima® for mixed (open/closed plan) applications
- Item 1920 available with Create!™ printed images and patterns
- Available with factory-cut holes for USAI® trimless downlight fixture integration
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- 10-Year replacement panel available for item 1920




COLOR



White
(WH)

DETAILS



1. Ultima® Vector®
2. Ultima® Vector® with Prelude® 15/16" suspension system

TechLine 877 276-7876
armstrongceilings.com/ultima

Armstrong®
World Industries

ULTIMA®

Vector®
fine texture

USDA
CERTIFIED
BIOBASED
PRODUCT
PRODUCT 95%

SUSTAIN®
High Performance
Sustainable Ceiling Systems

Declare.

GREENGUARD
Gold Certified
(details below)

LEED®
WELL™ LBC


UP TO 76% RECYCLED CONTENT

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/repurposed producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

Calculate sustainability with Green Genie™
armstrongceilings.com/greengenie

LOCATION DEPENDENT

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
ULTIMA®	74	1921	12 x 24 x 3/4" □
15/16" Vector with 1/4" Reveal			
			
		1920	24 x 24 x 3/4" □
3/4" Thick			
Made-to-Order Sizes	Width	Length	
	4" - 24"	9" - 48"	

1 Ctn Min
FASTSIZE
3 WEEKS
order to ship


Visit the product page online and see "Configure an Item" to verify capabilities. Questions? email Techline@armstrongceilings.com

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

PERFORMANCE SELECTION Dots represent high level of performance.

UL Classified Acoustics	Total Acoustics ¹	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	DURABILITY	Recycle Program	30-Yr Warranty		
N/A	N/A	N/A	Class A	0.88	*	*	Fog	Wash	Scratch	Soil	Recycle Program	30-Yr Warranty
0.70	33	N/A	Class A	0.88	*	*						
N/A	N/A	N/A	Class A	0.88	*	*						

SUSPENSION SYSTEM



TRIM KITS FOR VECTOR® PANELS

Item No.	Color	Length	Substrate	Pcs/Ctn
VETK4ZW	Blizzard White	4"	Steel	24
VETK6ZW	Blizzard White	6"	Steel	24
VETK24ZW	Blizzard White	24"	Steel	24
VETK48ZW	Blizzard White	48"	Steel	24
VETK96ZW	Blizzard White	96"	Steel	24

Made-to-Order Sizes & Colors

4-6 WEEKS order to ship

Length 4" - 96"

ACCESSORIES (must be ordered separately)

Item No.		Pcs/Ctn
440A	 Border Clip for Vector® panels (for all installations)	50
442A	 Hold-down Clip for Vector® panels (for all installations)	50
7425	24" Stabilizer Bar	100
7445	48" Stabilizer Bar	100
522	 Midpoint Clip (Needed for panels over 30" wide)	50
7870	 Spring Border Clip (For installations with the panel resting on the wall molding)	1,000

PHYSICAL DATA

Material
Wet-formed mineral fiber with DuraBrite® acoustically transparent membrane.

Surface Finish
DuraBrite with factory-applied latex paint.

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

ASTM E1264 Classification
Type IV, Form 2, Pattern E; Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions
GREENGUARD Gold Certified
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustical Performance
CAC testing conducted using Prelude® suspension system.

Primary (Embodied) Energy
See all LCA information on our EPDs.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL.COM/GG UL 2818



Insulation Value
R Factor - 2.2 (BTU units)
R Factor - 0.39 (Watts units)

Cleaning and Disinfecting
Cleaning and CDC recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
1920 - 1.08 lbs/SF; 48 SF/ctn
1921 - 1.08 lbs/SF; 24 SF/ctn

Minimum Order Quantity
1 carton, excludes FastSize™ items

