

ULTIMA®

Vector®
fine texture



CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



DESIGNFlex®
A New World of Choice
for Ceiling Systems

plus capabilities
to do more



armstrongceilings.com/capabilities
See more photos at:
armstrongceilings.com/photogallery

Ultima Vector panels with Prelude XL 15/16" suspension system

Smooth-texture panels with a 1/4" reveal and downward accessibility; ideal for projects where plenum space is limited. Offer both Sustain® and Total Acoustics® panel performance for flexible spaces.

KEY SELECTION ATTRIBUTES

- DesignFlex® options include made-to-order sizes available to ship in 3 weeks
- Ultima® Vector® panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Mold- and mildew-resistant surface
- Smooth, clean, durable finish – Washable, Scratch-resistant, Soil-resistant
- 1/4" reveal resulting in a monolithic appearance
- Trim Kit for Vector® in Blizzard White finish for easy installation and bright visual
- Downward accessible for minimal plenum height (Vector)
- USDA-Certified Biobased Product – 95%
- Visual coordinates with Optima® for mixed (open/closed plan) applications
- Item 1920 available with Create!™ printed images and patterns
- Available with factory-cut holes for USAI® trimless downlight fixture integration
- 30-Year Limited System Warranty against visible sag, mold, and mildew

- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant
- 10-Year replacement panel available for item 1920



COLOR



White
(WH)

DETAILS



1. Ultima® Vector®
2. Ultima® Vector® with Prelude® 15/16" suspension system

TechLine 877 276-7876
armstrongceilings.com/ultima

Armstrong®
World Industries

ULTIMA®

Vector®

fine texture





USDA
CERTIFIED
BIOBASED
PRODUCT
PRODUCT 95%SUSTAIN®
High Performance
Sustainable Ceiling Systems

Declare®

LEED®
WELL® LBCUP TO 76%
RECYCLED
CONTENTenergy management
construction waste mgmt
regional materials
design for flexibility
EPD
recyclable/ bio-based producer resp.Calculate sustainability with Ecomedes
armstrongceilings.com/ecomedesbiobased materials
recycled content
sourcing of raw materials
material ingredient reporting
low emitting/ materials
lighting quality
acoustics

LOCATION DEPENDENT

VISUAL SELECTION





















armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
ULTIMA®	74	1921	12 × 24 × 3/4" □
15/16" Vector with 1/4" Reveal			
 			
 			
3/4" Thick			
<div> <div>Made-to-Order Sizes</div> <div>Visit the product page online and see "Configure an Item" to verify capabilities. Questions? email Techline@armstrongceilings.com</div> </div>			
<div> <div>1 Ctn Min FASTSIZE 3 WEEKS order to ship</div> <div>Width</div> <div>Length</div> </div>			
<div> <div>4" - 24"</div> <div>9" - 48"</div> </div>			

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$\$

UL Classified Acoustics		Total Acoustics ¹	Fire Performance	Light Reflect	Bio-BLOCK Anti-Mold/ Mildew	Humi-Guard+ Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	DURABILITY				Recycle Program	30-Yr Warranty
 NRC + CAC =														
N/A	N/A	N/A	Class A	0.88	*	*	*							
0.70	33	N/A	Class A	0.88	*	*	*							
N/A	N/A	N/A	Class A	0.88	*	*	*							

SUSPENSION SYSTEM

15/16"



Prelude® XL®

TRIM KITS FOR VECTOR® PANELS

Item No.	Color	Length	Substrate	Pcs/Ctn
VETK4ZW	Blizzard White	4"	Steel	24
VETK6ZW	Blizzard White	6"	Steel	24
VETK24ZW	Blizzard White	24"	Steel	24
VETK48ZW	Blizzard White	48"	Steel	24
VETK96ZW	Blizzard White	96"	Steel	24

Made-to-Order
Sizes & Colors4-6
WEEKS
order to shipLength
4" - 96"

ACCESSORIES (must be ordered separately)

Item No.			Pcs/Ctn
440A		Border Clip for Vector® panels (for all installations)	50
442A		Hold-down Clip for Vector® panels (for all installations)	50
7425		24" Stabilizer Bar	100
7445		48" Stabilizer Bar	100
522		Midpoint Clip (Needed for panels over 30" wide)	50
7870		Spring Border Clip (For installations with the panel resting on the wall molding)	1,000

PHYSICAL DATA

Material

Wet-formed mineral fiber with DuraBrite® acoustically transparent membrane.

Surface Finish

DuraBrite with factory-applied latex paint.

Fire Performance

Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

ASTM E1264 Classification

Type A, Form A2.2, Pattern E; Fire Class A

Humidity/Sag Resistance

HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew

Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustical Performance

CAC testing conducted using Prelude® suspension system.

High Recycled Content

Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value

R Factor - 2.2 (BTU units)

R Factor - 0.39 (Watts units)

Cleaning and Disinfecting

Cleaning and CDC recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty

When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton

1920 - 1.08 LBS/SF; 48 SF/CTN
1921 - 1.08 LBS/SF; 24 SF/CTN

Minimum Order Quantity

1 carton, excludes FastSize™ items

TechLine / 1 877 276-7876
armstrongceilings.com/ultima
BPCS-3313-924

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are registered trademarks of the International Living Future Institute®; WELL™ and WELL Building Standard are trademarks of the International WELL Building Institute; UL is a registered trademark of UL LLC; Revit® is a registered trademark of Autodesk, Inc.; USAI Lighting is a registered trademark of USAI Lighting, LLC; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2024 AWI Licensing LLC

Armstrong®
World Industries

MINERAL FIBER - Standard

