

# Declare.

## WoodWorks™ - Solid Wood Armstrong World Industries

**Final Assembly:** Morristown, Tennessee, USA; Beverly, West Virginia, USA

**Life Expectancy:** 30 Year(s)

**Embodied Carbon:** 0.583 kg CO2eq 

**Declared Unit:** 1 square foot of product

**End of Life Options:** Salvageable/Reusable in its Entirety, Landfill (100%)

### Ingredients:

Kiln dried wood; Titanium dioxide; Triethanolamine; Undisclosed (< 0.51%); 2-Propanol, 1-methoxy-; Water; 2-Propenoic acid, 1,6-hexanediyol ester; oxybis(methyl-2,1-ethanediyol) diacrylate; Ethanol, 2-propoxy-; Black Tint; Glycol Ether; 2-Propanol, 1-methoxy-, acetate; 2-Propenoic acid, (1-methyl-1,2-ethanediyol) bis[oxy(methyl-2,1-ethanediyol)] ester; Amorphous Silica; Chromate(1-), hydroxy[2-hydroxy-3-[[[2-hydroxy-3-nitrophenyl)methylene]amino]-5-nitrobenzenesulfonato (3-)-], hydrogen, compd. with 3-[(2-ethylhexyl)oxy]-1-propanamine (1:1); Isopropyl alcohol; Tint; White Tint; Chromium, 2-[2-(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)diazenyl]benzoate 2-[2-(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)diazenyl]-5-sulfobenzoate lithium sodium complexes; 2-Butoxyethanol; Chromate(3-), bis[3-hydroxy-4-[(2-hydroxy-1-naphthalenyl)azo]-7-nitro-1-naphthalenesulfonato (3-)-], trisodium; Ethanol; Methanone, (1-hydroxycyclohexyl)phenyl-; Talc; Trimethylolpropane Triacrylate/2-Hydroxypropyl Acrylate; 1-Propanone, 2-hydroxy-2-methyl-1-phenyl-, 1,3-Propanediol, 2,2-bis(hydroxymethyl)-, polymer with 2-methyloxirane and oxirane, 2-propenoate; Poly(oxy-1,2-ethanediyol),  $\alpha$ -hydro- $\omega$ -[(1-oxo-2-propenyl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1); Silica Gel; 1,3-Propanediol, 2,2-bis(hydroxymethyl)-, polymer with (chloromethyl)oxirane, 2-propenoate; Amines, C10-14-branched and linear alkyl, [1-[(2-hydroxy-4-nitrophenyl) azo]-2-naphthalenolato(2-)] [1-[(2-hydroxy-5-nitrophenyl) azo]-2-naphthalenolato(2-)]chromate(1-); ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate; phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide; Phosphine oxide; Poly[oxy(methyl-1,2-ethanediyol)],  $\alpha,\alpha',\alpha''$ -1,2,3-propanetriyltris[ $\omega$ -[(1-oxo-2-propenyl)oxy]-]; Undisclosed (< 0.015%); 1,2-Propanediol, diacetate; 5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-

<sup>1</sup>LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

### Living Building Challenge Criteria: Compliant

#### I-13 Red List:

- LBC Red List Free      % Disclosed: 99.48% at 100ppm
- LBC Red List Approved      VOC Content: Not Applicable
- Declared

**I-10 Interior Performance:** Not Applicable

**I-14 Responsible Sourcing:** Product Available with FSC Chain of Custody; Low Risk Wood

ARM-0081  
EXP. 01 JAN 2026  
Original Issue Date: 2022

