

WOODWORKS®

Tegular



**TOTAL
ACOUSTICS®**
Sound Absorption (NRC)
+ Sound Blocking (CAC)



FAST134
Select Items Ship Fast
armstrongceilings.com/fast134



CAD/Revit® drawings at:
armstrongceilings.com/cadrevit

WoodWorks Tegular panels with W2 perforation in Constants™ Redux Wood Wheat and Suprafine® XL® suspension system in White

Now get Total Acoustics® performance with WoodWorks® Tegular perforated panels – excellent noise reduction and sound blocking in one system.

KEY SELECTION ATTRIBUTES


- Get total noise control and design flexibility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics
- Standard veneers feature various species and cuts for beautiful wood visuals
- ASTM E84 Class A Fire Performance
- The natural warmth of wood can contribute to biophilic designs and building certification standards like the WELL™ v2 "Nature and Place" feature
- Create upturns for continuous visuals and clouds with WoodWorks® trim
- Select products included in the FAST134 program – ready to ship in 4 weeks or less
- Shorter lead times and lower cost than custom millwork
- USDA Biobased Content: 100%
- FSC® certified wood available as a premium quoted option (FSC® C007626)
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

VENEER CUTS


Different cuts of a log will yield different graining visuals. Choose your veneer to achieve your desired look.



Plain Sliced
Produces the well-known cathedral or loop-grain effect.




Quarter Sliced
Produces a striped, often straight-grain effect.



Rift Sliced
Produces a tight, linear grain along the entire length of the veneer.

WOODWORKS® - Standard

VISUAL SELECTION

Edge Profile	Item No. ♦	Dimensions Nominal W x L x H (Inches)	Perforations
WOODWORKS® Regular	5404F01_ _ _ _ _	24 x 24 x 3/4"	W1, W2, W3, W4, W5, W6
9/16" Square Regular	6484F01_ _ _ _ _	12 x 48 x 3/4"	W1, W2, W3, W4, W5, W6
	6485F01_ _ _ _ _	12 x 72 x 3/4"	W1, W2, W3, W4, W5, W6
	6486F01_ _ _ _ _	24 x 48 x 3/4"	W1, W2, W3, W4, W5, W6
	6487F01_ _ _ _ _	24 x 72 x 3/4"	W1, W2, W3, W4, W5, W6
TechZone® Panels	6510F01_ _ _ _ _	24 x 42 x 3/4"	W1, W2, W4
	6511F01_ _ _ _ _	30 x 30 x 3/4"	W1, W2, W4
	6512F01_ _ _ _ _	27 x 30 x 3/4"	W1, W2, W4

FAST
4 WEEKS
or LessFAST134 program items ready to ship from manufacturer in 4 weeks or less.
Up-to-date lead times and product options (sizes and colors) at armstrongceilings.com/fast134

FSC® certified* WOODWORKS Regular	5404F02_ _ _ _ _	24 x 24 x 3/4"	W1, W2, W3, W4, W5, W6	Class A	*	*	*
	6484F02_ _ _ _ _	12 x 48 x 3/4"	W1, W2, W3, W4, W5, W6	Class A	*	*	*
	6485F02_ _ _ _ _	12 x 72 x 3/4"	W1, W2, W3, W4, W5, W6	Class A	*	*	*
	6486F02_ _ _ _ _	24 x 48 x 3/4"	W1, W2, W3, W4, W5, W6	Class A	*	*	*
	6487F02_ _ _ _ _	24 x 72 x 3/4"	W1, W2, W3, W4, W5, W6	Class A	*	*	*
FSC-certified TechZone Panels	6510F02_ _ _ _ _	24 x 42 x 3/4"	W1, W2, W4	Class A	*	*	*
	6511F02_ _ _ _ _	30 x 30 x 3/4"	W1, W2, W4	Class A	*	*	*
	6512F02_ _ _ _ _	27 x 30 x 3/4"	W1, W2, W4	Class A	*	*	*

♦ When specifying or ordering, include the appropriate 2-digit perforation and 3-letter color suffixes.

* FSC-certified wood is a premium option available through ASQuote@armstrongceilings.com

NOTE: Items 6485 and 6487 (12" x 72" and 24" x 72" series) include suspension system stabilizer hooks.

Dots represent high level of performance.

PERFORMANCE

Fire Rating	CleanAssure™ Disinfectable Panels		
	Fog	Spray	Wipe
Class A	*	*	*
Class A	*	*	*
Class A	*	*	*
Class A	*	*	*
Class A	*	*	*
Class A	*	*	*
Class A	*	*	*
Class A	*	*	*

ACOUSTICAL INFORMATION

Perforation	Infill Panel Item No.	Description	NRC	CAC	Total Acoustics¹
W1	Unperforated		N/A	42	
W2	Round Straight	8200T10 Fiberglass	0.45	-	
		1713BL School Zone® Fine Fissured™	0.55	39	
		2820BK Calla®	0.55	37	
		5823 BioAcoustic™	0.40	24	
		5479 BioAcoustic	0.40	24	
		1318 Backstage Noir®	0.55	31	
W3	Round Diagonal	8200T10 Fiberglass	0.45	-	
		1713BL School Zone® Fine Fissured	0.55	39	
		2820BK Calla	0.55	37	
		5823 BioAcoustic	0.40	24	
		5479 BioAcoustic	0.40	24	
		1318 Backstage Noir	0.55	31	
W4	Round Straight	8200T10 Fiberglass	0.60	-	
		1713BL School Zone® Fine Fissured	0.60	39	GOOD
		2820BK Calla	0.65	37	GOOD
		5823 BioAcoustic	0.65	24	
		5479 BioAcoustic	0.65	24	
		1318 Backstage Noir	0.60	31	
W5	Oval Straight Slotted	8200T10 Fiberglass	0.50	-	
		1713BL School Zone® Fine Fissured	0.50	39	
		2820BK Calla	0.55	37	
		5823 BioAcoustic	0.45	24	
		5479 BioAcoustic	0.45	24	
		1318 Backstage Noir	0.55	31	
W6	Oval Straight Slotted	8200T10 Fiberglass	0.40	-	
		1713BL School Zone® Fine Fissured	0.35	39	
		2820BK Calla	0.35	37	
		5823 BioAcoustic	0.45	24	
		5479 BioAcoustic	0.45	24	
		1318 Backstage Noir	0.35	31	

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.




GOOD (NRC 0.60-0.65; CAC 35+)

BETTER (NRC 0.70-0.75; CAC 35+)

BEST (NRC 0.80+; CAC 35+)

EXAMPLE: **5404 F02 W2 NWM**
Panel Dimension/Type: 24" x 24"
Substrate: FSC-certified
Perforation: W2 Round Straight
Finish: Plain Slice White Maple Rg 6006

STANDARD PERFORATION OPTIONS (Actual 1:6 scale shown)

					
W1 (Unperforated)	W2 - Rg 6006 (Round Straight)	W3 - Rd 6006 (Round Diagonal)	W4 - Rg 6011 (Round Straight)	W5 - Lg 9512 (Oval Straight Slotted)	W6 - Lg 9508 (Oval Straight Slotted)

NOTE: Slotted perforations run parallel to the length of the panel and borders vary with panel size.

TechLine 877 276-7876

armstrongceilings.com/woodworksCustom
Perforations
Available

ACCESSORIES


	Item No. ♦	Description	Dimensions Nominal W × L × H (Inches)	Color	PCS/ CTN
Suspension Systems	7501BL	Suprafine® XL® 12' Heavy Duty Main Beam	9/16 × 144 × 1-11/16"	White	20
	XL7549	Suprafine 4' Cross Tee	9/16 × 48 × 1-11/16"	White	60
	XL7520	Suprafine 2' Cross Tee	9/16 × 24 × 1-11/16"	White	60
	7804BL	Angle Molding (recommended with wood trims)	7/8 × 144 × 9/16"	White	30
	7891	12-Gauge Hanger Wire	144" Length	N/A	N/A
Accessories	6091	Safety Cable	N/A	N/A	50
	6408 _ _ _	3/4" Edgebanding	3/4" × 300"	All Veneers	N/A
Infill Panels	1713BL	Fine Fissured™ Lay-in Panel	24 × 24 × 3/4"	Tech Black	14
	2820BK	Calla® Lay-in Panel	24 × 24 × 1"	Black	10
	5479	BioAcoustic™ Infill Panel	24 × 24 × 5/8"	Beige Matte	12
	1318	Backstage Noir® Square Lay-in Panel	24 × 24 × 3/4"	Black	12
	5823	BioAcoustic Infill Panel	24 × 24 × 5/8"	Black Matte	12
	8200T10	Fiberglass Infill Panel	24 × 24 × 1"	Black Gloss	12
Perimeter Trim	5415F01W1H4 _ _ _	4" WoodWorks® Vector®/Tegular Trim with 4 clips (Item 5925)	4 × 96 × 3/4"	All Veneers	4
	5415F01W1H6 _ _ _	6" WoodWorks Vector®/Tegular Trim with 4 clips (Item 5925)	6 × 96 × 3/4"	All Veneers	4
	5925	WoodWorks Trim Clips	N/A	N/A	1 (25 PC minimum order quantity)
	7239	Adjustable Trim Clip	N/A	Mill Finish	50
	AX _ VESTR _ _ _	Axiom® Vector Straight Trim	N/A	Silver Grey, Black, 10 LF Gun Metal	
	AX _ VECUR _ _ _	Axiom Vector Curved Trim	N/A	Silver Grey, Black, 10 LF Gun Metal	
FSC® certified Premium Trim*	5415F02W1H4 _ _ _	4" WoodWorks Vector/Tegular Trim with 4 clips (Item 5925)	4 × 96 × 3/4"	All Veneers	4
	5415F02W1H6 _ _ _	6" WoodWorks Vector/Tegular Trim with 4 clips (Item 5925)	6 × 96 × 3/4"	All Veneers	4

♦ When specifying or ordering, include the 3-digit color suffix that coordinates with your WoodWorks ceiling: (e.g. 5415F01W1H4 N M P)

* FSC-certified wood is a premium option available through ASQuote@armstrongceilings.com.

Axiom Trim also available in multiple colors and profile sizes. For details, visit armstrongceilings.com/axiom

SUSPENSION SYSTEMS (Heavy-duty)

9/16"
Tegular

Silhouette® HD



Suprafine® HD



Interlude® XL® HRC HD

Suprafine suspension system is available in many standard colors. All other suspension systems are available in standard White only. Other colors available as special order.

PHYSICAL DATA

Material

Fire-rated particle board (FRPB) with real wood veneers.
Vertical Grain Fir (NVF) is FRPB with a reconstituted veneer.

Surface Finish

Clear or tinted semi-gloss coating

Fire Performance

Class A: ASTM E84 surface burning characteristics.

Flame Spread Index 25 or less. Smoke Developed
Index 50 or less.CAN/ULC S102 surface burning characteristics. Flame
Spread Rating 25 or less. Smoke Developed Classification
50 or less.

Acoustical Performance

CAC testing conducted using Silhouette
suspension system.

ASTM E1264 Classification

ASTM E1264 Type XX - Fire Class A

Primary (Embodied) Energy

See all LCA information on our EPDs.

Application Considerations

Variation among panels may occur due to the natural
characteristics of the wood and grain.It is very important that WoodWorks panels be climatized prior
to installation. Relative humidity between 25% and 55%, and
temperatures between 50°F and 86°F, must be maintained
throughout the life of the product.

Design Considerations

Different panels should not be installed together. Perforated
border on 24" × 72" panels are different than other
panel sizes.All perforated panels are standard with fleece attached. Panels
without fleece must be specified.

Specification Consideration

Attention: For FSC-certified wood products to maintain their
CoC certification, products must be sold to a CoC-certified
distributor or directly to the installing contractor. Failure to
do so breaks the CoC.

Installation Considerations

Due to panel weight, 24" × 48" and 24" × 72" panels require
that the suspension system be attached to the back with safety
cables attached. 12" × 72" and 24" × 72" panels require the
use of suspension system stabilizer clips (which are included
in the cartons).

Seismic Restraint

WoodWorks Tegular ceiling panels have been engineered, tested,
and approved for application in all seismic areas when installed
per Armstrong Ceilings installation instructions.

Cleaning and Disinfecting

Cleaning and CDC-approved disinfecting options available on
armstrongceilings.com/cleaning

FAST134 Program Considerations

Size of Job Matters: Big jobs, over 2500 SF or 50 pieces
for shapes/vertical elements will have longer lead times.Location Matters: Transit time not included. We are ready
to ship in 1 week on FAST1 items. However, transit to the
states west of Wyoming may add time.Distributor Truck Schedule Matters: We rely on distribution to help
move products around the country. When speed matters, work with
your local distributor to ensure FAST134 service.Stock vs. Made-to-Order Matters: FAST3 & FAST4 items are
made-to-order and will ship direct to distributor. FAST1 (stocked
items) will go through distribution and depend on distributor
truck schedules.

Warranty

Details at armstrongceilings.com/warranty

Weight; Square Feet

Panels – 2.75 LBS/SF