

WOODWORKS®

Wall Panels




FAST134

Select Items Ship Fast
armstrongceilings.com/fast134



CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



Nominal 24" × 72" WoodWorks Wall Panels and 24" × 24" WoodWorks® Vector® panels in Plain Slice White Maple with Axiom® Vector trim in Fern

Wall system available in a variety of wood species, stains, sizes, and perforation options.

KEY SELECTION ATTRIBUTES


- Coordinate veneer choice with WoodWorks® ceilings
- Standard veneers feature various species and cuts for beautiful wood visuals
- ASTM E84 Class A Fire Performance
- The natural warmth of wood can contribute to biophilic designs and building certification standards like the WELL™ v2 "Nature and Place" feature
- Install panels horizontally or vertically using clips or splines
- Perforated panel with acoustical backing improves sound quality and reduces reverberation time within a space
- USDA-certified Biobased Product 100% (preferred for government projects)
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Select products included in the FAST134 program – ready to ship in 4 weeks or less
-  FSC® certified wood available as a premium quoted option (FSC® C007626)

VENEER CUTS


Different cuts of a log will yield different graining visuals. Choose your veneer to achieve your desired look.



Plain Sliced
Produces the well-known cathedral or loop-grain effect.



Quarter Sliced
Produces a striped, often straight-grain effect.



Rift Sliced
Produces a tight, linear grain along the entire length of the veneer.

WOODWORKS®

Wall Panels

USDA
CERTIFIED
BIOBASED
PRODUCT
PRODUCT 100%



RECYCLED
CONTENT

UP TO
80%

LEED V5

COMMON MATERIALS FRAMEWORK

Human Health

Climate Health

Ecosystem Health

Circular Economy

EPD

EPD

OCCUPANT EXPERIENCE

Acoustics



FINISH RANGES

The carefully curated species and veneer cuts offer a beautiful natural variation. The images here reflect the visual range that is likely within our product. Darkest to lightest tones may occur within an installation due to the character of wood.



Plain Slice White Maple (NWM)



Plain Slice White Ash (NWA)



Vertical Grain Fir (NVF)



Rift White Oak (NRO)



Plain Slice White Oak (NOK)



Plain Slice Cherry (NPC)



Quartered Mahogany (NGM)



Quartered Sapele (NQS)



Quartered Walnut (NGW)



Plain Slice Walnut (NWN)

CUSTOM FINISHES



Custom Wood
Species and Finishes
Available

LEGACY VENEERS

Natural Variations™
Plain Slice




Maple (NMP)



Light Cherry (NLC)

Constants™
Vertical Grain



Walnut (CWA)



Redux Wood Wheat (CRW)

Due to printing limitations, shade may vary from actual product.



WOODWORKS®

Wall Panels

USDA
CERTIFIED
BIOBASED
PRODUCT
PRODUCT 100%

RECYCLED
CONTENTUP TO
80%

LEED V5

COMMON MATERIALS FRAMEWORK

Human Health

Climate Health

EPD

Ecosystem Health

EPD

Circular Economy

OCCUPANT EXPERIENCE

Acoustics



VISUAL SELECTION

	Item No. ♦	Dimensions Nominal W × L × H* (Inches)
WOODWORKS® Wall Panels	5814F01_ _E1_ _ _	24 × 48 × 3/4"
(with acoustical fleece)	5818F01_ _E1_ _ _	24 × 96 × 3/4"
Edge: Square (E1) Installation: Z-clip	5819F01_ _E1_ _ _	24 × 108 × 3/4"
	5820F01_ _E1_ _ _	24 × 120 × 3/4"
Edge: Kerfed (E4) Installation: Spline	5814F01_ _E4_ _ _	24 × 48 × 3/4"
	5818F01_ _E4_ _ _	24 × 96 × 3/4"
	5819F01_ _E4_ _ _	24 × 108 × 3/4"
	5820F01_ _E4_ _ _	24 × 120 × 3/4"

FAST
4 WEEKS
or Less

FAST134 program items ready to ship from manufacturer in 4 weeks or less.
Up-to-date lead times and product options (sizes and colors) at armstrongceilings.com/fast134

FSC® certified WOODWORKS Wall Panels	5814F02_ _E1_ _ _	24 × 48 × 3/4"
(with acoustical fleece)	5818F02_ _E1_ _ _	24 × 96 × 3/4"
	5819F02_ _E1_ _ _	24 × 108 × 3/4"
	5820F02_ _E1_ _ _	24 × 120 × 3/4"
Edge: Square (E1) Installation: Z-clip		
Edge: Kerfed (E4) Installation: Spline	5814F02_ _E4_ _ _	24 × 48 × 3/4"
	5818F02_ _E4_ _ _	24 × 96 × 3/4"
	5819F02_ _E4_ _ _	24 × 108 × 3/4"
	5820F02_ _E4_ _ _	24 × 120 × 3/4"

♦ When specifying or ordering, include the appropriate perforation and finish suffixes. (e.g., 5814F01 W 1 E1 N W M)
NOTE: For veneers and sizes available as special order, call TechLine at 1 877 276-7876.

* Panels will be installed with 1/4" or larger gap between panels. When using spline installation, module will be 24".

PERFORMANCE

Dots represent high level of performance.

Fire Performance	CleanAssure™ Disinfectable Panels			
	Fog	Spray	Wipe	
Class A	*	*	*	
Class A	*	*	*	
Class A	*	*	*	
Class A	*	*	*	
Class A	*	*	*	
Class A	*	*	*	
Class A	*	*	*	

ACOUSTICAL INFORMATION

NRC Rating		
D-20 Mounting with acoustical fleece	C-20 Mounting with 1" fiberglass infill **	
Perforation		
W1	N/A	N/A
W2	0.50	0.65
W3	0.50	0.65
W4	0.55	0.80
W5	0.45	0.70
W6	0.45	0.60

** Fiberglass Infill Panel Item 8200T10

WoodWorks Walls perforations align with the following ceiling panels:

Perforation	WoodWorks® Vector®	WoodWorks Concealed
W2	✓	✓
W3	✓	✓
W4	✓	
W5	✓	
W6	✓	



WOODWORKS®

Wall Panels

USDA
CERTIFIED
BIOBASED
PRODUCT
PRODUCT 100%



RECYCLED
CONTENT

UP TO
80%

LEED V5

COMMON MATERIALS FRAMEWORK

Human Health

Climate Health

Ecosystem Health

EPD

EPD

Circular Economy

OCCUPANT EXPERIENCE

Acoustics



ACCESSORIES

	Item No. ♦	Description	Dimensions	Finish/Material	Pieces/Carton	
Finish Accessories*	6481F01W1H_ _ _ _ ♦♦	4", 6", 8" Veneered Trim with 4 Clips – Item 5925 (With Faux Wood Edgebanding on Long Edges)	96" × 3/4"	All Finishes	N/A	
	5849F51_ _ _	Finish Molding (without furring strips)	1.15" × 126"	All Finishes	Bulk	
	5907F51_ _ _	Trim Finish Molding (with furring strips)	1-7/8" × 126"	All Finishes	Bulk	
	5851F51_ _ _	Peak Corner	126"	All Finishes	Bulk	
	5852F51_ _ _	Bullnose Corner	126"	All Finishes	Bulk	
	5855F51_ _ _	4" Base Molding	4" × 95"	All Finishes	Bulk	
	5856F51_ _ _	6" Base Molding	6" × 95"	All Finishes	Bulk	
	585910_	Corner Installation Spline	118"	Plastic (X) or Aluminum (Y)	Bulk	
	5867F51_ _ _	Wall Trim Inside Corner	126"	All Finishes	Bulk	
	6408_ _ _	WoodWorks Edgebanding Coordinating Faux Wood	3/4" × 300"	All Finishes	25 LF	
Installation Components	663910_ _	Wall Installation Spline	120"	Black (BL), Natural Anodized (NA)	Bulk	
	5672	Z-clip	2"	Aluminum	250 PCS/CTN	
	5673	Z-clip Bar	72"	Aluminum	20 PCS/CTN	
Infill Panels	5479	BioAcoustic	24 × 24 × 5/8"	Beige - Matte	12 PCS/CTN	
	8200T10	Fiberglass Infill Panel	24 × 24 × 1"	Black - Gloss	12 PCS/CTN	

♦ When specifying or ordering, include the appropriate 1-, 2-, or 3-letter suffix (e.g., 5855F51 N W M = 4" Base Molding in Plain Slice White Maple).

♦♦ When specifying or ordering, include the height (4, 6, or 8) and 3-letter veneer suffix that coordinates with your WoodWorks ceiling (e.g. 6481F01W1H 4 N W M).

* Finish accessories are solid wood that is stained to coordinate with veneer finishes.

PHYSICAL DATA

Material

Fire-Rated Particle Board (FRPB) with real wood veneers. Vertical Grain Fir (NVF), Constants(TM) Walnut (CWA), and Constants Redux Wood Wheat (CRW) are FRPB with a reconstituted veneer.

Surface Finish

Clear or tinted semigloss coating

Fire Performance

Class A: ASTM E84 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. CAN/ULC S102 surface burning characteristics. Flame Spread Rating 25 or less. Smoke Developed Classification 50 or less.

Application Considerations

Variation among panels may occur due to the natural characteristics of the wood and grain (special order panels available).

It is very important that WoodWorks® panels are climatized prior to installation. Relative humidity between 25% and 55% and temperatures between 50°F and 86°F must be maintained throughout the life of the product.

Design Considerations

The reveal width on WoodWorks® Regular panels and WoodWorks Walls is different. For an application with the same size reveal in the ceiling and on the wall, order custom-cut panels or use Vector® ceiling panels Z-clipped to the wall.

Specification Consideration

Attention: For FSC®-certified wood products to maintain their CoC certification, products must be sold to a CoC-certified distributor or directly to the installing contractor. Failure to do so breaks the CoC.

FAST134 Program Considerations

Size of Job Matters: Big jobs, over 2500 SF or 50 pieces for shapes/vertical elements will have longer lead times.

LEED® is a registered trademark of the U.S. Green Building Council; Living Building Challenge® (LBC) is a registered trademark of the International Living Future Institute; WELL™ and WELL Building Standard™ are trademarks of the International WELL Building Institute; Revit® is a registered trademark of Autodesk, Inc. FSC® is a registered trademark of Forest Stewardship Council®, A.C., license code FSC-C007626; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2025 AWI Licensing LLC

Location Matters: Transit time not included. We are ready to ship in 1 week on FAST1 items. However, transit to the states west of Wyoming may add time.

Distributor Truck Schedule Matters: We rely on distribution to help move products around the country. When speed matters, work with your local distributor to ensure FAST134 service.

Stock vs. Made-to-Order Matters: FAST3 & FAST4 items are made-to-order and will ship direct to distributor. FAST1 (stocked items) will go through distribution and depend on distributor truck schedules.

Warranty

Details at armstrongceilings.com

Weight; Square Feet/Carton

Panels – 2.75 LBS/SF; bulk packaged per order.

TechLine / 1 877 276-7876
armstrongceilings.com/woodworkswalls
BPCS-5098-1025

Armstrong®
World Industries



PARTITIONS & WALLS