



<u>Quarterty:</u>				
Total LF (12'-0" pcs)				
Radius Fascia LF (6'-0	" pcs) (Rad	ius:, (Convex or Concave)	
Vaulted Fascia LF (6'-	0" pcs) (Rad	dius:,	Convex or Concave)	
Standard Accessories:				
Inside Mitered Corner	r(s) (Angle:)		
Outside Mitered Corr	er(s) (Angle	e:)		_
End Closure(s) (Left, F	Right)		-
End Term(s) (Left, Right)				
Sump(s) (Downspout Size:)				
Spillout(s)				
Custom Accessories: (sl	ketches requi	red)		
Special Miters and Zees	·	,		Pro
*All Componets for installing Accessories are included.				
MATERIAL:	THICKN	FSS.		Ho
☐ Pre-Finished Aluminum			□.063	Job Name
				Job #:
☐ Mill Finished Aluminum	□.040	□.050	□.063	Location:
☐ Pre-Finished Steel	□ 24 ga	22 ga		CUSTON
☐ Stainless Steel	☐ 24 ga	□ 22 ga		Authorized
COLOD				Approved
COLOR:				Date:

Quantity:

-	C DIMENSION	H DIMENSION		
-	2-1/2" 4"	5-3/4" 7-1/4"		
- -	5-1/2"	8-3/4"		
-	7" 8-1/2"	10-1/4" 11-3/4"		
ANSI/SPRI ES-1 Tested				

ojects Requirement's prizontal Design Pressure:_____psf

0.10=0.4=0.40	
Location:	Distributor:
Job #:	Representative:
Job Name:	Customer:

CUSTOMER APPROVAL	

Authorized Signature:

Approved by: