



Product Approval
USER: Public User

[Product Approval Menu](#) > **Application Detail**

OFFICE OF THE SECRETARY

FL #	FL20821-R1
Application Type	Affirmation
Code Version	2017
Application Status	Approved
Comments	
Archived	<input type="checkbox"/>
Product Manufacturer	ATAS International, Inc.
Address/Phone/Email	6612 Snowdrift Road Allentown, PA 18106 (610) 395-8445 Ext 223 jbush@atas.com
Authorized Signature	james bush jbush@atas.com
Technical Representative	James E. Bush
Address/Phone/Email	ATAS International, Inc. 6612 Snowdrift Road Allentown, PA 18106 jbush@atas.com
Quality Assurance Representative	James Bush
Address/Phone/Email	6612 Snowdrift Road Allentown, PA 18106 jbush@atas.com
Category	Roofing
Subcategory	Roofing Accessories that are an Integral Part of the Roofing System
Compliance Method	Test Report
Testing Lab	Architectural Testing, Inc York
Quality Assurance Entity	Architectural Testing, Inc., an Intertek Company
Quality Assurance Contract Expiration Date	12/31/2020
Validated By	Steven M. Urich, PE <input type="checkbox"/> Validation Checklist - Hardcopy Received
Certificate of Independence	FL20821_R1_COI_ati_letter_of_ind.pdf
Referenced Standard and Year (of Standard)	Standard ANSI/SPRI/FM 4435/ES-1 Year 2011
Equivalence of Product Standards Certified By	Approved Testing Lab FL20821_R1_Equiv_SPRI ES-1 Equivalency Letter.pdf

I affirm that there are no changes in the new Florida Building Code which affect my product(s) and my product(s) are in compliance with the new Florida Building Code.

Documentation from approved Evaluation or Validation Entity Yes No N/A

Product Approval Method

Method 1 Option B

Date Submitted

03/01/2018

Date Validated

03/01/2018

Date Pending FBC Approval

Date Approved

03/04/2018

Summary of Products

FL #	Model, Number or Name	Description
20821.1	Continuous Cleat Coping	5 1/2" front face height, 4 1/2" back face height, 10" wide. 24 ga. steel
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Rated outward 229 psf and rated upward 397 psf		Installation Instructions FL20821_R1_II_Continuous Cleat Coping - Design Drawing.pdf Verified By: Architectural Testing, Inc York Test Reports FL20821_R1_TR_f1420.01-119-16-r1.pdf
20821.2	Continuous Cleat Coping	5 1/2" front face height, 4 1/2" back face height, 10" wide. .040 aluminum
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Rated outward 231 psf and rated upward 400 psf		Installation Instructions FL20821_R1_II_Continuous Cleat Coping - Design Drawing.pdf Verified By: Architectural Testing, Inc York Test Reports FL20821_R1_TR_f1420.01-119-16-r1.pdf
20821.3	Continuous Cleat Coping	5 1/2" front face height, 4 1/2" back face height, 24 wide. .040 aluminum
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Rated outward 98 psf and rated upward 170 psf		Installation Instructions FL20821_R1_II_Continuous Cleat Coping - Design Drawing.pdf Verified By: Architectural Testing, Inc York Test Reports FL20821_R1_TR_f1420.02-119-16-r0 (2).pdf
20821.4	Continuous Cleat Coping	5 1/2" front face height, 4 1/2" rear face height, 24" wide. .24 ga. steel
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Rated outward 90 psf and rated upward 157 psf		Installation Instructions FL20821_R1_II_Continuous Cleat Coping - Design Drawing.pdf Verified By: Architectural Testing, Inc York Test Reports FL20821_R1_TR_f1420.02-119-16-r0 (2).pdf
20821.5	Drip Edge Fascia	7 3/4" face height, .040 aluminum
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Rated outward 243 psf		Installation Instructions FL20821_R1_II_Drip Edge Fascia - Design Drawing.pdf Verified By: Architectural Testing, Inc York Test Reports FL20821_R1_TR_f1420.02-119-16-r0 (2).pdf
20821.6	Drip Edge Fascia	7 3/4" face height, 24 ga. steel
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Rated outward 230 psf		Installation Instructions FL20821_R1_II_Drip Edge Fascia - Design Drawing.pdf Verified By: Architectural Testing, Inc York Test Reports FL20821_R1_TR_f1420.02-119-16-r0 (2).pdf
20821.7	Edge-Lok 2 Fascia	11 3/4" face height, .040 aluminum
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Rated outward 50 psf		Installation Instructions FL20821_R1_II_Edge Lok 2 Fascia - Design Drawing.pdf Verified By: Architectural Testing, Inc York Test Reports FL20821_R1_TR_f1420.01-119-16-r1.pdf

20821.8	Edge-Lok 2 Fascia	11 3/4" face height, 24 ga. steel
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Rated outward 40 psf		Installation Instructions FL20821_R1_II_Edge Lok 2 Fascia - Design Drawing.pdf Verified By: Architectural Testing, Inc York Test Reports FL20821_R1_TR_f1420.01-119-16-r1.pdf
20821.9	Edge-Lok 3 Fascia	11 3/4" face height, .040 aluminum
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Rated outward 133 psf		Installation Instructions FL20821_R1_II_Edge Lok 3 - Design Drawing.pdf Verified By: Architectural Testing, Inc York Test Reports FL20821_R1_TR_f1420.01-119-16-r1.pdf
20821.10	Edge-Lok 3 Fascia	11 3/4" face height, 24 ga. steel
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Rated outward 140 psf		Installation Instructions FL20821_R1_II_Edge Lok 3 Fascia - Design Drawing.pdf Verified By: Architectural Testing, Inc York Test Reports FL20821_R1_TR_f1420.01-119-16-r1.pdf
20821.11	Gravel Stop	8 1/2" face height, .040 aluminum
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Rated outward 203 psf		Installation Instructions FL20821_R1_II_Gravel Stop Fascia - Design Drawing.pdf Verified By: Architectural Testing, Inc York Test Reports FL20821_R1_TR_f1420.02-119-16-r0 (2).pdf
20821.12	Gravel Stop	8 1/2" face height, 24 ga. steel
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Rated outward 200 psf		Installation Instructions FL20821_R1_II_Gravel Stop Fascia - Design Drawing.pdf Verified By: Architectural Testing, Inc York Test Reports FL20821_R1_TR_f1420.02-119-16-r0 (2).pdf
20821.13	Rapid-Lok Coping	7 1/2 front face height, 5 1/2 back face height, 12 3/4" wide. 24 ga. steel
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Rated outward 60 psf and rated upward 103 psf		Installation Instructions FL20821_R1_II_Rapid Lok Coping - Design Drawing.pdf Verified By: Architectural Testing, Inc York Test Reports FL20821_R1_TR_f1420.01-119-16-r1.pdf
20821.14	Rapid-Lok Coping	7 1/2: front face height, 5 1/2" back face height, 12 3 /4" wide. .040 aluminum
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Rated outward 67 psf and rated upward 117 psf		Installation Instructions FL20821_R1_II_Rapid Lok Coping - Design Drawing.pdf Verified By: Architectural Testing, Inc York Test Reports FL20821_R1_TR_f1420.01-119-16-r1.pdf
20821.15	Rapid-Lok Coping	7 1/2" front face height, 5 1/2" back face heath, 32" wide. 24 ga. steel
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Rated outward 25 psi and rated upward 43 psf		Installation Instructions FL20821_R1_II_Rapid Lok Coping - Design Drawing.pdf Verified By: Architectural Testing, Inc York Test Reports FL20821_R1_TR_f1420.02-119-16-r0 (2).pdf
20821.16	Rapid-Lok Coping	7 1/2" front face, 5 1/2" back face, 32" wide. .040 aluminum
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Rated outward 29 psf and rated upward 50 psf		Installation Instructions FL20821_R1_II_Rapid Lok Coping - Design Drawing.pdf Verified By: Architectural Testing, Inc York Test Reports FL20821_R1_TR_f1420.02-119-16-r0 (2).pdf

20821.17	Rapid-Lok Fascia	5 1/2 face height, 24 ga. steel
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Rated outward 593 psf		Installation Instructions FL20821 R1 II Rapid Lok Fascia - Design Drawing.pdf Verified By: Architectural Testing, Inc York Test Reports FL20821 R1 TR f1420.01-119-16-r1.pdf
20821.18	Rapid-Lok Fascia	11 1/2" face height, 24 ga. steel
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Rated outward 133 psf		Installation Instructions FL20821 R1 II Rapid Lok Fascia - Design Drawing.pdf Verified By: Architectural Testing, Inc York Test Reports FL20821 R1 TR f1420.02-119-16-r0 (2).pdf
20821.19	Rapid-Lok Fascia	5 1/2" face height, .040 aluminum
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Rated outward 490 psf		Installation Instructions FL20821 R1 II Rapid Lok Fascia - Design Drawing.pdf Verified By: Architectural Testing, Inc York Test Reports FL20821 R1 TR f1420.01-119-16-r1.pdf
20821.20	Rapid-Lok Fascia	11 1/2" face height, .040 aluminum
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: N/A Other: Rated outward 167 psf		Installation Instructions FL20821 R1 II Rapid Lok Fascia - Design Drawing.pdf Verified By: Architectural Testing, Inc York Test Reports FL20821 R1 TR f1420.02-119-16-r0 (2).pdf

[Back](#)
[Next](#)

[Contact Us](#) :: 2601 Blair Stone Road, Tallahassee FL 32399 Phone: 850-487-1824

The State of Florida is an AA/EEO employer. [Copyright 2007-2013 State of Florida.](#) :: [Privacy Statement](#) :: [Accessibility Statement](#) :: [Refund Statement](#)

Under Florida law, email addresses are public records. If you do not want your e-mail address released in response to a public-records request, do not send electronic mail to this entity. Instead, contact the office by phone or by traditional mail. If you have any questions, please contact 850.487.1395. *Pursuant to Section 455.275(1), Florida Statutes, effective October 1, 2012, licensees licensed under Chapter 455, F.S. must provide the Department with an email address if they have one. The emails provided may be used for official communication with the licensee. However email addresses are public record. If you do not wish to supply a personal address, please provide the Department with an email address which can be made available to the public. To determine if you are a licensee under Chapter 455, F.S., please click [here](#).

Product Approval Accepts: