



Quantity:					
Total LF (12'-0" pcs)					
Radius Fascia LF (6'-0	" pcs) (Rad	ius:, (Convex or Concave)		
Vaulted Fascia LF (6'-	0" pcs) (Rad	dius:,	Convex or Concave)		
Standard Accessories:					
Inside Mitered Corner	(s) (Angle:)			
Outside Mitered Corr	-	С			
End Closure(s) (-				
End Term(s) (Le	-				
Sump(s) (Downspout	-				
Spillout(s)	-				
Custom Accessories: (sl		ANSI/S			
Special Miters and Zees	_	Projects Requirer			
*All Componets for installing Acc	_	Horizontal Design			
MATERIAL:	THICKN	ESS:			
Pre-Finished Aluminum	□.0 4 0	 050	□.063	Job Name:	
☐ Mill Finished Aluminum	□ 040		□.063	Job #:	
				Location:	
☐ Pre-Finished Steel	□ 24 ga	□ 22 ga		CUSTOMER APP	PROV
☐ Stainless Steel	☐ 24 ga	☐ 22 ga		Authorized Signatu	ıre: _
COLOD				Approved by:	
COLOR:				Date:	

-	C DIMENSION	H DIMENSION				
- - -	2-1/2" 4" 5-1/2"	6" 7-1/2" 9"				
-	7" 8-1/2"	10-1/2" 12"				
ANSI/SPRI ES-1 Tested						
Projects Requirement's Horizontal Design Pressure:psf						
Job Name:	Customer	Customer:				
Job #:	Represen	Representative:				
Location:	Distributo	Distributor:				
CUSTOMER APPROVAL						
Authorized Signature:						
Approved by:						
Date:						