





Quantity: Total LF (12'-0" pcs)	)" non) (Dad	iuc.				
Radius Fascia LF (6'-0" pcs) (Radius:, Convex or Concave) Vaulted Fascia LF (6'-0" pcs) (Radius: , Convex or Concave)				-	C DIMENSION	H DIMENSION
Standard Accessories:         Inside Mitered Corner(s) (Angle:         Outside Mitered Corner(s) (Angle:				- - -	2-1/2" 4" 5-1/2" 7"	4" 5-1/2" 7" 8-1/2"
Custom Accessories: (sketches required) Special Miters and Zees *All Componets for installing Accessories are included.				ANSI/SPRI ES-1 Tested Projects Requirement's Horizontal Design Pressure:psf		
MATERIAL:	THICKN □ .040	Job Name:     Customer:       Job #:     Representative:				
Mill Finished Aluminum	040	.050	.063	Location:	Distributor:	
Pre-Finished Steel	🗌 24 ga	□ 22 ga		CUSTOMER APPROVAL		
Stainless Steel	_ 24 ga	□ 22 ga		Authorized Signature:		
COLOR:				Approved by: Date:		

eadquarters - 6612 Snowdrift Road - Allentown, PA 18106 - Phone: +1 800-468-1441 www.atas.com