ATLAS[®] UNDERLAYMENTS & STEEP SLOPE ACCESSORIES

PREFERRED BY ROOFING PROFESSIONALS.

Atlas has you covered on every part of the job, even what goes under your roofing. We are proud to offer the largest and most innovative variety of premium underlayment and roll-roofing products. They are manufactured to ensure easy installation as well as to perfectly complement virtually all roofing systems.



DATA SHEET

TER GRANULAR

3050



ROOF UNDERLAYMENTS

WORLD'S LARGEST PRODUCER OF **ROOFING UNDERLAYMENTS**



Atlas offers homeowners increased coverage of their Premium Protection Period on any Atlas Signature Select® Roofing System. Qualifying Atlas Signature Select® Underlayments and Accessories are listed on the back of this data sheet and can be identified by this 🌐 mark. For more information please visit: www.AtlasSignatureSelect.com



In order to qualify for the Lifetime Algae Warranty, installation must include Pro-Cut® Hip and Ridge featuring Scotchgard[™] Protector with Atlas Pristine shingles featuring Scotchgard[™] Protector.

CORPORATE SALES & MARKETING 2000 RiverEdge Parkway, Suite 800 Atlanta, Georgia 30328

www.ATLASROOFING.com

SALES OFFICES

Ardmore, OK (800) 261-2852 FAX (580) 223-6894 Daingerfield, TX (800) 270-2852 FAX (903) 645-2291

FAX (937) 746-6040

Franklin, OH

(800) 260-2852

Hampton, GA (800) 251-2852 FAX (770) 946-5249

PRO-CUT- STARTER STRIP

Meridian, MS (800) 933-2721 FAX (601) 483-7344



Made in U.S.A.

	Product	ASTM	FL Code Approved	MIAMIDADE COUNTY APPROVED		Description	Width	Length	Approx. Ro Coverage
Glass	Fiber Reinforced Asphalt S	aturated Felt							
Î	Gorilla Guard [®] EVERFELT [™] 30	D 6757	FL 11915	Yes	Engineered Underlayment		36"	141.5'	4 Squares
Î	Gorilla Guard [®] EVERFELT [™] SPEC 30	D 6757	FL 16226	Yes	Engineered Underlayment		36"	72'	2 Squares
Synth	etic Shingle Underlayment								
Î	Summit [®] Synthetic	D 6757	FL 11915	Dade Product Control Approved		en Polypropylene Fabric with UV & esistive Coatings, 180-Day Exposure	48"	250'	10 Square
Î	Summit [®] 60 Synthetic	D 6757	_	-	Woven Polypropylene Fabric with UV & Water Resistive Coatings, 60-Day Exposure		48"	250'	10 Square
BS P	eel and Stick Underlaymen	t							
Î	WeatherMaster [®] Granular	D 1970	FL 11915	Dade Product Control Approved	Peel & Stick, Granular Surfaced SBS Reinforced Underlayment	36"	33.3'	1 Square	
-						36"	72.1'	2 Square	
Î	WeatherMaster® 100 [†]	D 1970	FL 11915	Dade Product Control Approved	Peel & Stick, Granular Surfaced SBS Reinforced Underlayment		36"	33.3'	1 Square
Î	WeatherMaster® 200 [†]	D 1970	FL 11915	Dade Product Control Approved	Peel & Stick, Granular Surfaced		36"	66.6'	2 Square
Î	WeatherMaster [®] PolySeal ^{™ †}	D 1970	FL 11915	Dade Product Control Approved	Peel & Stick, Polysurfaced, High Temp, SBS Modified Asphalt Roof Underlayment		36"	66.6'	2 Square
Î	WeatherMaster® Film	D 1970	-	-	Film Surfaced, SBS Modified Self- Adhesive Membrane Reinforced With Non-Woven Fiberglass Mat		36"	66.6'	2 Square
Î	WeatherMaster [®] TU Ultra [†]	D 1970	FL 11915	Dade Product Control Approved	Peel & Stick, Woven Polyester Surfaced SBS, Heavy Tile Underlayment		36"	72'	2 Square
ÎÌ	WeatherMaster®	D 1970			Versatile Glass Fiber Valley Underlayment		36"	33.3'	1 Square
1	Valley Liner [†]	D 1970	_	_			36"	66.6'	2 Square
tand	ard Asphalt Saturated Orga	nic Felt		1					
-	#15 Saturated Felt	D 4869 Type I	FL 11915	N/A	Standard Shingle Underlayment Saturated Felt		36"	144'	4 Square
-	#30 Saturated Felt	D 4869 Type I	FL 11915	N/A	Heavy Shingle Underlayment Saturated Felt		36"	72'	2 Square
peci	ication Asphalt Saturated C	Drganic Felt							
-	#15 Specification Felt	D 4869 Type II, D 226 Type I	FL 11915	Yes	Specification Shingle Underlayment Saturated Felt		36"	144'	4 Square
_	#30 Specification Felt	D 4869 Type IV, D 226 Type II	FL 11915	Yes	Specification Shingle & Tile Underlayment Saturated Felt		36"	72'	2 Square
hing	le Starter Products								
					6 <u>x</u>	For use with up to 6" exposure	7 1⁄2"*	36"*	118 Lineal
	Atlas Pro-Cut [®] Starter Strip With FASTAC [®] Sealant	-	Yes	Yes	6xr	For use with up to 6" exposure	7 1⁄5"	33' 4"	33' 4" Ro
					8.5x	For use with up to 81/2" exposure	10½"	2211/16"	79 Lineal
					10 X	For use with up to 10" exposure	12"	36"	78 Lineal
	Ridge Shingle to qualify for the Lifetime Algae Wa	arranty, installation must	include Pro-Cut® Hir	o and Ridge featuring	Scotchgar	I [™] Protector with Atlas Pristine shingles featu	ring Scote	ngard [™] Protec	tor.
Î	Atlas Pro-Cut [®] Hip & Ridge featuring Scotchgard [™] Protector	D 3462, D 3018 Type I	Yes	Yes	Scotchgard Protector with Atlas Pristine shingles featu Matching all Pinnacle® Pristine featuring Scotchgard™ Protector, StormMaster® Shake, StormMaster® Slate & ProLam™ Shingles		12"	12"	31 Lineal Coverag