


Roofing Products Reference Guide

SHINGLES/UNDERLAYMENT/ACCESSORIES

Signature Select®
Roofing System



Product Features At A Glance

Roof Shingles

[illegible]

Roof Shingle Accessories

	StormMaster® Hip & Ridge Shingles	Pro-Cut® High Profile Hip & Ridge Shingles	Pro-Cut® Hip & Ridge Shingles	ProLam™ Hip & Ridge Shingles	Pro-Cut® Starter Shingles
Colors	Colors to match StormMaster® shingles	Colors to match Atlas shingles	Colors to match Atlas shingles	Colors to match ProLam™ shingles	N/A
Warranty	Standard Limited Warranty**	Standard Limited Warranty**	Standard Limited Warranty**	Standard Limited Warranty**	N/A
Impact Rating	Class 4 UL 2218 Impact Resistance	—	Class 3 UL 2218 Impact Resistance	—	—
Asphalt Technology	Core4® Technology Modified Asphalt	SBS Modified Asphalt	Standard Shingle Asphalt	Standard Shingle Asphalt	Standard Shingle Asphalt
System Warranty	Signature Select® Eligible ¹	Signature Select® Eligible ¹	Signature Select® Eligible ¹	Signature Select® Eligible ¹	Signature Select® Eligible ¹
Algae Protection	3M™ Scotchgard™ Protector ²	3M™ Scotchgard™ Protector ²	3M™ Scotchgard™ Protector ²	Algae Resistant Shingle (ARS)	N/A

Roof Underlayment

	Summit® 180	Summit® 60	Gorilla Guard® 30	WeatherMaster®	Felt
Type	Premium Quality Synthetic Roof Underlayments	Premium Quality Synthetic Roof Underlayments	Engineered Underlayment - 36% Lighter than Traditional Organic Felt Underlayment	Ice & Water - SBS-Modified Asphalt Membrane	ATSM 4869 Organic Asphalt Saturated Felt
Exposure	180-day exposure to UV	60-day exposure to UV	—	Up to 180 day exposure to UV ³	—
System Warranty	Signature Select® Eligible ¹	Signature Select® Eligible ¹	Signature Select® Eligible ¹	Signature Select® Eligible ¹	—

Roof Ventilation


[illegible]

Atlas Designer Shingles

For lasting protection against black streaks caused by algae, install shingles featuring the Atlas Lifetime* Algae Resistance Limited Warranty.

StormMaster® Shake

Premium Protection with Exclusive Core4® Technology



Length: 42" / 1066.8 mm
Width: 14" / 355.6 mm
Exposure: 6" / 152.4 mm
Shingles Per Bundle: 18-20



10 COLORS

Aspen Grove
Black Shadow
Chestnut
Copper Canyon
Grand Teton
Midnight Beach
Midnight Lake
Morning Harvest
Pewter
Weathered Wood

FEATURES

Scotchgard™ Protector
3M™ Smog-Reducing Technology
150 mph Wind Limited Warranty**
FASTAC® Double Sealant Lines
Manufactured Using Core4®
Polymer Modified Technology
Class 4 Impact Resistance - UL 2218
Atlas Lifetime* Algae Resistance
Limited Warranty
Lifetime Limited Warranty**
Atlas Signature Select® Eligible¹

ASTM

D7158, Class H Wind Resistance,
Passed at 150 mph
D6381, Uplift Resistance
D3018, Type 1
D3161, Class F, Tested at 110 mph
D3462, As Manufactured
E108, Class A Fire Resistance

UL


2218, Class 4 Impact Resistance
790, Class A Fire Resistance

CODES AND COMPLIANCES

Meets AC438 Criteria
CAN/CSA-A123.5-M90
Florida Building Code Approved – FL 16305
Miami-Dade County Product
Control Approved

Pinnacle® Impact

Lasting Beauty that Weathers the Storm



Length: 42" / 1066.8 mm
Width: 14" / 355.6 mm
Exposure: 6" / 152.4 mm
Shingles Per Bundle: 18-20



6 COLORS

Black Shadow IR
Desert Shake IR
Hearthstone IR
Heather IR
Pewter IR
Weathered Wood IR

FEATURES

Scotchgard™ Protector
3M™ Smog-Reducing Technology
Class 4 Impact Resistance - UL 2218
130 mph Wind Limited Warranty**
FASTAC® Double Sealant Lines
Enhanced Polymer Technology
Atlas Lifetime* Algae Resistance
Limited Warranty
Lifetime Limited Warranty**
Atlas Signature Select® Eligible¹

ASTM

D7158, Class H Wind Resistance,
Passed at 150 mph
D6381, Uplift Resistance
D3018, Type 1
D3161, Class F, Tested at 110 mph
D3462, As Manufactured
E108, Class A Fire Resistance

UL


2218, Class 4 Impact Resistance
790, Class A Fire Resistance

CODES AND COMPLIANCES

Meets AC438 Criteria
CAN/CSA-A123.5-M90
Florida Building Code Approved – FL 16305
Miami-Dade County Product
Control Approved

Pinnacle® Sun

Cool Roof Technology that Fights Smog



Length: 42" / 1066.8 mm
Width: 14" / 355.6 mm
Exposure: 6" / 152.4 mm
Shingles Per Bundle: 18-20



6 COLORS

Cool Coastal Cliffs
Cool Coral Canyon
Cool Driftwood
Cool Moonlight Beach
Cool Sand
Cool Surf

FEATURES

Scotchgard™ Protector
3M™ Cooling Technology
3M™ Smog-Reducing Technology
Class 3 Impact Resistance - UL 2218
130 mph Wind Limited Warranty**
FASTAC® Double Sealant Lines
Atlas Lifetime* Algae Resistance
Limited Warranty
Lifetime Limited Warranty**
Atlas Signature Select® Eligible¹

ASTM

D7158, Class H Wind Resistance,
Passed at 150 mph
D6381, Uplift Resistance
D3018, Type 1
D3161, Class F, Tested at 110 mph
D3462, As Manufactured
E108, Class A Fire Resistance
E1980, Solar Reflectance

UL

2218, Class 3 Impact Resistance
790, Class A Fire Resistance

CODES AND COMPLIANCES

Meets AC438 Criteria
CAN/CSA-A123.5-M90
Florida Building Code Approved – FL 16305
Miami-Dade County Product
Control Approved




#AtlasProtects



A Brand You
Know And Trust
Scotchgard™ Protector
25+ years of proven
performance.

Pinnacle® Pristine

High Performance Meets Lasting Beauty



Length: 42" / 1066.8 mm
Width: 14" / 355.6 mm
Exposure: 6" / 152.4 mm
Shingles Per Bundle: 18-20



16 COLORS

Black Shadow
Burnt Hickory
Coastal Granite
Copper Canyon
Hearthstone
Heather
Majestic Shake
Morning Harvest
Oyster Shell
Pewter
Summer Storm
Sunset
Tan Mist
Weathered Shadow
Weathered Wood
Woodland Green

FEATURES

Scotchgard™ Protector
Class 3 Impact Resistance - UL 2218
130 mph Wind Limited Warranty**
FASTAC® Double Sealant Lines
Atlas Lifetime* Algae Resistance
Limited Warranty
Lifetime Limited Warranty**
Atlas Signature Select® Eligible¹

ASTM

D7158, Class H Wind Resistance,
Passed at 150 mph
D6381, Uplift Resistance
D3018, Type 1
D3161, Class F, Tested at 110 mph
D3462, As Manufactured
E108, Class A Fire Resistance

UL


2218, Class 3 Impact Resistance
790, Class A Fire Resistance

CODES AND COMPLIANCES

Meets AC438 Criteria
CAN/CSA-A123.5-M90
Florida Building Code Approved – FL 16305
Miami-Dade County Product
Control Approved

ProLam™

Exceptional Value in a Designer Look



Length: 42" / 1066.8 mm
Width: 14" / 355.6 mm
Exposure: 6" / 152.4 mm
Shingles Per Bundle: 18-20



7 COLORS

Black Shadow
Desert Shake
Hearthstone
Hickory
Pewter
Weathered Shadow
Weathered Wood

FEATURES

Up To 130 mph Wind
Limited Warranty**
Algae Resistant Shingle
Lifetime Limited Warranty**
3M™ Ceramic-Coated Granules
Atlas Signature Select® Eligible¹

ASTM

D7158, Class H Wind Resistance,
Passed at 150 mph
D6381, Uplift Resistance
D3018, Type 1
D3161, Class F, Tested at 110 mph
D3462, As Manufactured
E108, Class A Fire Resistance

UL


790, Class A Fire Resistance

CODES AND COMPLIANCES

Meets AC438 Criteria
CAN/CSA-A123.5-M90
Florida Building Code Approved – FL 16305
Miami-Dade County Product
Control Approved

GlassMaster®

Classic Style. Proven Performance.



Length: 36" / 914.4 mm
Width: 12" / 304.8 mm
Exposure: 5" / 127 mm
Shingles Per Bundle: 26



3 COLORS

Black Shadow
Hearthstone Gray
Weathered Wood

FEATURES

60 mph Wind Limited Warranty**
30-Year Limited Warranty**
Algae-Resistant Shingle
3M™ Ceramic-Coated Granules
Atlas Signature Select® Eligible¹

ASTM

D7158, Class H Wind Resistance,
Passed at 150 mph
D6381, Uplift Resistance
D3018, Type 1
D3161, Type 1, Class F,
Tested at 110 mph
D3462, As Manufactured
E108, Class A Fire Resistance

UL

790, Class A Fire Resistance

CODES AND COMPLIANCES

Meets AC438 Criteria
CAN/CSA-A123.5-M90
Florida Building Code Approved – FL 16305
Miami-Dade County Product
Control Approved



Dreaming of a Home Redesign?


Get creative with the Roof Inspiration Center, a suite of home design tools from Atlas. Whether you have 3 minutes or 30, your new look is just around the corner.

AtlasRoofing.com/Roof-Inspiration

Hip & Ridge Shingles

StormMaster®

Hip & Ridge Shingles Featuring Core4®



Dimensions: 10" x 11 1/2"
Exposure: Up to 5 5/8"
Coverage: 20 Linear Feet
Shingles Per Package: 66



COLORS

To match Atlas shingles

FEATURES

Scotchgard™ Protector
Manufactured Using Core4®
Polymer Modified Technology
Atlas Lifetime* Algae Resistance
Limited Warranty
Lifetime Limited Warranty**
Class 4 Impact Resistance - UL 2218
Atlas Signature Select® Eligible¹

UL


2218, Class 4 Impact Rating
790, Class A Fire Resistance

CODES AND COMPLIANCES

Class A Fire Resistance (UL R21860)
Wind Resistance (UL 997)
CAN/CSA-A123.5-M90
Florida Building Code Approved – FL 16305
Miami-Dade County Product
Control Approved

Pro-Cut®

High Profile
Hip & Ridge Shingles



Dimensions: 10" x 11 1/2"
Exposure: 8 1/4"
Coverage: 20 Linear Feet
Shingles Per Package: 30



COLORS

To match Atlas shingles

FEATURES


Scotchgard™ Protector
Manufactured Using SBS Asphalt
Atlas Lifetime* Algae Resistance
Limited Warranty
Lifetime Limited Warranty**
Atlas Signature Select® Eligible¹

CODES AND COMPLIANCES

Class A Fire Resistance (UL R21860)
Wind Resistance (UL 997)
CAN/CSA-A123.5-M90

Pro-Cut®

Hip & Ridge Shingles



Dimensions: 12" x 12"
Exposure: 5 5/8"
Coverage: 31 Linear Feet
Shingles Per Package: 66



COLORS

To match Atlas shingles

FEATURES

Scotchgard™ Protector
Class 3 Impact Resistance - UL 2218
Atlas Lifetime* Algae Resistance
Limited Warranty
Lifetime Limited Warranty**
Atlas Signature Select® Eligible¹

ASTM


D3018, Type 1
D3161, Type 1, Class F, Tested at 110 mph
D3462, As Manufactured
E108, Class A Fire Resistance

UL

2218, Class 3 Impact Resistance
790, Class A Fire Resistance

CODES AND COMPLIANCES

Meets AC438 Criteria
CAN/CSA-A123.5-M90
Florida Building Code Approved – FL 16305
Miami-Dade County Product
Control Approved




Signature Select®
ROOFING SYSTEM

Starter Shingles

ProLam™

Hip & Ridge Shingles



Dimensions: 12" x 12"
Exposure: Up to 5 5/8"
Coverage: 31 Linear Feet
Shingles Per Package: 66



LIFETIME



ARS



SYSTEM

COLORS

Black Shadow
Desert Shake
Hearthstone
Hickory
Pewter
Weathered Wood

FEATURES

Algae Resistance Limited Warranty
130 mph Wind Limited Warranty**
Atlas Signature Select® Eligible¹

ASTM

D3018, Type I
D3161, Type I, Class F, Tested at 110 mph
D3462, As Manufactured
E108, Class A Fire Resistance

UL


790, Class A Fire Resistance

CODES AND COMPLIANCES

Meets AC438 Criteria
CAN/CSA-A123.5-M90
Florida Building Code Approved – FL 16305
Miami-Dade County Product
Control Approved

Pro-Cut® HP42™

Starter Shingles



Shingle Dimensions: 8" x 42"
Exposure Limits: Up To 6"
Per Bundle: 140 Linear Feet

ASTM

D3018, Type I
D3161, Type I, Class F, Tested at 110 mph
D3462 As Manufactured

CODES AND COMPLIANCES

Florida Building Code Approved – FL 16305
Miami-Dade County Product
Control Approved



SYSTEM

Pro-Cut®

6" Starter Shingle Roll

Roll Dimensions: 7.2" x 33' 4"
Exposure Limits: Up To 6"
Per Roll: 33' 4"

ASTM

D3018, Type I
D3161, Type I, Class F, Tested at 110 mph
D3462 As Manufactured
D1970

CODES AND COMPLIANCES

Florida Building Code Approved – FL 16305
Miami-Dade County Product
Control Approved



SYSTEM

Pro-Cut®

9" Universal Starter Shingle Roll

Roll Dimensions: 9" x 33' 6"
Exposure Limits: Up To 9"
Per Roll: 33' 4"

ASTM

D3018, Type I
D3161, Type I, Class F, Tested at 110 mph
D3462 As Manufactured
D1970

CODES AND COMPLIANCES

Florida Building Code Approved – FL 16305
Miami-Dade County Product
Control Approved



SYSTEM

Demand Peak Coverage

When you install an Atlas Signature Select® Roofing System¹, all the components are designed for and backed by the industry's best warranty coverage.

Unlike many other roofing warranties that over promise and under deliver, Atlas packs value and assurance into an enhanced premium protection period, which includes non-prorated labor and materials, tear-off and disposal fees, coverage of the full Atlas product system, and transferability.

Signature Select® Roofing System Components:

- 1 Atlas Ice & Water Underlayment
- 2 Atlas Premium Underlayment
- 3 Atlas Starter Shingles
- 4 Atlas Roof Shingles
- 5 Atlas Ventilation Products
- 6 Atlas Hip & Ridge Shingles

* In order to qualify for the Atlas Lifetime Algae Resistance Limited Warranty against black streaks caused by blue-green algae, installation must include StormMaster® Hip & Ridge shingles featuring Scotchgard™, Pro-Cut® Hip & Ridge shingles featuring Scotchgard™ Protector or Pro-Cut® High Profile Hip & Ridge shingles featuring Scotchgard™ Protector with Atlas shingles featuring Scotchgard™ Protector.

** Refer to the Atlas Roofing Limited Shingle Warranty for all coverage requirements.

¹ Refer to the Atlas Signature Select® Limited Warranty for all system coverage requirements.

² Helps resist the black streaks caused by algae.

³ WeatherMaster® Tile - 180 Days, WeatherMaster® Pro-Grade - 90 Days WeatherMaster® 200 - 45 Days, WeatherMaster® Flexible - 30 Days.

Scotchgard™ and the Scotchgard™ Protector logo, including the plaid design and 3M™ logo, are all trademarks of 3M.

Roof Ventilation

TruRidge® ROOF VENTILATION

TruRidge® Standard Exhaust Vent



Length: 4' Width: 12"
Exterior baffle product
Standard with nails

TruRidge® All-Weather Exhaust Vent



Length: 4' Width: 12"
Exterior baffle product
Standard with filter & nails

TruRidge® PRO 25 Roll Exhaust Vent



25'(L) x 14-3/4"(W) x 5/8"(H)
Low Profile. Standard with coil nails

HighPoint® ROOF VENTILATION

HighPoint® Performance Ridge Exhaust Vent




Length: 4' Width: 12"
Firm, pliable design ensures and maintains proper
orientation of baffle
Standard with filter & nails

HighPoint® Invisaridge™ Exhaust Vent



Length: 4' Width: 12"
Virtually invisible from any angle
Standard with nails

HighPoint® Intake Vent




Length: 4' Width: 10"
Intake ventilation for homes without soffits
Standard with filter

HighPoint® AL 50 Slant Back Box Vent



One-Piece Base/Throat, Round Throat, Louvered
Choice of aluminum or galvanized steel construction
Available in Black, Weathered Wood and Brown

HighPoint® GL 50 Slant Back Box Vent



One-Piece Base/Throat, Round Throat, Louvered
Choice of aluminum or galvanized steel construction
Available in Black, Weathered Wood and Brown

HighPoint® Power Vent HT



25.63" H x 25.31" W x 8.56" D
Standard with Pre-Wired Humidistat and Thermostat
Available in Black and Weathered Wood

SBS Peel & Stick Premium Underlayments

WeatherMaster® Pro-Grade Ice & Water 200

Fabric-Faced High-Temp Underlayment



Length: 66.8'
Width: 36"
2 Square Roll Provides Approximately
200 sq. ft. of Material

CODES AND COMPLIANCES

Underwriters Laboratories Class A and
Class C Fire Rating – Based on Roof Covering
ASTM D1970, Ice Dam and Metal Underlayment
ICC-ES Report ER 1783
Florida Building Code Approved - FL 17322
Miami-Dade County Product
Control Approved

CLIMATE-SOURCE.COM/ER1783

WeatherMaster® Flexible Ice & Water

Film-Faced High-Temp Underlayment



Length: 66.8'
Width: 36"
2 Square Roll Provides Approximately
200 sq. ft. of Material

CODES AND COMPLIANCES

Underwriters Laboratories Class A and
Class C Fire Rating – Based on Roof Covering
ASTM D1970, Standard Ice Dam Underlayment
Florida Building Code Approved - FL 17322

WeatherMaster® Ice & Water 200

Granular Shingle Underlayment



Length: 65'
Width: 36"
1.95 Square Roll Provides Approximately
195 sq. ft. of Material

CODES AND COMPLIANCES

Underwriters Laboratories Class A and
Class C Fire Rating – Based on Roof Covering
ASTM D1970, Standard Ice Dam Underlayment
ICC-ES Report ER 1783
Florida Building Code Approved - FL 17322
Miami-Dade County Product
Control Approved

CLIMATE-SOURCE.COM/ER1783

WeatherMaster® Tile

Stackable High-Temp Underlayment



Length: 72'
Width: 36"
2 Square Roll Provides Approximately
216 sq. ft. of Material

CODES AND COMPLIANCES

Underwriters Laboratories Class A and
Class C Fire Rating – Based on Roof Covering
ASTM D1970, Premium Ice Dam and Tile
Underlayment
Florida Building Code Approved - FL 17322
Miami-Dade County Product
Control Approved

CLIMATE-SOURCE.COM/ER1783

Premium Synthetic Underlayments

Summit® 180

Premium Synthetic Underlayment



Length: 250'
Width: 48"
Square Per Roll Coverage: 10
Coverage with 4" Lap: 917 sq. ft.


CODES AND COMPLIANCES

ASTM D8257, Mechanically Attached
Polymeric Roof Underlayment Used in
Steep Slope Roofing
AC 207, UV Exposure for 180 Days
AC 207, Accelerated Aging
ASTM E108, Fire Resistance
ASTM D6757, Inorganic Shingle
Underlayment Standard
UL 790, Fire Resistance
UL Classified as a Prepared
Roofing Accessory
Florida Building Code Approved - FL 21350
Miami-Dade County Product
Control Approved

CLIMATE-SOURCE.COM/ER1783

Summit® 60

Premium Synthetic Underlayment



Length: 250'
Width: 48"
Square Per Roll Coverage: 10
Coverage with 4" Lap: 917 sq. ft.

CODES AND COMPLIANCES

ASTM D8257, Mechanically Attached
Polymeric Roof Underlayment Used in
Steep Slope Roofing
AC 207, UV Exposure for 60 Days
AC 207, Accelerated Aging
ASTM E108, Fire Resistance
ASTM D6757, Inorganic Shingle
Underlayment Standard
UL 790, Fire Resistance
UL Classified as a Prepared
Roofing Accessory
Florida Building Code Approved - FL 21350
Miami-Dade County Product
Control Approved

CLIMATE-SOURCE.COM/ER1783

Felt Underlayments

#15 Organic Asphalt Saturated Felt



Length: 144'
Width: 36"
Square Per Roll Coverage: 4
Square Feet Per Roll: 432

CODES AND COMPLIANCES

ASTM D4869, Type 1
Florida Building Code Approved - FL 17322

Gorilla Guard® 30

Engineered Underlayment



Length: 141.5'
Width: 36"
Square Per Roll Coverage: 4
Coverage with 2" Lap: 400 sq. ft.

CODES AND COMPLIANCES

UL Classified as a Roofing
Accessory
ASTM D6757
Florida Building Code Approved -
FL 17322
Meets Performance Characteristics of
ASTM D4869 (#15 & #30 Standard)
and ASTM D226 Type I



AtlasRoofing.com

#AtlasProtects