


GRIP-TWIST® NC BOLT CONNECTOR

COLD-SWAGED BOLT CONNECTOR COUPLER WITH UNC THREADS

- POSITIVE CONNECTION BETWEEN REINFORCEMENT AND THREADED RODS / BOLTS
- FULL STRENGTH OF BAR MAINTAINED
- FOR LOAD TRANSFER BETWEEN STEEL STRUCTURES AND CONCRETE
- BOLT CONNECTORS MADE FROM WELDABLE GRADE OF STEEL
- PRECAST PANEL CONSTRUCTION – Can be used in conjunction with BPI® Barsplicer XP threaded rebar to easily and safely assemble precast panels.

THREADED ROD/BOLTS SPECIAL APPLICATIONS STRUCTURAL ANCHORING PRECAST ASSEMBLY LIFTING APPLICATIONS AS A HEADED DEVICE



NC FEMALE GRIP-TWIST® CONNECTOR				DIMENSIONS (in)					
REBAR SIZE US [Metric]	UNC THREAD SIZE*	WEIGHT (lbs)	SWAGING DIE SET COLOR CODE	Connector Outside Dia.	Bar Insertion After Swaging F	Final Length After Swaging L	Thread Length T	End Allowance A	Non-Swaged Length N
#3 [10]	1/2 – 13	0.19	ORANGE	3/4	1 3/8	2 3/8	5/8	1	1 1/8
#4 [13]	1/2 – 13	0.30	PINK	7/8	1 3/4	2 15/16	3/4	1 3/16	1 5/16
	5/8 – 11	0.27							
#5 [16]	5/8 – 11	0.58	RED	1 1/8	2 1/4	3 9/16	1 1/8	1 3/8	1 9/16
	3/4 – 10	0.53							
#6 [19]	3/4 – 10	1.09	YELLOW	1 3/8	2 3/4	4 1/4	1 1/4	1 9/16	1 13/16
	7/8 – 9	1.02							
#7 [22]	7/8 – 9	1.62	BLUE	1 9/16	3 1/8	4 15/16	1 1/2	1 7/8	2 1/8
	1 – 8	1.54							
#8 [25]	1 – 8	2.31	BLACK	1 3/4	3 9/16	5 5/8	1 3/4	2 1/8	2 3/8
	1 1/8 – 7	2.19							
#9 [29]	1 1/8 – 7	3.17	RED	1 15/16	4	6 3/8	2	2 7/16	2 3/4
	1 1/4 – 7	3.05							
#10 [32]	1 1/4 – 7	4.45	YELLOW	2 3/16	4 1/2	7 3/16	2 1/4	2 3/4	3 1/8
	1 3/8 – 6	4.10							
#11 [36]	1 1/4 – 7	5.62	BLUE	2 3/8	4 7/8	7 5/8	2 3/8	2 3/4	3 1/8
	1 3/8 – 6	5.39							
	1 1/2 – 6	5.31							
#14 [43]	1 1/2 – 6	10.3	PINK	2 7/8	6 1/16	9 3/8	2 7/8	3 5/16	3 7/8
	1 3/4 – 5	9.75							
	2 – 4 1/2	9.47							
#18 [57]	1 3/4 – 5	25.6	RED	3 7/8	7 7/8	12 1/8	3 5/8	4 5/16	5 1/16
	2 1/2 – 4	23.6							

* OTHER SIZES AVAILABLE UPON REQUEST

ALL DIMENSIONS ARE APPROXIMATE

While the information contained in this document is believed to be accurate at the time of publication, BPI reserves the right to make changes, design modifications, corrections and other revisions as it sees fit, without notice. All products described herein are supplied in accordance with BPI's standard Terms and Conditions of Sale. This document is of a promotional nature only. Aspects of structural design, evaluation of product fitness for use, suitability or similar attributes are the responsibility of others.



DOWNLOAD THE FREE BARSPlice APP AND FOLLOW US ON SOCIAL MEDIA!



Barsplice Products, Inc., 4900 Webster Street, Dayton OH 45414, USA
Tel: 937-275-8700 • www.barsplice.com • e-mail: bar@barsplice.com



Copyright © 2023, Barsplice Products, Inc., "BPI". All rights reserved.