



Boise Cascade
Engineered Wood Products

VERSA-STUD® 1.7 2650 FLYER

for product manufactured in Alexandria [Lena], Louisiana.



Stronger

Straighter

Stiffer

Longer

Better homes from better builders —
by design . . .
with **VERSA-STUD®** wall framing

VERSA-STUD 1.7 2650
EAST 5/05/2008 R
07/19/11

VERSA-STUD® 1.7 2650 FLYER

for product manufactured in Alexandria [Lena], Louisiana

Engineered Studs for Tall Walls

VERSA-STUD® 1.7 2650 laminated veneer lumber wall framing is engineered for the high quality builder who wants . . .

- Stronger walls to resist wind loads
- Stiffer walls for a solid feel
- Straight walls for a high quality finish

Long, continuous **VERSA-STUD® 1.7 2650** wall framing to provide superior strength, stiffness, and appearance in any tall wall application. **VERSA-STUD® 1.7 2650** wall framing provides more resistance to wind pressure than walls framed with dimension lumber and eliminates the hinge created by platform framing. 1½" x 5½" **VERSA-STUD® 1.7 2650** wall framing has 2.3 times more bending strength than No. 2 SPF 2x6 studs.



Available from better lumber yards in lengths up to 24 feet

1½" VERSA-STUD 1.7 2650 Allowable Design Values

Product	Bending F _b [psi] ^{(1) (2)}	Compression Parallel to Grain F _c [psi] ⁽¹⁾	Horizontal Shear F _v [psi] ⁽¹⁾	Modulus of Elasticity E [psi]
VERSA-STUD® 1.7 2650 1½"x5½"	3005	3000	285	1,700,000
Spruce Pine Fir (North) #1 / #2 Grade 2x6	1310	1150	135	1,400,000
Hem-Fir #2 Grade 2x6	1270	1300	150	1,300,000
Western Woods #2 Grade 2x6	1010	900	135	1,000,000

(1) Load duration factor may be applied to design stresses.

(2) Repetitive member and size factors have been applied to bending stresses.

— Design values are for loads applied to the narrow face of the studs

— Dimension lumber values taken from 2001 Edition, *NDS Lumber Values for Wood Construction* (per 2003 IBC/IRC).

1½" VERSA-STUD 1.7 2650 Design Properties

Width [in]	Depth [in]	Weight [lb/ft]	Allowable Shear [lb]	Allowable Moment [lb-ft]	Moment of Inertia (I) [in ⁴]
1½	3½	1.5	998	776	5.4
1½	5½	2.4	1568	1821	20.8
1½	7¼	3.2	2066	3069	47.6
1½	9¼	4.0	2636	4862	98.9
1½	11¼	4.9	3206	7008	178.0

For information about Boise Cascade's engineered wood products, including sales terms and conditions, warranties and disclaimers,

visit our website at www.BCewp.com