

USES

- Used in concrete flatwork as a control or construction joint
- Tongue & Groove design provides excellent load transfer characteristics
- Used as a screed rail to finish the concrete



ADVANTAGES

- QuicKey™ is only galvanized joint system that features knockouts for square dowels, which provide better load transfer over round dowels & also reduces edge curl on the slab.
- Knockouts sizes meet both ACI and PCA recommendations for the design of tongue and groove key joint
- Saves on installation time... stake quickly interlocks at any point with key joint, reducing to place stakes precisely.
- Stiffened ribs are designed for increased rigidity while installing
- LOCKING-TAB™ stakes provide a positive interlock between stake & key joint to eliminates floating or rising from the stake, minimizing high spots.
- Stake profile features a non-twist design with allows the stake to be driven at a straight angle



Video

MATERIAL

- QuicKey™ Keyway is made from 24 gauge G60 HDMG Steel
- Square knockouts every 6 inches
- Available in 10ft lengths for 4", 5", 6", 8" & 10-12" slabs
- LOCKING-TAB™ Stakes takes are made from 14-gauge HRPO steel
- Available in 12" (QK12), 15" (QK15), 18" (QK18), 24 (QK24) & 30" (QK30) lengths
- Removable and Non-Removable Keyway caps are made from Flexible PVC materials

