



Bostik, Inc.
11320 West Watertown Plank Road
Wauwatosa, WI 53226
Telephone: 800.726.7845
Fax: 414.774.8775
Inquiry: inquiry@bostik-us.com
Website: <http://www.bostik.com/us>

This product guide specification is based on the Construction Specifications Institute (CSI) *Project Delivery Guide*, *Construction Specifications Practice Guide*, *MasterFormat®*, *SectionFormat™*, and *PageFormat™*. This product guide specification is a manufacturer-specific proprietary product specification using the proprietary method of specifying applicable to master guide specifications and project specifications. Text requiring decisions are indicated by brackets []; delete unused text in the final copy of the specification.

Revise the section number and title to suit project requirements, specification practices and section content. Refer to CSI *MasterFormat®* for other section numbers and titles.

SECTION 09 30 00.29

TILING - MASTIC

PART 1 - GENERAL

1.1 SUMMARY

- A. Section Includes: Epoxy modified grout and mortar admixture.

1.2 SUBMITTALS

- A. Product Data: Manufacturer's technical product data including manufacturer's installation instructions.

1.3 DELIVERY, STORAGE, AND HANDLING

- A. Deliver and store packaged materials in original containers with seals unbroken and labels intact until time of use.
- B. Store materials on elevated platforms, under cover, and in a dry location.

1.4 FIELD CONDITIONS

- A. Environmental Limitations: Do not install materials until construction in spaces is complete and ambient temperature and humidity conditions are maintained at the levels indicated in referenced standards and manufacturer's written instructions.

PART 2 - PRODUCTS

2.1 MANUFACTURER

- A. Manufacturer: Bostik, Inc., 11320 West Watertown Plank Road, Wauwatosa, WI 53226, Telephone: 800.726.7845, Fax: 414.774.8775, Inquiry: inquiry@bostik-us.com, Website: www.bostik.com/us.

2.2 ADMIXTURE

Specifier Note: Retain paragraph below for proprietary method specification. Use of such phrases as “or equal” or “or approved equal” or similar phrases may cause ambiguity in specifications. Such phrases require verification (procedural and regulatory) and assignment of responsibility for determining “or equal” products.

- A. Product: 1900™.
 - 1. Description: Epoxy modified admixture for mixing with Hydroment® Dry Tile Grout™ (Sanded).
 - 2. Physical Properties: When mixed with Hydroment® Dry Tile Grout™ (Sanded) complies with ANSI A118.8.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine substrates, areas, and conditions where materials will be installed, with Installer present, for compliance with requirements for installation tolerances and other conditions affecting performance of the Work.
- B. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 PREPARATION

- A. Comply with manufacturer’s written instructions, including product technical bulletins and product package instructions.

3.3 INSTALLATION

- A. Comply with ANSI A108 and manufacturer’s written instructions, including product technical bulletins and product package instructions.
- B. Mixing: Mix with mortar and grout only according to manufacturer’s written instructions.

END OF SECTION