



Safety Data Sheet

915SS
915 Sealant Series

Revision Date 04-May-2016
Supersedes Date: No information available
Version 1.01

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Product Name 915 Sealant Series
Product Code 915SS
Product(s) Covered See section 16 for more information

1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended use No information available.
Uses Advised Against No information available

1.3. Details of the Supplier of the Safety Data Sheet

Company Name
Bostik, Inc.
11320 W. Watertown Plank Road
Wauwatosa, Wisconsin 53226 USA
Phone: +1 (800) 843-0844 (Domestic Toll Free)
Phone: +1 (414) 774-2250 (International)
Fax: +1 (414) 774-8075
Email: msds@bostik-us.com

1.4. Emergency Telephone Number

Emergency Telephone Telephone: 1-800-227-0332
(Outside U.S.) 1-703-527-3887

Section 2: HAZARD IDENTIFICATION

2.1. Classification of the Substance or Mixture

Respiratory sensitization	Category 1
Carcinogenicity	Category 2
Flammable Liquids	Category 4

2.2. Label Elements

EMERGENCY OVERVIEW

DANGER

Hazard statements

May cause allergy or asthma symptoms or breathing difficulties if inhaled
Suspected of causing cancer
Combustible liquid

Safety Data Sheet

915SS
915 Sealant Series

Revision Date 04-May-2016
Supersedes Date: No information available
Version 1.01



Appearance No information available **Physical State** Liquid **Odor** Solvent

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Avoid breathing dust/fume/gas/mist/vapors/spray
In case of inadequate ventilation wear respiratory protection
Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
In case of fire: Use CO₂, dry chemical, or foam to extinguish.

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards Not Otherwise Classified (HNOC)

Not applicable

Unknown Toxicity

40.86% of the mixture consists of ingredient(s) of unknown toxicity

2.3. Other Information

Causes mild skin irritation.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable

3.2 Mixtures

Chemical Name	CAS No	Weight-%
Limestone	1317-65-3	10 - 30
Polyvinyl chloride	9002-86-2	10 - 30
Titanium dioxide	13463-67-7	1 - 5
Propylene carbonate	108-32-7	1 - 5
Stearic acid	57-11-4	1 - 5
Iron hydroxide oxide	20344-49-4	1 - 5
m-Xylene	108-38-3	1 - 5
Benzenesulfonyl isocyanate, 4-methyl-	4083-64-1	0.1 - 1
p-Xylene	106-42-3	0.1 - 1

Safety Data Sheet

915SS
915 Sealant Series

Revision Date 04-May-2016
Supersedes Date: No information available
Version 1.01

Carbon black	1333-86-4	0.1 - 1
Ethylbenzene	100-41-4	0.1 - 1
Quartz	14808-60-7	0.1 - 1

The exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

General Advice	If symptoms persist, call a physician.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin Contact	Immediate medical attention is not required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Inhalation	Immediate medical attention is not required. If symptoms persist, call a physician. Move to fresh air in case of accidental inhalation of vapors or decomposition products.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a physician. Do NOT induce vomiting.
Self-protection of the First Aider	Use personal protective equipment as required.

4.2. Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms No information available.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

Note to physicians Treat symptomatically.

4.4. Reference to Other Sections

Reference to Other Sections Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION
Section 11: TOXICOLOGY INFORMATION

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media

Use. Dry chemical. Carbon dioxide (CO₂). Water spray (fog). Alcohol resistant foam.

Unsuitable Extinguishing Media

CAUTION: Use of water spray when fighting fire may be inefficient.

5.2. Special Hazards Arising from the Substance or Mixture

Specific Hazards Arising from the Chemical

Keep product and empty container away from heat and sources of ignition. Risk of ignition.

Explosion Data

Sensitivity to Mechanical Impact None.

Safety Data Sheet

915SS
915 Sealant Series

Revision Date 04-May-2016
Supersedes Date: No information available
Version 1.01

Sensitivity to Static Discharge None.

5.3. Advice for Firefighters

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions Use personal protective equipment as required. Remove all sources of ignition. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Pay attention to flashback. Take precautionary measures against static discharges.

6.2. Environmental Precautions

Environmental Precautions Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. See Section 12 for additional Ecological Information.

6.3. Methods and Material for Containment and Cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning up Soak up with inert absorbent material. Dam up. Pick up and transfer to properly labeled containers. Take precautionary measures against static discharges.

6.4. Reference to other sections

Reference to Other Sections Section 7: HANDLING AND STORAGE
Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION
Section 13: DISPOSAL CONSIDERATIONS

Section 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Advice on Safe Handling Use with local exhaust ventilation. All equipment used when handling the product must be grounded. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

7.2. Conditions for Safe Storage, including any Incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat. Keep in properly labeled containers.

Incompatible Materials None known based on information supplied.

7.3. Specific End Use(s)

Other Information No information available.

7.4. References to Other Sections

Safety Data Sheet

915SS
915 Sealant Series

Revision Date 04-May-2016
Supersedes Date: No information available
Version 1.01

Reference to Other Sections Section 13: DISPOSAL CONSIDERATIONS
Section 10: STABILITY AND REACTIVITY

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

Exposure Guidelines

. As Titanium dioxide (13463-67-7) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses. As Limestone CAS 1317-65-3 is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses. As Quartz (14808-60-7) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses. As Carbon black (1333-86-4) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses.

Chemical Name	ACGIH TLV	NIOSH IDLH	OSHA PEL	Mexico
Limestone 1317-65-3	-	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ STEL: 20 mg/m ³
Polyvinyl chloride 9002-86-2	TWA: 1 mg/m ³ respirable fraction	-	-	-
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	IDLH: 5000 mg/m ³	TWA: 15 mg/m ³ total dust	TWA: 10 mg/m ³ STEL: 20 mg/m ³
Iron hydroxide oxide 20344-49-4	TWA: 1 mg/m ³ Fe	TWA: 1 mg/m ³ Fe	-	TWA: 1 mg/m ³ STEL: 2 mg/m ³
m-Xylene 108-38-3	STEL: 150 ppm TWA: 100 ppm	IDLH: 900 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 150 ppm STEL: 655 mg/m ³	-	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 150 ppm STEL: 655 mg/m ³
p-Xylene 106-42-3	STEL: 150 ppm TWA: 100 ppm	IDLH: 900 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 150 ppm STEL: 655 mg/m ³	-	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 150 ppm STEL: 655 mg/m ³
Carbon black 1333-86-4	TWA: 3 mg/m ³ inhalable fraction	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH	TWA: 3.5 mg/m ³	TWA: 3.5 mg/m ³ STEL: 7 mg/m ³
Ethylbenzene 100-41-4	TWA: 20 ppm	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³	TWA: 100 ppm TWA: 435 mg/m ³	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust	: (30)/((%SiO ₂ + 2) mg/m ³ TWA total dust : (250)/((%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/((%SiO ₂ + 2) mg/m ³ TWA respirable fraction	TWA: 0.1 mg/m ³

Chemical Name	Argentina	Brazil	Chile	Venezuela
Limestone 1317-65-3	TWA: 10 mg/m ³	-	TWA: 8 mg/m ³	-
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	-	-	TWA: 10 mg/m ³
Iron hydroxide oxide	TWA: 1 mg/m ³	-	-	TWA: 1 mg/m ³

Safety Data Sheet

915SS
915 Sealant Series

Revision Date 04-May-2016
Supersedes Date: No information available
Version 1.01

20344-49-4				
m-Xylene 108-38-3	TWA: 100 ppm STEL: 150 ppm	-	-	Skin STEL: 150 ppm TWA: 100 ppm
p-Xylene 106-42-3	TWA: 100 ppm STEL: 150 ppm	-	-	Skin STEL: 150 ppm TWA: 100 ppm
Carbon black 1333-86-4	TWA: 3.5 mg/m ³	-	-	TWA: 3.5 mg/m ³
Ethylbenzene 100-41-4	TWA: 100 ppm STEL: 125 ppm	TWA: 78 ppm TWA: 340 mg/m ³	TWA: 80 ppm TWA: 348 mg/m ³	Skin STEL: 125 ppm TWA: 100 ppm
Quartz 14808-60-7	TWA: 0.05 mg/m ³	-	TWA: 0.08 mg/m ³	TWA: 0.025 mg/m ³

8.2. Exposure Controls

Engineering Controls

Showers
Eyewash stations
Ventilation systems.

Personal protective equipment [PPE]

Eye/Face Protection

Tight sealing safety goggles.

Skin and Body Protection

Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.

Respiratory Protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations

When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	Liquid
Color	Multiple Colors
Odor	Solvent
Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting Point/Freezing Point	No information available	
Boiling Point	No information available	
Flash Point	74.4 °C / 165.9 °F	
Evaporation Rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper Flammability Limit	No information available	
Lower Flammability Limit	No information available	
Vapor Pressure	No information available	
Vapor Density	No information available	
Specific Gravity	No information available	
Water Solubility	No information available	
Solubility in Other Solvents		
Partition Coefficient	No information available	
Autoignition Temperature	No information available	

Safety Data Sheet

915SS
915 Sealant Series

Revision Date 04-May-2016
Supersedes Date: No information available
Version 1.01

Decomposition Temperature No information available
Kinematic Viscosity No information available

Dynamic Viscosity No information available
Explosive Properties No information available
Oxidizing Properties No information available

9.2. Other Information

Softening Point No information available
Molecular Weight No information available
Solvent Content (%) No information available
Solid Content (%) 96.0
Density 1.2-1.4 g/cm³
VOC 2.8 %

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

None under normal use conditions.

10.2. Chemical Stability

Stable under recommended storage conditions.

10.3. Possibility of Hazardous Reactions

None under normal processing.

10.4. Conditions to Avoid

Heat, flames and sparks.

10.5. Incompatible Materials

None known based on information supplied.

10.6. Hazardous Decomposition Products

None known based on information supplied.

Section 11: TOXICOLOGY INFORMATION

11.1. Information on Toxicological Effects

Product Information No Data Available
Inhalation No Data Available.
Eye contact No Data Available.
Skin Contact No Data Available.
Ingestion No Data Available.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Limestone 1317-65-3	>5000 mg/kg (rat)	-	-
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-

Safety Data Sheet

915SS
915 Sealant Series

Revision Date 04-May-2016
Supersedes Date: No information available
Version 1.01

Propylene carbonate 108-32-7	= 29000 mg/kg (Rat)	> 20 mL/kg (Rabbit)	-
Stearic acid 57-11-4	>5000 mg/Kg	> 5 g/kg (Rabbit)	-
Iron hydroxide oxide 20344-49-4	> 10000 mg/kg (Rat)	-	Dust 6H >195g/m ³
m-Xylene 108-38-3	= 5 g/kg (Rat)	= 14100 µL/kg (Rabbit)	-
Benzenesulfonyl isocyanate, 4-methyl- 4083-64-1	= 2234 mg/kg (Rat)	-	> 640 ppm (Rat) 1 h
p-Xylene 106-42-3	= 4029 mg/kg (Rat)	-	= 4550 ppm (Rat) 4 h = 4740 ppm (Rat) 4 h
Carbon black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 1432 mg/L (Rat) 4 h
Quartz 14808-60-7	>2000 mg/kg (Rat)	-	-

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

Symptoms	No information available.
Skin Corrosion/Irritation	No information available.
Serious Eye Damage/Eye Irritation	No information available.
Irritation	No information available.
Corrosivity	No information available.
Sensitization	No information available.
Germ Cell Mutagenicity	No information available.
Reproductive Toxicity	No information available.
Developmental Toxicity	No information available.
Teratogenicity	No information available.
STOT - Single Exposure	No information available.
STOT - Repeated Exposure	No information available.
Chronic Toxicity	May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects.
Target Organ Effects	Blood, Central nervous system, Eyes, Gastrointestinal tract (GI), Kidney, Liver, Lungs, Respiratory system, Skin.
Aspiration Hazard	No information available.
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen. As Titanium dioxide (13463-67-7) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses. As Quartz (14808-60-7) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses. As Carbon black (1333-86-4) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses.

Chemical Name	ACGIH	IARC	NTP	OSHA
Polyvinyl chloride 9002-86-2	-	Group 3	-	-
Titanium dioxide 13463-67-7	-	Group 2B	-	X
m-Xylene 108-38-3	-	Group 3	-	-
p-Xylene 106-42-3	-	Group 3	-	-
Carbon black 1333-86-4	A3	Group 2B	-	X
Ethylbenzene 100-41-4	A3	Group 2B	-	X

Safety Data Sheet

915SS
915 Sealant Series

Revision Date 04-May-2016
Supersedes Date: No information available
Version 1.01

Quartz 14808-60-7	A2	Group 1	Known	X
----------------------	----	---------	-------	---

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Confirmed animal carcinogen with unknown relevance to humans

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
Limestone 1317-65-3	CE50 (72h) >200mg/L Algae (Desmodesmus subspicatus)	CL50 (96h)>10000mg/L Fish (Oncorhynchus mykiss)		CE50 (48h) >1000 mg/L Daphnia Magna
Propylene carbonate 108-32-7	EC50 72 h > 500 mg/L (Desmodesmus subspicatus)	LC50 96 h = 5300 mg/L (Leuciscus idus static) LC50 96 h > 1000 mg/L (Cyprinus carpio semi-static)	EC50 > 10000 mg/L 17 h	EC50 48 h > 500 mg/L (Daphnia magna)
m-Xylene 108-38-3	EC50 72 h = 4.9 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h 14.3 - 18 mg/L (Pimephales promelas flow-through) LC50 96 h = 12.9 mg/L (Poecilia reticulata semi-static) LC50 96 h = 8.4 mg/L (Oncorhynchus mykiss semi-static)		EC50 48 h 2.81 - 5.0 mg/L (Daphnia magna Static)
p-Xylene 106-42-3	EC50 72 h = 3.2 mg/L (Pseudokirchneriella subcapitata) EC50 3 h = 105.1 mg/L (Chlorella vulgaris)	LC50 96 h = 2.6 mg/L (Oncorhynchus mykiss static) LC50 96 h = 2.6 mg/L (Oncorhynchus mykiss) LC50 96 h = 8.8 mg/L (Poecilia reticulata semi-static) LC50 96 h 7.2 - 9.9 mg/L (Pimephales promelas static)	EC50 = 5.7 mg/L 30 min	EC50 48 h 3.55 - 6.31 mg/L (Daphnia magna Static)
Carbon black 1333-86-4	>10000 mg/l (Desmodesmus subspicatus) OECD 202	>1000 mg/l (Brachydanio rerio) OCDE 203		EC50 24 h > 5600 mg/L (Daphnia magna)
Ethylbenzene 100-41-4	EC50 96 h > 438 mg/L (Pseudokirchneriella subcapitata) EC50 96 h 1.7 - 7.6 mg/L (Pseudokirchneriella subcapitata) EC50 72 h = 4.6 mg/L (Pseudokirchneriella subcapitata) EC50 72 h 2.6 - 11.3 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h = 32 mg/L (Lepomis macrochirus static) LC50 96 h 11.0 - 18.0 mg/L (Oncorhynchus mykiss static) LC50 96 h 7.55 - 11 mg/L (Pimephales promelas flow-through) LC50 96 h = 4.2 mg/L (Oncorhynchus mykiss semi-static) LC50 96 h 9.1 - 15.6 mg/L (Pimephales promelas static) LC50 96 h = 9.6 mg/L (Poecilia reticulata static)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50 48 h 1.8 - 2.4 mg/L (Daphnia magna)

Safety Data Sheet

915SS
915 Sealant Series

Revision Date 04-May-2016
Supersedes Date: No information available
Version 1.01

12.2. Persistence and Degradability

No information available.

12.3. Bioaccumulative Potential

No information available.

12.4. Mobility in Soil

No information available.

12.5 Other adverse effects

No information available

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

Disposal of Wastes

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations

Contaminated Packaging

Dispose of in accordance with federal, state and local regulations

Section 14: TRANSPORTATION INFORMATION

Note:

49 CFR 173.150(f)(2) "The requirements in this subchapter do not apply to a material classed as a combustible liquid in a non-bulk packaging unless the combustible liquid is a hazardous substance, a hazardous waste, or a marine pollutant."

DOT

UN/ID No	NA1993
Hazard Class	Combustible liquid
Packing Group	III
Special Provisions	IB3, T1, T4, TP1
Description	NA1993, Combustible liquid, n.o.s. (Xylenes), Combustible liquid, III,
Emergency Response Guide Number	128

IATA

Not regulated

IMDG

Not regulated

Section 15: REGULATORY INFORMATION

Global Inventories

TSCA	Listed
DSL	Not Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

Listed - The components of this product are either listed or exempt from listing on inventory.

Safety Data Sheet

915SS
915 Sealant Series

Revision Date 04-May-2016
Supersedes Date: No information available
Version 1.01

Not Listed - One or more components of this product are not listed on inventory.

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class

B3 - Combustible liquid
D2A - Very toxic materials



United States of America

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No
m-Xylene	108-38-3
Ethylbenzene	100-41-4

SARA 311/312 Hazard Categories

Acute Health Hazard	yes
Chronic Health Hazard	yes
Fire Hazard	yes
Sudden release of pressure hazard	No
Reactive Hazard	No

California Proposition 65

This product contains one or more of the substances listed on Proposition 65 at or above 0.01 wt. %

Chemical Name	CAS No
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	68515-49-1
Titanium dioxide	13463-67-7
Carbon black	1333-86-4
Ethylbenzene	100-41-4
Quartz	14808-60-7

Europe

Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead (7439-92-1), Cadmium (7440-43-9), Mercury (7439-97-6), Hexavalent chromium (7440-47-3), Polybrominated biphenyls (PBB), and Polybrominated diphenyl ethers (PBDE) above the regulated limit mentioned in this regulation.

EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Section 16: OTHER INFORMATION

Product(s) Covered

Safety Data Sheet

915SS
915 Sealant Series

Revision Date 04-May-2016
Supersedes Date: No information available
Version 1.01

A27000-95	915 WHITE	52GL
A27000-95L	915 wht MD52GL/P3 VARWT	
A27038	915 WHITE BLNK FOIL S/P 12/20.	

HMIS **Health Hazards 2*** **Flammability 2** **Physical Hazards 0** **Personal Protection X**

Key or Legend to Abbreviations and Acronyms Used in the Safety Data Sheet

No information available

Key Literature References and Sources for Data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision Date 04-May-2016

Revision Note Not applicable.

Training Advice No information available

Additional information No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet