



**915FS**  
**915 Fast Set Series**

**Revision Date** 08-Oct-2015  
**Supersedes Date:** No information available  
**Version** 1.03

## Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product Identifier

<b>Product Name</b>	915 Fast Set Series
<b>Product Code</b>	915FS
<b>Product(s) Covered</b>	
A77800	BOS 915 FS WHITE 24/10.1
A77800-95L	BOS915FS/WHT/DRM/52GL/VW/LB/3P
A77805	BOS 915 FS CAPITOL TAN 24/10.1
A77805-95L	BS915FS/CAPTAN/DR/52GL/VRWT/3P
A77810	BOS 915 FS BLACK 24/10.1
A77810-95	BOSTIK 915FS, BLACK, 52GL DRUM
A77810-95L	BOS 915FS/BLK/DR/52GL/VRWLB/3P
A77820	BOS 915 FS STONE 24/10.1
A77820-95L	BS915FS/STN/DRM/52GL/VRWTLB/3P
A77830	BOS 915 FS MED BRONZE 24/10.1
A77830-95L	B915FS/MEDBRZ/DR/52GL/VRWLB/3P
A77840	BOS 915 FS TER COTTA 24/10.1
A77840-95L	B915FS/TERACTA/DR/52GL/VRWT/3P
A77850	BOS 915 FS BRONZE 24/10.1
A77850-95L	BOS915FS/BRONZ/DR/52GL/VRWT/3P
A77860	BOS 915 FS ANTQ WHITE 24/10.1
A77860-95L	BOS915FS/ATQWH/DR/52GL/VRWT/3P
A77870	BOS 915 FS ALUM GRAY 24/10.1
A77870-95L	915FS/ALGRY/DRM/52GL/VRWTLB/3P
A77880	BOS 915 FS LIMESTONE 24/10.1
A77880-7C	BOS 915 FS LIMESTONE 5 GL PAIL
A77880-95L	BOS915FS/LMSTN/DR/52GL/VRWT/3P
A77890	BOS 915 FS LIGHT GRAY 24/10.1
A77890-95L	BS915FS/LTGRY/DR/52GL/VRWLB/3P
A77900	915 FAST SET WHITE S/PK12/20
A77905	915 FAST SET CAP TAN S/PK12/20
A77910	915 FAST SET BLACK S/PK12/20
A77920	915 FAST SET STONE S/PK12/20
A77930	915 FAST SET MDBROZ S/PK12/20
A77940	915 FAST SET TERACOTA S/P12/20
A77950	915 FAST SET BRONZE S/PK12/20
A77960	915 FAST SET ANTQWHT S/PK12/20
A77970	915 FAST SET ALMGRAY S/PK12/20
A77980	915 FAST SET LIMESTN S/PK12/20
A77990	915 FAST SET LT GREY S/PK12/20

### 1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

<b>Recommended use</b>	No information available.
<b>Uses Advised Against</b>	No information available

### 1.3. Details of the Supplier of the Safety Data Sheet

# Safety Data Sheet

915FS  
915 Fast Set Series

Revision Date 08-Oct-2015  
Supersedes Date: No information available  
Version 1.03

## Company Name

Bostik, Inc.  
11320 W. Watertown Plank Road  
Wauwatosa, Wisconsin 53226 USA  
Phone: +1 (800) 843-0844 (Domestic Toll Free)  
Phone: +1 (414) 774-2250 (International)  
Fax: +1 (414) 774-8075  
Email: msds@bostik-us.com

## 1.4. Emergency Telephone Number

Emergency Telephone Telephone: 1-800-227-0332  
(Outside U.S.) 1-703-527-3887

## Section 2: HAZARD IDENTIFICATION

### 2.1. Classification of the Substance or Mixture

Respiratory sensitization	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 2
Flammable Liquids	Category 4

### 2.2. Label Elements

## EMERGENCY OVERVIEW

### DANGER

#### Hazard Statements

May cause allergy or asthma symptoms or breathing difficulties if inhaled  
May cause an allergic skin reaction  
Suspected of causing cancer  
Combustible liquid



**Appearance** No information available      **Physical State** Liquid      **Odor** Solvent

#### Precautionary Statements - Prevention

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Avoid breathing dust/fume/gas/mist/vapors/spray  
In case of inadequate ventilation wear respiratory protection  
Contaminated work clothing should not be allowed out of the workplace  
Wear protective gloves  
Keep away from heat/sparks/open flames/hot surfaces. — No smoking

#### Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

# Safety Data Sheet

915FS  
915 Fast Set Series

Revision Date 08-Oct-2015  
Supersedes Date: No information available  
Version 1.03

Specific treatment (see first aid measures on this label)

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam to extinguish.

## Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

## Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

## Hazards Not Otherwise Classified (HNOC)

Not applicable

## Unknown Toxicity

53.65% of the mixture consists of ingredient(s) of unknown toxicity

## 2.3. Other Information

Causes mild skin irritation.

## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical Name	CAS No	Weight-%
Polyvinyl chloride	9002-86-2	10 - 30
Limestone	1317-65-3	5 - 10
Titanium dioxide	13463-67-7	1 - 5
Propylene carbonate	108-32-7	1 - 5
m-Xylene	108-38-3	1 - 5
Iron hydroxide oxide	20344-49-4	1 - 5
Benzenesulfonyl isocyanate, 4-methyl-	4083-64-1	0.1 - 1
p-Xylene	106-42-3	0.1 - 1
Carbon black	1333-86-4	0.1 - 1
Isophorone diisocyanate	4098-71-9	0.1 - 1
Ethylbenzene	100-41-4	0.1 - 1

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

## Section 4: FIRST AID MEASURES

### 4.1. Description of First Aid Measures

#### General Advice

If symptoms persist, call a physician.

#### Eye contact

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.

#### Skin Contact

Immediate medical attention is not required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

#### Inhalation

Immediate medical attention is not required. If symptoms persist, call a physician. Move to

# Safety Data Sheet

915FS  
915 Fast Set Series

Revision Date 08-Oct-2015  
Supersedes Date: No information available  
Version 1.03

fresh air in case of accidental inhalation of vapors or decomposition products.

**Ingestion** Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a physician. Do NOT induce vomiting.

**Self-protection of the First Aider** Use personal protective equipment as required.

## 4.2. Most Important Symptoms and Effects, Both Acute and Delayed

**Symptoms** No information available.

## 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

**Note to physicians** Treat symptomatically.

## 4.4. Reference to Other Sections

**Reference to Other Sections** SECTION 8: Exposure controls/personal protection  
Section 11: TOXICOLOGY INFORMATION

## **Section 5: FIRE-FIGHTING MEASURES**

### 5.1. Extinguishing Media

#### **Suitable Extinguishing Media**

Use. Dry chemical. Carbon dioxide (CO2). Water spray (fog). Alcohol resistant foam.

#### **Unsuitable Extinguishing Media**

CAUTION: Use of water spray when fighting fire may be inefficient.

### 5.2. Special Hazards Arising from the Substance or Mixture

#### **Specific Hazards Arising from the Chemical**

Keep product and empty container away from heat and sources of ignition. Risk of ignition.

#### **Explosion Data**

<b>Sensitivity to Mechanical Impact</b>	None.
<b>Sensitivity to Static Discharge</b>	None.

### 5.3. Advice for Firefighters

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **Section 6: ACCIDENTAL RELEASE MEASURES**

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**Personal Precautions** Use personal protective equipment as required. Remove all sources of ignition. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Pay attention to flashback. Take precautionary measures against static discharges.

### 6.2. Environmental Precautions

**Environmental Precautions** Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. See Section 12 for additional Ecological Information.

# Safety Data Sheet

915FS  
915 Fast Set Series

Revision Date 08-Oct-2015  
Supersedes Date: No information available  
Version 1.03

## 6.3. Methods and Material for Containment and Cleaning up

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

**Methods for Cleaning up** Soak up with inert absorbent material. Dam up. Pick up and transfer to properly labeled containers. Take precautionary measures against static discharges.

## 6.4. Reference to other sections

**Reference to Other Sections** SECTION 8: Exposure controls/personal protection  
Section 7: HANDLING AND STORAGE  
Section 13: DISPOSAL CONSIDERATIONS

## Section 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Advice on Safe Handling** Use with local exhaust ventilation. All equipment used when handling the product must be grounded. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

### 7.2. Conditions for Safe Storage, including any Incompatibilities

**Storage Conditions** Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat. Keep in properly labeled containers.

**Incompatible Materials** None known based on information supplied.

### 7.3. Specific End Use(s)

**Other Information** No information available.

### 7.4. References to Other Sections

**Reference to Other Sections** Section 13: DISPOSAL CONSIDERATIONS  
Section 10: STABILITY AND REACTIVITY

## SECTION 8: Exposure controls/personal protection

### 8.1. Control Parameters

**Exposure Guidelines** . As Titanium dioxide (13463-67-7) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses. As Carbon black (1333-86-4) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses. As Limestone CAS 1317-65-3 is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses.

Chemical Name	ACGIH TLV	NIOSH IDLH	OSHA PEL	Mexico
Polyvinyl chloride 9002-86-2	TWA: 1 mg/m <sup>3</sup> respirable fraction	-	-	-
Limestone 1317-65-3	-	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> STEL: 20 mg/m <sup>3</sup>

# Safety Data Sheet

915FS  
915 Fast Set Series

Revision Date 08-Oct-2015  
Supersedes Date: No information available  
Version 1.03

Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	IDLH: 5000 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust	TWA: 10 mg/m <sup>3</sup> STEL: 20 mg/m <sup>3</sup>
m-Xylene 108-38-3	STEL: 150 ppm TWA: 100 ppm	IDLH: 900 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 150 ppm STEL: 655 mg/m <sup>3</sup>	-	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 150 ppm STEL: 655 mg/m <sup>3</sup>
Iron hydroxide oxide 20344-49-4	TWA: 1 mg/m <sup>3</sup> Fe	TWA: 1 mg/m <sup>3</sup> Fe	-	TWA: 1 mg/m <sup>3</sup> STEL: 2 mg/m <sup>3</sup>
p-Xylene 106-42-3	STEL: 150 ppm TWA: 100 ppm	IDLH: 900 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 150 ppm STEL: 655 mg/m <sup>3</sup>	-	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 150 ppm STEL: 655 mg/m <sup>3</sup>
Carbon black 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable fraction	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH	TWA: 3.5 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup> STEL: 7 mg/m <sup>3</sup>
Isophorone diisocyanate 4098-71-9	TWA: 0.005 ppm	TWA: 0.005 ppm TWA: 0.045 mg/m <sup>3</sup> STEL: 0.02 ppm STEL: 0.180 mg/m <sup>3</sup>	-	TWA: 0.01 ppm TWA: 0.09 mg/m <sup>3</sup>
Ethylbenzene 100-41-4	TWA: 20 ppm	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>

Chemical Name	Argentina	Brazil	Chile	Venezuela
Limestone 1317-65-3	TWA: 10 mg/m <sup>3</sup>	-	TWA: 8 mg/m <sup>3</sup>	-
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	-	-	TWA: 10 mg/m <sup>3</sup>
m-Xylene 108-38-3	TWA: 100 ppm STEL: 150 ppm	-	-	Skin STEL: 150 ppm TWA: 100 ppm
Iron hydroxide oxide 20344-49-4	TWA: 1 mg/m <sup>3</sup>	-	-	TWA: 1 mg/m <sup>3</sup>
p-Xylene 106-42-3	TWA: 100 ppm STEL: 150 ppm	-	-	Skin STEL: 150 ppm TWA: 100 ppm
Carbon black 1333-86-4	TWA: 3.5 mg/m <sup>3</sup>	-	-	TWA: 3.5 mg/m <sup>3</sup>
Isophorone diisocyanate 4098-71-9	TWA: 0.005 ppm	-	-	TWA: 0.005 ppm
Ethylbenzene 100-41-4	TWA: 100 ppm STEL: 125 ppm	TWA: 78 ppm TWA: 340 mg/m <sup>3</sup>	TWA: 80 ppm TWA: 348 mg/m <sup>3</sup>	Skin STEL: 125 ppm TWA: 100 ppm

## 8.2. Exposure Controls

### Engineering Controls

Showers  
Eyewash stations  
Ventilation systems.

### Personal protective equipment [PPE]

#### Eye/Face Protection

Tight sealing safety goggles.

#### Skin and Body Protection

Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.

# Safety Data Sheet

915FS  
915 Fast Set Series

Revision Date 08-Oct-2015  
Supersedes Date: No information available  
Version 1.03

**Respiratory Protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**General Hygiene Considerations** When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

**Physical State** Liquid  
**Color** Multiple Colors  
**Odor** Solvent  
**Odor Threshold** No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting Point/Freezing Point	No information available	
Boiling Point	No information available	
Flash Point	74.4 °C / 166 °F	
Evaporation Rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper Flammability Limit	No information available	
Lower Flammability Limit	No information available	
Vapor Pressure	No information available	
Vapor Density	No information available	
Specific Gravity	No information available	
Water Solubility	No information available	
Solubility in Other Solvents		
Partition Coefficient	No information available	
Autoignition Temperature	No information available	
Decomposition Temperature	No information available	
Kinematic Viscosity	No information available	
Dynamic Viscosity	No information available	
Explosive Properties	No information available	
Oxidizing Properties	No information available	

### 9.2. Other Information

**Softening Point** No information available  
**Molecular Weight** No information available  
**Solvent Content (%)** No information available  
**Solid Content (%)** 96  
**Density** 1.2-1.4  
**VOC** 2.8 %

## Section 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

None under normal use conditions.

### 10.2. Chemical Stability

Stable under recommended storage conditions.

### 10.3. Possibility of Hazardous Reactions

# Safety Data Sheet

915FS  
915 Fast Set Series

Revision Date 08-Oct-2015  
Supersedes Date: No information available  
Version 1.03

None under normal processing.

## 10.4. Conditions to Avoid

Heat, flames and sparks.

## 10.5. Incompatible Materials

None known based on information supplied.

## 10.6. Hazardous Decomposition Products

None known based on information supplied.

## **Section 11: TOXICOLOGY INFORMATION**

### 11.1. Information on Toxicological Effects

<b>Product Information</b>	No Data Available
<b>Inhalation</b>	No Data Available.
<b>Eye contact</b>	No Data Available.
<b>Skin Contact</b>	No Data Available.
<b>Ingestion</b>	No Data Available.

### **Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Limestone 1317-65-3	>5000 mg/kg (rat)	-	-
Titanium dioxide 13463-67-7	> 10000 mg/kg ( Rat )	-	-
Propylene carbonate 108-32-7	= 29000 mg/kg ( Rat )	> 20 mL/kg ( Rabbit )	-
m-Xylene 108-38-3	= 5 g/kg ( Rat )	= 14100 µL/kg ( Rabbit )	-
Iron hydroxide oxide 20344-49-4	> 10000 mg/kg ( Rat )	-	Dust 6H >195g/m <sup>3</sup>
Benzenesulfonyl isocyanate, 4-methyl- 4083-64-1	= 2234 mg/kg ( Rat )	-	> 640 ppm ( Rat ) 1 h
p-Xylene 106-42-3	= 4029 mg/kg ( Rat )	-	= 4550 ppm ( Rat ) 4 h = 4740 ppm ( Rat ) 4 h
Carbon black 1333-86-4	> 15400 mg/kg ( Rat )	> 3 g/kg ( Rabbit )	-
Isophorone diisocyanate 4098-71-9	= 4814 mg/kg ( Rat )	1060 - 4780 mg/kg ( Rabbit )	= 0.135 mg/L ( Rat ) 4 h
Ethylbenzene 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 1432 mg/L ( Rat ) 4 h

### Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

<b>Symptoms</b>	No information available.
<b>Skin Corrosion/Irritation</b>	No information available.
<b>Serious Eye Damage/Eye Irritation</b>	No information available.
<b>Irritation</b>	No information available.
<b>Corrosivity</b>	No information available.
<b>Sensitization</b>	No information available.
<b>Germ Cell Mutagenicity</b>	No information available.
<b>Reproductive Toxicity</b>	No information available.
<b>Developmental Toxicity</b>	No information available.
<b>Teratogenicity</b>	No information available.
<b>STOT - Single Exposure</b>	No information available.



# Safety Data Sheet

915FS  
915 Fast Set Series

Revision Date 08-Oct-2015  
Supersedes Date: No information available  
Version 1.03

**STOT - Repeated Exposure  
Chronic Toxicity**

No information available.  
May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects.

**Target Organ Effects**

Blood, Central nervous system, Eyes, Gastrointestinal tract (GI), Kidney, Liver, Lungs, Respiratory system, Skin.

**Aspiration Hazard  
Carcinogenicity**

No information available.  
The table below indicates whether each agency has listed any ingredient as a carcinogen. As Titanium dioxide (13463-67-7) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses. As Carbon black (1333-86-4) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses.

Chemical Name	ACGIH	IARC	NTP	OSHA
Polyvinyl chloride 9002-86-2	-	Group 3	-	-
Titanium dioxide 13463-67-7	-	Group 2B	-	X
m-Xylene 108-38-3	-	Group 3	-	-
p-Xylene 106-42-3	-	Group 3	-	-
Carbon black 1333-86-4	A3	Group 2B	-	X
Ethylbenzene 100-41-4	A3	Group 2B	-	X

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A3 - Confirmed animal carcinogen with unknown relevance to humans

**IARC (International Agency for Research on Cancer)**

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

## Section 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
Limestone 1317-65-3	CE50 (72h) >200mg/L Algae (Desmodesmus subspicatus)	CL50 (96h) >10000mg/L Fish (Oncorhynchus mykiss)		CE50 (48h) >1000 mg/L Daphnia Magna
Propylene carbonate 108-32-7	EC50 72 h > 500 mg/L (Desmodesmus subspicatus)	LC50 96 h > 1000 mg/L (Cyprinus carpio semi-static) LC50 96 h = 5300 mg/L (Leuciscus idus static)	EC50 > 10000 mg/L 17 h	EC50 48 h > 500 mg/L (Daphnia magna )
m-Xylene 108-38-3	EC50 72 h = 4.9 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h 14.3 - 18 mg/L (Pimephales promelas flow-through) LC50 96 h = 8.4 mg/L (Oncorhynchus mykiss semi-static) LC50 96 h = 12.9 mg/L (Poecilia reticulata semi-static)		EC50 48 h 2.81 - 5.0 mg/L (Daphnia magna Static)
p-Xylene 106-42-3	EC50 72 h = 3.2 mg/L (Pseudokirchneriella subcapitata) EC50 3 h =	LC50 96 h 7.2 - 9.9 mg/L (Pimephales promelas static) LC50 96 h = 2.6 mg/L	EC50 = 5.7 mg/L 30 min	EC50 48 h 3.55 - 6.31 mg/L (Daphnia magna Static)

# Safety Data Sheet

915FS  
915 Fast Set Series

Revision Date 08-Oct-2015  
Supersedes Date: No information available  
Version 1.03

	105.1 mg/L (Chlorella vulgaris)	(Oncorhynchus mykiss ) LC50 96 h = 2.6 mg/L (Oncorhynchus mykiss static) LC50 96 h = 8.8 mg/L (Poecilia reticulata semi-static)		
Carbon black 1333-86-4	>10000 mg/l (Desmodesmus subspicatus) OECD 202	>1000 mg/l (Brachydanio rerio) OCDE 203		EC50 24 h > 5600 mg/L (Daphnia magna )
Isophorone diisocyanate 4098-71-9	EC50 72 h = 118.7 mg/L (Desmodesmus subspicatus)	LC50 48 h = 1.8 mg/L (Leuciscus idus static)		EC50 24 h = 83.7 mg/L (Daphnia magna )
Ethylbenzene 100-41-4	EC50 72 h = 4.6 mg/L (Pseudokirchneriella subcapitata) EC50 96 h > 438 mg/L (Pseudokirchneriella subcapitata) EC50 72 h 2.6 - 11.3 mg/L (Pseudokirchneriella subcapitata) EC50 96 h 1.7 - 7.6 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h 11.0 - 18.0 mg/L (Oncorhynchus mykiss static) LC50 96 h = 4.2 mg/L (Oncorhynchus mykiss semi-static) LC50 96 h 7.55 - 11 mg/L (Pimephales promelas flow-through) LC50 96 h = 32 mg/L (Lepomis macrochirus static) LC50 96 h 9.1 - 15.6 mg/L (Pimephales promelas static) LC50 96 h = 9.6 mg/L (Poecilia reticulata static)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50 48 h 1.8 - 2.4 mg/L (Daphnia magna )

## 12.2. Persistence and Degradability

No information available.

## 12.3. Bioaccumulative Potential

No information available.

## 12.4. Mobility in Soil

No information available.

## 12.5 Other adverse effects

No information available

## Section 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste Treatment Methods

#### Disposal of Wastes

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations

#### Contaminated Packaging

Dispose of in accordance with federal, state and local regulations

## Section 14: TRANSPORT INFORMATION

### Note:

49 CFR 173.150(f)(2) "The requirements in this subchapter do not apply to a material classed as a combustible liquid in a non-bulk packaging unless the combustible liquid is a hazardous substance, a hazardous waste, or a marine pollutant."

### DOT

UN/ID No

NA1993

Proper Shipping Name

Combustible liquid, n.o.s.

# Safety Data Sheet

915FS  
915 Fast Set Series

Revision Date 08-Oct-2015  
Supersedes Date: No information available  
Version 1.03

<b>Hazard Class</b>	Combustible liquid
<b>Packing Group</b>	III
<b>Special Provisions</b>	IB3, T1, T4, TP1
<b>Description</b>	NA1993, Combustible liquid, n.o.s. (Xylenes), Combustible liquid, III,
<b>Emergency Response Guide Number</b>	128

**IATA** Not regulated

**IMDG** Not regulated

## Section 15: REGULATORY INFORMATION

### Global Inventories

<b>TSCA</b>	Listed
<b>DSL</b>	Not Listed

#### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL** - Canadian Domestic Substances List

**Listed** - The components of this product are either listed or exempt from listing on inventory.

**Not Listed** - One or more components of this product are not listed on inventory.

### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

#### WHMIS Hazard Class

B3 - Combustible liquid

D2A - Very toxic materials



### United States of America

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No
m-Xylene	108-38-3
Ethylbenzene	100-41-4

#### California Proposition 65

This product contains one or more of the substances listed on Proposition 65 at or above 0.01 wt. %

Chemical Name	CAS No
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	68515-49-1
Titanium dioxide	13463-67-7
Carbon black	1333-86-4
Ethylbenzene	100-41-4
Quartz	14808-60-7

### Europe

# Safety Data Sheet

915FS  
915 Fast Set Series

Revision Date 08-Oct-2015  
Supersedes Date: No information available  
Version 1.03

## Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead (7439-92-1), Cadmium (7440-43-9), Mercury (7439-97-6), Hexavalent chromium (7440-47-3), Polybrominated biphenyls (PBB), and Polybrominated diphenyl ethers (PBDE) above the regulated limit mentioned in this regulation.

## EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## Section 16: OTHER INFORMATION

HMIS Health Hazards 2\* Flammability 2 Physical Hazards 0 Personal Protection X

### Key or Legend to Abbreviations and Acronyms Used in the Safety Data Sheet

No information available

### Key Literature References and Sources for Data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision Date 08-Oct-2015

Revision Note Not applicable.

Training Advice No information available

Further information No information available

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**