



SAFETY DATA SHEET

In accordance with OSHA 29 CFR 1910.1200

EFA+(TM)
Revision Number 3.01

Revision date 16-Oct-2025
Supersedes date 01-Nov-2019

1. Identification

1.1. Product identifier

Product Name EFA+(TM)

Other means of identification

Other information Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives
Restrictions on use No information available

1.3. Details of the supplier of the safety data sheet

Responsible Party

Bostik Inc.
11320 W. Watertown Plank Road
Wauwatosa, Wisconsin 53226 USA
Phone: +1(800) 726-7845 (Domestic Toll Free)
Phone: +1 (414) 774-2250 (International)

E-mail For regulatory and SDS-related questions, please contact a Bostik representative at https://www.bostik.com/us/en_US/customer-support/

1.4. Emergency telephone number

Emergency Telephone CHEMTREC (Chemical Transportation Emergency Center)
Chemtrec: 1-800-424-9300 (US) , 1-703-527-3887 (Outside U.S.)
Rocky Mountain Poison Center: 1-866-767-5089

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Flammable liquids	Category 4
Respiratory sensitization	Category 1
Skin sensitization	Category 1

Hazards not otherwise classified (HNOC)

Not applicable

2.2. Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

May cause allergy or asthma symptoms or breathing difficulties if inhaled
May cause an allergic skin reaction
Combustible liquid

SAFETY DATA SHEET

EFA+(TM)
Revision Number 3.01

Revision date 16-Oct-2025
Supersedes date 01-Nov-2019



Appearance Paste

Physical state Liquid

Odor No information available

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray
In case of inadequate ventilation wear respiratory protection
Contaminated work clothing must not be allowed out of the workplace
Keep away from flames and hot surfaces. - No smoking
Wear protective gloves/eye protection/face protection

Precautionary Statements - Response

IF ON SKIN: Wash with plenty of water and soap
If skin irritation or rash occurs: Get medical advice/attention
Wash contaminated clothing before reuse
IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing
If experiencing respiratory symptoms: Call a POISON CENTER or doctor
In case of fire: Use CO₂, dry chemical, or foam to extinguish

Precautionary Statements - Storage

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

2.3. Other Information

No information available.

3. Composition/information on ingredients

3.1. Substances

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%
Limestone	1317-65-3	40 - 70
Naphtha, petroleum, hydrotreated heavy, <0.1% Benzene	64742-48-9	1 - <5
Methylenediphenyl diisocyanate	26447-40-5	0.1 - <1
Quartz	14808-60-7	0.1 - <1
4-isocyanatosulphonyltoluene tosyl isocyanate	4083-64-1	0.1 - <1

**The exact percentage (concentration) of composition has been withheld as a trade secret*

SAFETY DATA SHEET

EFA+(TM)
Revision Number 3.01

Revision date 16-Oct-2025
Supersedes date 01-Nov-2019

4. First-aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	May cause allergic respiratory reaction. Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Get medical attention immediately if symptoms occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	May cause an allergic skin reaction. May cause sensitization by skin contact. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. In the case of skin irritation or allergic reactions see a physician.
Ingestion	May produce an allergic reaction. Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Get immediate medical attention. If swallowed, call a poison control center or physician immediately.
Self-protection of the first aider	Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/ or wheezing. Itching. Rashes. Hives. May cause sensitization by skin contact.
Effects of Exposure	No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians	May cause sensitization in susceptible persons. Treat symptomatically.
--------------------	--

5. Fire-Fighting Measures

5.1. Extinguishing media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray. Alcohol resistant foam. Use water spray or fog; do not use straight streams. Move containers from fire area if you can do it without risk.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Product is or contains a sensitizer. May cause sensitization by inhalation. May cause sensitization by skin contact. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along
--	---

SAFETY DATA SHEET

EFA+(TM)
Revision Number 3.01

Revision date 16-Oct-2025
Supersedes date 01-Nov-2019

ground and collect in low or confined areas (sewers, basements, tanks).

Hazardous combustion products Carbon oxides. Carbon dioxide (CO₂). Hydrocarbons.

Explosion data
Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do it without risk. Do not touch or walk through spilled material. Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists. Wash thoroughly after handling.

Other information Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Environmental precautions Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. Dike far ahead of liquid spill for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Reference to other sections See section 8 for more information. See section 13 for more information.

7. Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Do not breathe dust/fume/gas/mist/vapors/spray. Use with local exhaust ventilation. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Take off contaminated clothing and wash before reuse.

7.2. Conditions for safe storage, including any incompatibilities

SAFETY DATA SHEET

EFA+(TM)
Revision Number 3.01

Revision date 16-Oct-2025
Supersedes date 01-Nov-2019

Storage Conditions

Keep out of the reach of children. Keep in properly labeled containers. Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep away from water or moist air.

Recommended storage temperature Keep at temperatures between 50 and 95 °F / 10 and 35 °C.

7.3 References to other sections

Reference to other sections Section 10: STABILITY AND REACTIVITY
Section 13: DISPOSAL CONSIDERATIONS

8. Exposure Controls/Personal Protection

8.1. Control parameters

Exposure Limits

This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Limestone 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Methylenediphenyl diisocyanate 26447-40-5	-	Ceiling: 0.02 ppm Ceiling: 0.2 mg/m ³	-
Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 µg/m ³ (vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust

Chemical name	Argentina	Brazil	S.D. 594/1999	Colombia
Limestone 1317-65-3	TWA-CMP: 10 mg/m ³ ;	-	TWA-LPP: 7 mg/m ³ ; free of Asbestos with <1% free Crystalline Silica TWA-LPP: 5 mg/m ³ ; respirable fraction	-
Methylenediphenyl diisocyanate 26447-40-5	TWA-CMP: 0.005 ppm;	-	TWA-LPP: 0.004 ppm; TWA-LPP: 0.045 mg/m ³ ;	-
Quartz 14808-60-7	TWA-CMP: 0.05 mg/m ³ ; respirable fraction	TWA-LT: 0.025 mg/m ³ ; respirable particulate matter	TWA-LPP: 0.08 mg/m ³ ; respirable fraction	TWA: 0.025mg/m ³

Chemical name	Costa Rica	Peru	Uruguay	Venezuela
Methylenediphenyl diisocyanate 26447-40-5	TWA: 0.005ppm	-	-	-

SAFETY DATA SHEET

EFA+(TM)
Revision Number 3.01

Revision date 16-Oct-2025
Supersedes date 01-Nov-2019

Chemical name	Costa Rica	Peru	Uruguay	Venezuela
Quartz 14808-60-7	TWA: 0.025mg/m ³	TWA: 0.05mg/m ³	0.025 mg/m ³ TWA (respirable particulate matter)	TWA: 0.025 mg/m ³

8.2. Exposure controls

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles. Avoid contact with eyes.

Hand protection Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.

Skin and body protection Wear suitable protective clothing.

Respiratory protection Use appropriate respiratory protection.

General hygiene considerations Wear suitable gloves and eye/face protection. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin, eyes or clothing. Wash hands before breaks and immediately after handling the product. Take off contaminated clothing and wash it before reuse. Regular cleaning of equipment, work area and clothing is recommended.

9. Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Paste
Color White
Odor No information available
Odor threshold No information available

Property	Values	Remarks • Method
pH	No data available	None known
pH (as aqueous solution)	No data available	None known
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	172 °C / 342 °F	
Flash point	63 °C / 145 °F	CC (closed cup)
Evaporation rate	No data available	None known
Flammability	No data available	
Flammability Limit in Air		None known
Upper flammability or explosive	No data available	

SAFETY DATA SHEET

EFA+(TM)
Revision Number 3.01

Revision date 16-Oct-2025
Supersedes date 01-Nov-2019

limits		
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	None known
Relative vapor density	No data available	None known
Relative density	No data available	None known
Water solubility	Reacts with water	Reacts with water
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

9.2. Other information

Explosive properties	No information available	
Oxidizing properties	No information available	
Solvent content (%)	No information available	
Solid content (%)	95.5	
Softening point	No information available	
Molecular weight	No information available	
VOC content	<2 % <25 g/L	No information available
Density	1.649 g/cm ³	
Bulk density	No information available	

10. Stability and Reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Chemical stability Stable under normal conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Protect from moisture.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None known based on information supplied

11. Toxicological information

11.1. Information on toxicological effects

Product Information

SAFETY DATA SHEET

EFA+(TM)
Revision Number 3.01

Revision date 16-Oct-2025
Supersedes date 01-Nov-2019

Inhalation	May cause sensitization in susceptible persons.
Eye contact	Based on available data, the classification criteria are not met.
Skin contact	Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. May cause sensitization by skin contact.
Ingestion	May cause additional effects as listed under "Inhalation".

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Coughing and/ or wheezing. Itching. Rashes. Hives.
----------	---

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	>5000 mg/kg
ATEmix (dermal)	90,249.60 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapor)	>20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Limestone 1317-65-3	>5000 mg/kg (Rattus)	-	-
Naphtha, petroleum, hydrotreated heavy, <0.1% Benzene 64742-48-9	>6000 mg/kg (Rattus)	> 3160 mg/kg (Oryctolagus cuniculus)	>8500 mg/m ³ (Rattus) 4 h
Methylenediphenyl diisocyanate 26447-40-5	>10000 mg/kg (Rattus)	> 10000 mg/kg (Oryctolagus cuniculus)	=490 mg/m ³ (Rattus) 4 h
Quartz 14808-60-7	>2000 mg/kg (Rattus)	-	-
4-isocyanatosulphonyltoluene tosyl isocyanate 4083-64-1	=2234 mg/kg (Rattus)	LD 50 (Rattus) > 2000 mg/kg OECD 402	>640 ppm (Rattus) 1 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Based on available data, the classification criteria are not met.
Serious eye damage/eye irritation	Based on available data, the classification criteria are not met.
Respiratory or skin sensitization	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

EFA+(TM)
Revision Number 3.01

Revision date 16-Oct-2025
Supersedes date 01-Nov-2019

Carcinogenicity

This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Methylenediphenyl diisocyanate 26447-40-5	-	Group 3	-	-
Quartz 14808-60-7	A2 A2 - Suspected Human Carcinogen	Group 1	Known	X

Legend

IARC (International Agency for Research on Cancer)

Group 3 - Not classifiable as to carcinogenicity in humans

Methylenediphenyl diisocyanate (26447-40-5)

Method	Species	Results
	in vivo	Limited evidence of a carcinogenic effect

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT - single exposure

Based on available data, the classification criteria are not met.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Target organ effects

Respiratory system, Eyes, Skin.

Aspiration hazard

Based on available data, the classification criteria are not met.

Other adverse effects

No information available.

Interactive effects

No information available.

12. Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Limestone 1317-65-3	CE50 (72h) >200mg/L Algae (Desmodesmus subspicatus)	CL50 (96h) >10000mg/L (Oncorhynchus mykiss)	-	CE50 (48h) >1000 mg/L Daphnia Magna
Naphtha, petroleum, hydrotreated heavy, <0.1% Benzene 64742-48-9	-	LC50: =2200mg/L (96h, Pimephales promelas)	-	LC50: =2.6mg/L (96h, Chaetogammarus marinus)
Methylenediphenyl diisocyanate 26447-40-5	EC50: =3230mg/L (96h, Skeletonema costatum)	-	-	EC50: >1000mg/L (24h, Daphnia magna)

SAFETY DATA SHEET

EFA+(TM)
Revision Number 3.01

Revision date 16-Oct-2025
Supersedes date 01-Nov-2019

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
Limestone 1317-65-3	0.9
Methylenediphenyl diisocyanate 26447-40-5	4.5
4-isocyanatosulphonyltoluene tosyl isocyanate 4083-64-1	0.6

12.4. Mobility in soil

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

13. Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Contaminated packaging Dispose of in accordance with federal, state and local regulations.

14. Transport information

Note: The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). DOT Ground - "Non-bulk shipments may be non-regulated per 49CFR 173.150(f)(2)".

DOT

UN number or ID number	NA1993
Extended proper shipping name	Combustible liquid, n.o.s.(Naphtha, petroleum, heavy alkylate)
Transport hazard class(es)	Combustible liquid
Packing group	III
Special Provisions	IB3, T1, TP1, 148
DOT Marine Pollutant	I
Description	NA1993, Combustible liquid, n.o.s.(Naphtha, petroleum, heavy alkylate), Combustible liquid, III
Emergency Response Guide	128

SAFETY DATA SHEET

EFA+(TM)
Revision Number 3.01

Revision date 16-Oct-2025
Supersedes date 01-Nov-2019

Number

IATA Not regulated

IMDG Not regulated

15. Regulatory Information

International Inventories

TSCA	Complies
DSL	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

Complies - The components of this product are either listed or exempt from listing on inventory. Active

Not Listed - One or more components of this product are not listed on inventory.

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

16. Other Information

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity

ATE: Acute Toxicity Estimate

LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average)

Ceiling Maximum limit value

STEL

Sk*

STEL (Short Term Exposure Limit)

Skin designation

Prepared By Product Stewardship and Regulatory Affairs.

Revision date 16-Oct-2025

Revision Note SDS sections updated. 3. 4. 8. 9. 14.

Disclaimer

All information contained herein is believed to be accurate as of the date of publication, is provided "as-is" and is subject to change without notice. This is not a warranty, an agreement, or substitute for expert or professional advice. Bostik

SAFETY DATA SHEET

EFA+(TM)
Revision Number 3.01

Revision date 16-Oct-2025
Supersedes date 01-Nov-2019

Inc. ("Company") expressly disclaims and assumes no liability for the use of the products or reliance on this information. It is the sole responsibility of the user to determine the suitability of any products for user's application(s). **NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED (INCLUDING SUITABILITY FOR USE IN ANY MEDICAL DEVICE OR MEDICAL APPLICATION), IS MADE CONCERNING THE PRODUCTS OR THE INFORMATION PROVIDED HEREIN.** The information provided relates only to the specific products designated herein and may not be valid where such products are used in combination with other materials or in any process. The performance of the product, its shelf life, and application characteristics depends on many variables, and changes in these variables can impact product performance. You are responsible to test the suitability of any product in advance for any intended use or application and before commercialization. Nothing herein shall be construed as a license for the use of any product in a manner that might infringe any patent and it should not be construed as an inducement to infringe any patent. Please carefully review the Safety Data Sheet for the product.

The Company adheres to a strict policy that applies to the use of any of its products in medical device applications. This policy can be found at

<https://www.arkema.com/global/en/social-responsibility/innovation-and-sustainable-solutions/responsible-product-management/medical-device-policy/> which is incorporated herein by reference and made a part hereof. Except as expressly authorized, the Company (i) has designated specific medical grade compositions for products used in medical device applications and Company products not so designated are not authorized for use in medical device applications and (ii) strictly prohibits the use of any of its products in medical device applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. The Company does not design, manufacture and/or directly sell any medical devices. The Company does not co-design, or offer assistance to any purchaser of its products, in their design, manufacture and/or sale of products for medical devices. It is the sole responsibility of the manufacturer of medical devices to determine the suitability of all raw material, products and components, including any medical grade products, in order to ensure that the medical device is safe for end-use and complies with all applicable legal and regulatory requirements and to conduct all necessary tests and inspections.

End of Safety Data Sheet