



# Hardwood Installation Products


**ADHESIVES, MOISTURE CONTROL, SOUND ABATEMENT,  
AND ACCESSORIES**



# Complete Hardwood System Solutions

**PROTECTION EVERY STEP OF THE WAY**

- 1 Substrate Repair
- 2 Primer
- 3 Self-Leveling/Patch
- 4 Moisture Mitigation
- 5 Adhesive



<p><b>Step 1</b> Surface Prep</p>	
<p><b>Step 2</b> Moisture Mitigation</p>	 <p style="text-align: center;">OR</p>  <p style="text-align: right;">Moisture mitigation is <b>not required</b> for adhesives with</p>
<p><b>Step 3</b> Adhesive</p>	
<p><b>Warranty Available</b></p>	<p style="text-align: center;"><b>Up to Lifetime Warranty!</b></p>

Above are representative system examples that work to cover many installation needs. Consult your local Bostik sales rep for help defining a system of products that best suits your specific installation and warranty protection needs.




To learn more about Bostik system warranties, scan this code or visit: [bit.ly/BostikWarranty](https://bit.ly/BostikWarranty)  
**1-800-726-7845 | [www.bostik.com/us](http://www.bostik.com/us)**

T000646\_091321



# Contents



## Inside Our Technology

Tech Feature: Moisture-Vapor Control 4

Hardwood Reference Guide 5

## Axios® Tri-Linking™ Products

Tech Feature: AXIOS™ Tri-Linking™ 6

Tech Feature: Thickness Control™ Spacer Technology 6

Tech Feature: SoundGuard™ 7

Ultra-Set® SingleStep2™ 8

GreenForce® 9

Vapor-Lock™ 10

Bostik's BEST® 10

EFA+™ 11

BST™ 11

Pro-MSP™ 12

Pro-Cure™ 12

Wood-Tack™ 12

## Moisture Vapor Barrier Coatings

MVP4® 13

## Cartridge Products

Climb™ 14

Heavy-Duty™ Construction Adhesive 14

PWC 14

## Accessories

Ultimate™ Adhesive Remover 15

Cartridge Guns 15

AT YOUR SERVICE 24/7

NEW!

BOSTIK PRO™  
MOBILE APP

DOWNLOAD TODAY!



App Store



Google Play



# Experiencing moisture issues?

## We're here to help.

### The hardwood industry's most trusted line of moisture-vapor control products.

Bostik, the leader in hardwood adhesives, offers the most comprehensive range of products featuring unlimited moisture-vapor protection with **no concrete moisture testing requirements**. Also, with these Bostik adhesives, there are never any board width or length restrictions, making it easier for you to install your hardwood flooring. The formulas you trust and the performance you can rely on.

#### Adhesive Comparison



<b>Moisture Warranty And Duration</b>	Lifetime, Unlimited	Lifetime, Unlimited	Lifetime, Unlimited	Lifetime, Unlimited	Lifetime, Unlimited*
<b>Flooring Types Covered</b>	Solid, Engineered, Bamboo	Solid, Engineered, Bamboo	Solid, Engineered (Bamboo 15 lb/87% RH limit)	Engineered	Solid, Engineered, Bamboo

\*When used with any Axios®, Urethane, or MS-Polymer Bostik Adhesive.

# HARDWOOD

## Reference Guide

Ultra-Set®  
SingleStep2™

Vapor-Lock™

GreenForce®

Bostik's BEST®

BST™

Pro-MSP™

EFA+™

Pro-Cure™

Wood-Tack™

Product Trait	Ultra-Set® SingleStep2™	Vapor-Lock™	GreenForce®	Bostik's BEST®	BST™	Pro-MSP™	EFA+™	Pro-Cure™	Wood-Tack™
Axios® Tri-Linking™ Technology	✓	--	✓	--	--	--	--	--	--
Moisture limits (Max MVER)	Unlimited	Unlimited*	Unlimited	Unlimited**	15 lb	15 lb	15 lb	3 lb	3 lb
Moisture warranty	Lifetime	Lifetime	Lifetime	Lifetime	5 years	5 years	5 years	--	--
Warranty without moisture vapor testing	✓	--	✓	--	--	--	--	--	--
Thickness Control™ Spacer Technology	✓	✓	--	--	--	--	--	--	--
Easy clean after cure	✓	--	✓	--	--	✓	--	--	--
Workability	Excellent	Moderate	Excellent	Moderate	Moderate+	Easy	Easy	Moderate	Excellent
Green grab	Strong	Strong	Good	Good	Strong	Moderate	Moderate	Moderate	Good
Unit size	4 gallon	4 gallon	4 gallon, 12 x 28 oz	5 gallon, 12 x 28 oz, 24 x 10.1 oz, 12 x 10.1 oz	4 gallon	4 gallon 12 x 20 oz	5 gallon 4 gallon	4 gallon	4 gallon
<b>Warranty</b>									
Duration of Bond Warranty	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	10 year	10 year
Moisture Warranty Duration	Lifetime	Lifetime	Lifetime	Lifetime	5 Years	5 Years	5 Years	--	--
Flooring Types Under Moisture Protection Warranty	Solid, Bamboo, Engineered	Solid, Engineered	Solid, Bamboo, Engineered	Engineered	Engineered	Engineered	Engineered	--	--
<b>Cured Physical Properties</b>									
Concrete Moisture-Vapor Limits	None, Dry to the Touch	None, Dry to the Touch*	None, Dry to the Touch	None, Dry to the Touch**	≤ 15 lbs or 87% RH	≤ 15 lbs or 87% RH	≤ 15 lbs or 87% RH	≤ 3 lbs or 75% RH	≤ 3 lbs or 75% RH
Contains Bostik's BLOCKADE®	Yes	Yes	Yes	Yes	No	No	No	No	No
<b>Sound Reduction Performance</b>									
ASTM E2179 Increased Impact Insulation	21 dB	21 dB	--	--	--	***	--	--	--
ASTM E492-04 IIC- 6" Slab With 5/8" Gypsum Ceiling	70	69	***	--	--	***	--	--	--
ASTM E90-09 STC- 6" Slab With 5/8" Gypsum Ceiling	67	66	--	--	--	***	--	--	--
<b>Application Properties</b>									
Color	Beige w/ Black Specs	Brown w/ Black Specs	Beige	Tan	Brown	Brown	White	Beige	Beige/Tan
Density (lbs/gallon)	14.25	14.7	14.25	12.66	12.66	14.25	13.7	14.08	10.26
<b>Chemical Properties</b>									
Chemistry Type	AXIOS® Tri-Linking™	Urethane	AXIOS® Tri-Linking™	Urethane	Urethane	MS Polymer	Urethane	Urethane	Acrylic
VOC Compliant (calculated per SCAQMD Rule 116B)	Yes (0 g/L)	Yes (0 g/L)	Yes (0 g/L)	Yes (20 g/L)****	Yes (22 g/L)****	Yes (8 g/L)****	Yes (25 g/L)****	Yes (25 g/L)****	Yes (10 g/L)
<b>LEED® Point Contributions</b>									
EQ 4.1: Low-Emitting Materials—Adhesives & Sealants	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
MR 4.2: Recycled Content	Yes, 1% by Weight	Yes, 1% by Weight	No	No	No	No	No	No	No

\*Vapor-Lock™ moisture limit for bamboo: ≤15 lb or 85% RH

\*\*Unlimited moisture limits for Bostik's BEST® applies only to engineered hardwood flooring installations.

\*\*\* Meets or exceeds International Building Code requirements. Contact Bostik for details

\*\*\*\*Tested per EPA Method 24.

# Bostik unveils an innovative new technology

AXIOS™ Tri-Linking™ Polymer Technology is easy to spread, simple to clean, and offers you the most protection for your hardwood flooring installations. Exactly what you would expect from the hardwood adhesive technology leader.

## DESCRIPTION

Easy to clean and tough, Bostik's AXIOS™ Tri-Linking™ Polymer Technology is a breakthrough in adhesion science.

AXIOS™ technology combines the tenacious bond strength of Bostik's high-performance urethane chemistry with the remarkable ease of use experienced from today's most advanced European, hybrid polymer systems.

With moisture-vapor protection equivalent to premium moisture mitigation coatings, AXIOS™ is the go-to polymer chemistry for the ultimate in installation protection and simplicity. When combined with Bostik's patent-pending Thickness Control™ Spacer Technology, its performance is equivalent to the sound-dampening properties of cork.

AXIOS™ is formulated for use in a variety of residential and commercial hardwood flooring installations, making them easier to install and more durable.

## THE SCIENCE BEHIND THE TECHNOLOGY

Most hardwood adhesives today contain linear polymer chains that link to other molecules only at each end. AXIOS™ Tri-Linking™ Polymer Technology uses a revolutionary molecule that has three branches (similar to a tripod). This allows each molecule to bond in three locations instead of only two, making the adhesive bond stronger.

Tri-Linking™ polymers are also more "entangled" because of their unique shape. (Think of how tangled a bowl full of miniature tripods would be.) This entanglement creates a tightly interwoven layer that significantly inhibits water molecules from passing through, dramatically improving moisture-vapor protection, sound reduction, and strength.

# Reduce Risk, Improve Installations

## Focus on Bostik's Thickness Control™ Spacer Technology

At Bostik, innovation comes in many forms, not just chemistry. Bostik's patent-pending Thickness Control™ Spacer Technology is a proprietary feature that helps ensure proper membrane thickness is maintained between the hardwood flooring and substrate. Installers can use mallets to engage the tongue and groove or even walk on their work during the installation process without significant reduction in the film thickness that could compromise moisture protection or sound control.



The key is in the rubber crumbs mixed in with the adhesive. The particles are made of recycled, ground up car tires. The size of the particles creates the optimal membrane thickness for superior performance as a moisture-reduction and sound-control membrane. If you stand on a board installed over any adhesive using Thickness Control™ Spacers, the rubber particles prevent the fluid adhesive from squeezing out underneath the boards and the desired membrane thickness is maintained.

Bostik's Thickness Control™ Spacer Technology not only reduces your risk of failing to achieve proper membrane thickness that could result in flooring failures from moisture, but it also makes installation easier. You won't need a special trowel or a clip-on component that wears out quickly. You can use common trowels and be confident that you've got the moisture control and sound reduction performance you expect.



Thickness Control™ Spacers



# Sound Reduction With Adhesive!



Nobody wants to be disturbed by their neighbors. Whether it's the home-theater system from your neighbors below, or the high-heeled shoes of the neighbor above, acoustics play an essential role in the comfort of a home. Bostik offers several products specifically designed to improve acoustics.



Bostik installation systems with Sound Guard™ eliminate the need for mats or underlayments used beneath hardwood floors, resulting in faster install times and lower project costs. These adhesives reduce the vibration of boards, providing a quieter, more comfortable floor.



Test*	Ceiling Type	Vapor-Lock™	Ultra-Set® SingleStep2™	MVP4™ + Adhesive**
IIC	5/8" Suspended Gypsum	69 dB	70 dB	62 dB
	No Suspended Ceiling	49 dB	50 dB	49 dB
Δ IIC	No Suspended Ceiling	21 dB	21 dB	21 dB
STC	5/8" Suspended Gypsum	66 dB	67 dB	61 dB
	No Suspended Ceiling	50 dB	51 dB	52 dB

\* Tests were performed using 3/8" engineered hardwood bonded to 6" thick concrete.  
 \*\* Test performed with 9/16" thick engineered hardwood and Bostik's Best®.



# Hardwood Installation Products

## Ultra-Set® SingleStep2™

**ADVANCED TRI-LINKING™ ADHESIVE, MOISTURE CONTROL & SOUND REDUCTION MEMBRANE**

Ultra-Set® SingleStep2™ is a high-performance adhesive, moisture-control and sound-reduction membrane all in one. Bostik's breakthrough AXIOS® Tri-Linking™ Polymer Technology used in this formulation maintains the superior long-term durability, moisture control and sound abatement properties of high-end urethane adhesives. However, it is easier to spread and clean off of prefinished flooring before and after cure. This adhesive contains 1% recycled rubber material, has zero VOCs (as calculated per SCAQMD Rule 1168), and does NOT contain any water.



[www.youtube.com/BostikUSA](http://www.youtube.com/BostikUSA)



ULTRA-SET® SINGLESTEP2™				
Item No.	Size	Pail/Case UPC Code	Cartridge UPC Code	Units/pallet
30850854	4 gallon	747224700001	--	36 pails



## Bostik's System Solution

- |                              |                              |
|------------------------------|------------------------------|
| <b>1</b> Substrate Repair    | <b>4</b> Moisture Mitigation |
| <b>2</b> Primer              | <b>5</b> Adhesive            |
| <b>3</b> Self-Leveling/Patch |                              |

## GreenForce®

### ADVANCED TRI-LINKING™ ADHESIVE & MOISTURE CONTROL MEMBRANE

GreenForce® is a high-performance adhesive and moisture control membrane all in one. Bostik's breakthrough AXIOS® Tri-Linking™ Polymer Technology used in this formulation maintains the superior long-term durability and moisture protection properties of high-end urethane adhesives. However, it is easier to spread and clean off of prefinished flooring before and after cure. This adhesive has zero VOCs (as calculated per SCAQMD Rule 1168) and does NOT contain any water.



[www.youtube.com/BostikUSA](http://www.youtube.com/BostikUSA)



EASY CLEAN BEFORE & AFTER CURE

HARDWOOD

UNLIMITED MOISTURE-VAPOR PROTECTION

SUPERIOR BOND STRENGTH & GREEN GRAB

4 Gal  
15.1 L

#### GREENFORCE™

Item No.	Size	Pail/Case UPC Code	Cartridge UPC Code	Units/pallet
30850844	4 gallon	747224700018	--	36 pails
30850846	12 x 28 oz cartridge	10747224700107	747224700100	60 cases

# Vapor-Lock™

## HARDWOOD ADHESIVE, MOISTURE CONTROL & SOUND REDUCTION MEMBRANE

Bostik's Vapor-Lock™ is a high-performance adhesive, moisture-control, and sound-reduction membrane all in one. Its superior properties provide a tough, flexible, and tenacious bond to a variety of surfaces, and it is not adversely affected by exposure to moisture, water, or alkalinity. When applied as directed as a moisture vapor membrane, it will prevent damages caused by high subfloor moisture-vapor. As a result, costly and time-consuming concrete moisture testing is not required for solid or engineered hardwood flooring. For bamboo flooring, Vapor-Lock™ may be used for concrete slabs with elevated moisture levels up to 15 lbs or 87% RH.

Vapor-Lock™ exhibits exceptional green grab or high tack immediately after troweling, making installation easier and more secure. This adhesive contains 1% recycled rubber material, has zero VOCs (as calculated per SCAQMD Rule 1168), and does NOT contain any water. Vapor-Lock™ contains Bostik's BLOCKADE™ antimicrobial protection, which inhibits the growth of bacteria, mold, or mildew on the surface of the dried adhesive.



THICKNESS CONTROL™  
SPACER TECHNOLOGY

MOISTURE-VAPOR  
PROTECTION

SUPERIOR SOUND-DAMPENING  
PERFORMANCE



VAPOR-LOCK™				
Item No.	Size	Pail/Case UPC Code	Cartridge UPC Code	Units/pallet
30850864	4 gallon	747224699312	--	36 pails

HARDWOOD ADHESIVES

# Bostik's BEST®

## WOOD FLOORING URETHANE ADHESIVE AND MOISTURE-VAPOR CONTROL

Bostik's BEST® is a high-performance adhesive and moisture control membrane. Its superior properties provide a tough, flexible, and tenacious bond to a variety of surfaces. Bostik's BEST® high-tacking formula exhibits exceptional green grab immediately after troweling, making installation easier and more secure. When applied as directed as a moisture vapor membrane, it will prevent damages caused by high subfloor moisture vapor. As a result, costly and time-consuming concrete moisture testing is not required for engineered hardwood flooring. For solid hardwood or bamboo on substrates >3 lbs. or 75% RH, use MVP4® prior to the use of Bostik's BEST®.

This adhesive has low VOCs (measured per EPA Method 24) and does NOT contain any water. Bostik's BEST® contains Bostik's BLOCKADE™ antimicrobial protection, which inhibits the growth of bacteria, mold, or mildew on the surface of the dried adhesive.



OVER 25 YEARS OF INDUSTRY-  
LEADING PERFORMANCE

MOISTURE-VAPOR  
PROTECTION

BOSTIK'S BLOCKADE®  
ANTI-MICROBIAL PROTECTION



BOSTIK'S BEST®				
Item No.	Size	Pail/Case UPC Code	Cartridge UPC Code	Units/pallet
30850825	5 gallon	747224389053		36 pails
30618591	4 gallon	747224700926		36 pails
Item No.	Size	Pail/Case UPC Code	Cartridge UPC Code	Units/pallet
30850116	12 x 28 oz cartridge	10747224700121	747224700124	60 cases
30850117	12 x 10.1 oz cartridge	10747224700084	747224389107	96 cases
30850115	24 x 10.1 oz cartridge	10747224700060	747224389107	105 cases

# EFA+™

## ELASTOMERIC FLOORING ADHESIVE & MOISTURE-VAPOR RETARDER

Bostik's EFA+™ is an easy-to-trowel urethane adhesive and moisture-control membrane. It provides a tough, flexible, and tenacious bond to a variety of surfaces. Bostik's EFA+™ elastomeric characteristics allow the adhesive to move with the wood as it expands and contracts over the life of the floor. Bostik's EFA+™ exhibits a long open time, making installation easier and faster. This adhesive has low VOCs (as calculated per SCAQMD Rule 1168) and does NOT contain any water.



EFA+™				
Item No.	Size	Units/pallet	Pail/Case UPC Code	Cartridge UPC Code
30617512	4 gallon	36 pails	747224700919	--
30850811	5 gallon	36 pails	747224626455	--

HARDWOOD ADHESIVES

# BST™

## WOOD FLOORING ADHESIVE & MOISTURE-VAPOR RETARDER

Bostik's BST™ is a urethane adhesive and moisture control membrane. Its superior properties provide a tough, flexible, tenacious bond to a variety of surfaces. Bostik's BST™ elastomeric characteristics allow the adhesive to move with the wood as it expands and contracts over the life of the floor. Bostik's BST™ exhibits exceptional green grab making installation easier as it minimizes slipping of the flooring. This adhesive has low VOCs (as calculated per SCAQMD Rule 1168) and does NOT contain any water.



BST™				
Item No.	Size	Units/pallet	Pail/Case UPC Code	Cartridge UPC Code
30850806	4 gallon	36 pails	747224700278	--

# Pro-MSP™

## HARDWOOD ADHESIVE WITH MOISTURE -VAPOR PROTECTION

Bostik's Pro-MSP™ is a hardwood and bamboo adhesive and moisture-control membrane all in one. This adhesive formulation maintains long-term durability and moisture-control properties, and it is easy to spread and clean off of prefinished flooring before and after cure. This adhesive has low VOCs (as measured per EPA Method 24) and does NOT contain any water.



PRO-MSP™				
Item No.	Size	Units/pallet	Pail/Case UPC Code	Cartridge UPC Code
30850809	4 gallon	36 pails	747224700209	--
30617345	12 x 20 oz sausages	90 cases	10747224700886	747224700889

HARDWOOD ADHESIVES

# Pro-Cure™

## MOISTURE-CURE URETHANE ADHESIVE

Bostik's Pro-Cure™ is a professional grade, moisture-cure urethane adhesive for wood flooring. This adhesive does NOT contain any water. Pro-Cure™ may be used to adhere all engineered, acrylic impregnated, solid plank-flat milled, shorts, and bamboo and parquet hardwood flooring designed and recommended in writing by the hardwood flooring manufacturer for glue-down applications. This adhesive can also be used to install plywood as described, as well as ceramic tile, marble, and stone inlays for light commercial and/or residential applications.

- GREAT GREEN GRAB MINIMIZES SLIPPING
- MODERATE MOISTURE -VAPOR PROTECTION
- LOW VOC



PRO-CURE™				
Item No.	Size	Units/pallet	Pail/Case UPC Code	Cartridge UPC Code
30850842	4 gallon	36 pails	747224680402	--

# Wood-Tack™

## ENGINEERED WOOD FLOORING ADHESIVE

Bostik's Wood-Tack™ is an adhesive for engineered, solid, and select bamboo hardwood flooring installations. This air-curing, self-crosslinking adhesive is exceptionally easy to trowel, and its rapid tacking properties allow for fast installation of wood flooring materials. Wood-Tack™ is a low-VOC, low-odor adhesive that does not contain any solvents or heavy metals. This adhesive provides exceptional bond strength between the wood flooring and substrate.

- RAPID TACKING
- FAST INSTALLATION IN ABOVE-GRADE APPLICATIONS
- EXCEPTIONALLY EASY TO TROWEL



WOOD-TACK™				
Item No.	Size	Units/pallet	Pail/Case UPC Code	Cartridge UPC Code
30856391	4 gallon	48 pails	747224606723	--



MOISTURE  
VAPOR BARRIERS

## MVP4®

### MOISTURE-VAPOR PROTECTION, ANTI-FRACTURE AND NOISE REDUCTION MEMBRANE

Bostik MVP4® Moisture Vapor Protection is a one-part, trowel applied, elastomeric, moisture cure urethane membrane designed to be used beneath glue-down installations of engineered, solid, and bamboo hardwood flooring with Bostik's Best®, BST™, EFA+™, or Vapor-Lock™ adhesives. Bostik MVP4® is designed to reduce moisture-vapor transmission from the subfloor, create a noise reduction barrier over the substrate, and establish an anti-fracture membrane, which can bridge cracks that can occur in the substrate prior to or after installation (up to 1/8").



PREVENTS DAMAGE CAUSED  
BY SUBFLOOR MOISTURE

BELOW-, ON-, AND ABOVE-  
GRADE INSTALLATIONS

EXCEEDS IRC REQUIREMENTS  
FOR VAPOR RETARDERS



#### MVP4®

Item No.	Size	Pail/Case UPC Code	Units/pallet
308505841	5 gallon	747224669001	36 pails

# Climb™

## HARDWOOD WALL PLANK AND TREAD CAP ADHESIVE

Bostik's Climb™ is a one-component, easy gunning, non-sag adhesive that is specifically formulated for hardwood flooring planks or blocks on interior, above-grade walls and installation of stair tread caps. The Climb™ formula has superior green grab (grab strength while wet) and cures quickly to form a tenacious bond. Once cured, Climb™ remains tough yet flexible for extreme durability, helps reduce stair squeaking, and reduces the sound of footsteps on the stairs. This specialty formulation is also easy to clean off of hardwood wall planks and prefinished tread caps and risers even after cure. Climb™ has 0% solvents and low odor.



EXTREMELY STRONG, DURABLE BOND

EASY TO CLEAN, EVEN AFTER CURE

HELPS ELIMINATE SQUEAKING & REDUCES SOUND

### CLIMB™

Item No.	Color	Size	Barcode	Case Code
30854239	White	12 x 10.1 oz/case*	747224700292	10747224700299
Package Size	Weight/Unit	Units/Pallet	Weight/Pallet	
10.1 oz cartridge	13.3 lbs/case	96 cases	1,325 lbs	

\*Sold in full cases only

# Heavy Duty™

## CONSTRUCTION ADHESIVE

Bostik's Heavy Duty™ is a one-component, moisture cure polyurethane adhesive exhibiting high strength and is suitable for both interior and exterior installations. Heavy Duty™ Construction Adhesive typically does not require priming to achieve a watertight seal on common construction materials such as stone, concrete, masonry, cedar, wood, anodized aluminum, galvanized steel, vinyl, fiber-cement board, and so on. Heavy Duty™ Construction Adhesive can bond to wet, frozen, or treated lumber.

REDUCES SQUEAKS IN SUBFLOORS

95% SOLIDS AND FASTER CURE THAN TYPICAL SOLVENT-BASED SYSTEMS

ADHERES TO WET AND FROZEN LUMBER



### HEAVY DUTY™ CONSTRUCTION ADHESIVE

Item No.	Color	Size	Barcode	Case Code
30854485	Natural	12 x 10.1 oz/case*	747224699107	10747224699104
30850203	Natural	12 x 28 oz/case*	747224699206	10747224699203
Package Size	Weight/Unit	Units/Pallet	Weight/Pallet	
10.1 oz cartridge	15 lbs/case	96 cases	1,490 lbs	
28 oz cartridge	26 lbs/case	60 cases	1,610 lbs	

\*Sold in full cases only.

# PWC

## GENERAL PURPOSE SILICONIZED ACRYLIC CAULK

Bostik's PWC is a siliconized, acrylic latex caulk with excellent adhesion to most building materials and common household surfaces. PWC is compatible with latex and oil-based paints. Bostik PWC has been developed for caulking applications including: trim, windows, door frames, sinks, tubs, shower surrounds, countertops, ceramic tile, and natural stone.

PAINTABLE IN 2-3 HOURS

FLEXIBLE BOND AND LOW SHRINKAGE TO PREVENT CRACKING

COMPLEMENTS MOST PRE-FINISHED WHITE TRIM



### PWC

Item No.	Color	Size	Barcode	Case Code
30614464	White	10.1 oz/cartridge*	747224606778	10747224606775
Package Size	Weight/Unit	Units/Pallet	Weight/Pallet	
10.1 oz cartridges	13.2 lbs/case*	120 cases	1,584 lbs	

\*Sold in full cases only.



To view Bostik's YouTube channel scan this code or visit, [youtube.com/bostikUSA](https://youtube.com/bostikUSA)



## Ultimate™

### ADHESIVE REMOVER

Bostik's Ultimate™ Adhesive Remover is a readily biodegradable, low odor, water rinseable solution. Use Ultimate™ to remove wet and cured urethane adhesive from the surface of pre-finished (non-wax) wood flooring.

READY TO USE

REMOVES CURED AND UNCURED URETHANE ADHESIVES

RESIDUE FREE



#### ULTIMATE™ ADHESIVE REMOVER

Item No.	Item	Size	Units/pallet	Pail/Case UPC Code
30850832	Liquid	1 quart - 12/case	48 cases	747224656094
30612734	Towels	1 canister - 6/case	120 cases	747224656018

## Cartridge Guns

### CARTRIDGE DISPENSING GUNS

Bostik high-quality cartridge guns are designed to last and to make your job easier. Our standard 7:1 and 12:1 drives are perfect for lower viscosity products, whereas our higher deluxe 18:1 and 26:1 drives are perfect for the higher viscosity hardwood adhesives and construction sealants.

STANDARD 7:1 AND 12:1 DRIVES FOR LOWER VISCOSITY PRODUCTS

DELUXE 18:1 AND 26:1 DRIVE FOR VERY VISCOUS PRODUCTS

10.1 OZ, 20 OZ, AND 28 OZ SIZES



#### CARTRIDGE GUNS

Item No.	Size	Drive
30852242	Manual 10 oz	Standard 7:1 Drive
30852243	Manual 10 oz	Deluxe 26:1 Drive
30852244	Manual 28 oz	Deluxe 26:1 Drive

#### SAUSAGE GUNS

Item No.	Size	Drive
30616051	Manual 20 oz	Standard 12:1 Drive
30618568	Manual 20 oz	Deluxe 18:1 Drive



# Bostik Pro Rewards™ Contractor Loyalty Program

Now you can earn valuable reward points that can be redeemed for thousands of brand-name items or travel rewards, all while growing your business!

To join the **Bostik Pro Rewards™** contractor loyalty program, visit: [www.awardlink.com/Bostik](http://www.awardlink.com/Bostik) where you'll be asked to create a username and password for your account.

1. Submit your invoices via the ProRewards™ program web portal for eligible Bostik product purchases.
2. All qualifying Bostik product purchases will earn points deposited directly into your **Bostik Pro Rewards™** account.
3. Redeem the points you've earned for a wide variety of great rewards!



**Bostik, Inc.**  
 11320 W. Watertown Plank Road  
 Wauwatosa, WI 53226  
[www.bostik.com/us](http://www.bostik.com/us)

**JOIN NOW!**  
[www.awardlink.com/Bostik](http://www.awardlink.com/Bostik)