



SAFETY DATA SHEET

In accordance with OSHA 29 CFR 1910.1200

MULTIGRIP(TM)
Revision Number 2

Revision date 03-Apr-2024
Supersedes Date: 20-Oct-2016

1. Identification

1.1. Product identifier

Product Name MULTIGRIP(TM)

Other means of identification

Other information Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives
Restrictions on use No information available

1.3. Details of the supplier of the safety data sheet

Responsible Party

Bostik Inc.
11320 W. Watertown Plank Road
Wauwatosa, Wisconsin 53226 USA
Phone: +1(800) 726-7845 (Domestic Toll Free)
Phone: +1 (414) 774-2250 (International)

E-mail msds@bostik.com

1.4. Emergency telephone number

Emergency Telephone CHEMTREC (Chemical Transportation Emergency Center)
Chemtrec: 1-800-424-9300 (US) , 1-703-527-3887 (Outside U.S.)
Rocky Mountain Poison Center: 1-866-767-5089

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Respiratory sensitization	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 2
Flammable liquids	Category 4

Hazards not otherwise classified (HNOC)

Not applicable

2.2. Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

May cause allergy or asthma symptoms or breathing difficulties if inhaled
May cause an allergic skin reaction
Suspected of causing cancer

SAFETY DATA SHEET

MULTIGRIP(TM)
Revision Number 2

Revision date 03-Apr-2024
Supersedes Date: 20-Oct-2016

May cause damage to organs through prolonged or repeated exposure
Combustible liquid



Appearance Paste **Physical state** Liquid **Odor** No information available

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wear protective gloves/protective clothing/eye protection/face protection
In case of inadequate ventilation wear respiratory protection
Contaminated work clothing must not be allowed out of the workplace
Do not breathe dust/fume/gas/mist/vapors/spray
Keep away from flames and hot surfaces. - No smoking

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
IF ON SKIN: Wash with plenty of water and soap
If skin irritation or rash occurs: Get medical advice/attention
Wash contaminated clothing before reuse
IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing
If experiencing respiratory symptoms: Call a POISON CENTER or doctor
In case of fire: Use CO₂, dry chemical, or foam to extinguish

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

14 % of the mixture consists of ingredient(s) of unknown toxicity

2.3. Other Information

Causes mild skin irritation.

3. Composition/information on ingredients

3.1. Substances

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%
Naphtha (petroleum), hydrotreated heavy, <0.1% Benzene	64742-48-9	1 - <5
4,4'-Methylenediphenyl diisocyanate	101-68-8	1 - <5
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	1 - <5

SAFETY DATA SHEET

MULTIGRIP(TM)
Revision Number 2

Revision date 03-Apr-2024
Supersedes Date: 20-Oct-2016

Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer, isobutyl alcohol-blocked	201615-11-4	0.1 - <1
Quartz	14808-60-7	0.1 - <1
Benzenesulfonyl isocyanate, 4-methyl-	4083-64-1	0.1 - <1
N-(trichloromethylthio)phthalimide	133-07-3	0.1 - <1

**The exact percentage (concentration) of composition has been withheld as a trade secret*

4. First-aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.
Inhalation	May cause allergic respiratory reaction. Remove to fresh air. Give artificial respiration if victim is not breathing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If symptoms persist, call a physician.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	May cause an allergic skin reaction. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Take off contaminated clothing and wash before reuse. In the case of skin irritation or allergic reactions see a physician.
Ingestion	May produce an allergic reaction. Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Get immediate medical attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. See section 8 for more information.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/ or wheezing. Itching. Rashes. Hives. Prolonged contact may cause redness and irritation.
Effects of Exposure	No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians	May cause sensitization in susceptible persons. Treat symptomatically.
---------------------------	--

5. Fire-fighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray. Alcohol resistant foam. Move containers from fire area if you can do it without risk. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.

SAFETY DATA SHEET

MULTIGRIP(TM)
Revision Number 2

Revision date 03-Apr-2024
Supersedes Date: 20-Oct-2016

Unsuitable extinguishing media CAUTION: All these products have a very low flash point: Use of water spray when fighting fire may be inefficient.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Product is or contains a sensitizer. May cause sensitization by inhalation. May cause sensitization by skin contact. In the event of fire, cool tanks with water spray. Vapors may form explosive mixture with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. Vapors may spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Keep product and empty container away from heat and sources of ignition. Risk of ignition.

Hazardous combustion products Carbon oxides. Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Hydrogen cyanide. Isocyanates.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do it without risk. Evacuate personnel to safe areas. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation.

Other information Water spray may reduce vapor; but may not prevent ignition in closed spaces. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Environmental precautions Prevent entry into waterways, sewers, basements or confined areas. Do not flush into surface water or sanitary sewer system. Prevent product from entering drains. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of liquid spill for later disposal. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Methods for cleaning up Use personal protective equipment as required. Dam up. Soak up with inert absorbent material. Use clean non-sparking tools to collect absorbed material. Pick up and transfer to properly labeled containers. Take precautionary measures against static discharges. Clean contaminated surface thoroughly.

SAFETY DATA SHEET

MULTIGRIP(TM)
Revision Number 2

Revision date 03-Apr-2024
Supersedes Date: 20-Oct-2016

Reference to other sections See section 8 for more information. See section 13 for more information.

7. Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Do not breathe vapor or mist. In case of insufficient ventilation, wear suitable respiratory equipment. Use with local exhaust ventilation. Ground and bond all lines and equipment associated with product system. All equipment should be non-sparking and explosion proof. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Take off contaminated clothing and wash before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children.

Recommended storage temperature Keep at temperatures between 50 and 95 °F / 10 and 35 °C.

7.3 References to other sections

Reference to other sections

Section 10: STABILITY AND REACTIVITY
Section 13: DISPOSAL CONSIDERATIONS

8. Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product. The following ingredients are the only ingredients of the product above the cut-off level (or level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other recommended limit. At this time, the other relevant constituents have no known exposure limits from the sources listed here.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
4,4'-Methylenediphenyl diisocyanate 101-68-8	TWA: 0.005 ppm	(vacated) Ceiling: 0.02 ppm regulated under Methylene bisphenyl isocyanate (vacated) Ceiling: 0.2 mg/m ³ regulated under Methylene bisphenyl isocyanate Ceiling: 0.02 ppm Ceiling: 0.2 mg/m ³	IDLH: 75 mg/m ³ Ceiling: 0.020 ppm 10 min Ceiling: 0.2 mg/m ³ 10 min TWA: 0.005 ppm TWA: 0.05 mg/m ³
Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 µg/m ³ (vacated) TWA: 0.1 mg/m ³ respirable dust	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust

SAFETY DATA SHEET

MULTIGRIP(TM)
Revision Number 2

Revision date 03-Apr-2024
Supersedes Date: 20-Oct-2016

		: (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	
N-(trichloromethylthio)phthalimide 133-07-3	TWA: 1 mg/m ³ inhalable particulate matter dermal sensitizer	-	-

Chemical name	Argentina	Brazil	S.D. 594/1999	Colombia
4,4'-Methylenediphenyl diisocyanate 101-68-8	TWA: 0.005 ppm	TWA: 0.005 ppm	LPP: 0.004 ppm LPP: 0.05 mg/m ³	TWA: 0.005ppm
Quartz 14808-60-7	TWA: 0.05 mg/m ³	TWA: 0.025 mg/m ³	LPP: 0.08 mg/m ³	TWA: 0.025mg/m ³
N-(trichloromethylthio)phthalimide 133-07-3	-	TWA: 1 mg/m ³	-	TWA: 1mg/m ³

Chemical name	Costa Rica	Peru	Uruguay	Venezuela
4,4'-Methylenediphenyl diisocyanate 101-68-8	TWA: 0.005ppm	TWA: 0.005ppm TWA: 0.051mg/m ³	0.005 ppm TWA (listed under Methylene bisphenyl isocyanate (MDI))	TWA: 0.005 ppm
Quartz 14808-60-7	TWA: 0.025mg/m ³	TWA: 0.05mg/m ³	0.025 mg/m ³ TWA (respirable particulate matter)	TWA: 0.025 mg/m ³
N-(trichloromethylthio)phthalimide 133-07-3	-	-	1 mg/m ³ TWA (inhalable particulate matter)	-

8.2. Exposure controls

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles. Avoid contact with eyes.

Hand protection Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.

Skin and body protection Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed

SAFETY DATA SHEET

MULTIGRIP(TM)
Revision Number 2

Revision date 03-Apr-2024
Supersedes Date: 20-Oct-2016

out of the workplace. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Regular cleaning of equipment, work area and clothing is recommended.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Paste
Color	Cream
Odor	No information available
Odor threshold	No information available

Property	Values	Remarks • Method
pH	No data available	None known
pH (as aqueous solution)	No data available	None known
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	172 °C / 341.6 °F	
Flash point	63 °C / 145.4 °F	
Evaporation rate	No data available	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	None known
Relative vapor density	No data available	None known
Relative density	No data available	None known
Water solubility	No data available	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

9.2. Other information

Explosive properties	No information available	
Oxidizing properties	No information available	
Solvent content (%)	No information available	
Solid content (%)	94.6	
Softening point	No information available	
Molecular weight	No information available	
VOC content		No information available
Liquid Density	1.649 g/cm ³	
Bulk density	No information available	

10. Stability and reactivity

10.1. Reactivity

Reactivity	No information available.
------------	---------------------------

SAFETY DATA SHEET

MULTIGRIP(TM)
Revision Number 2

Revision date 03-Apr-2024
Supersedes Date: 20-Oct-2016

10.2. Chemical stability

Chemical stability Stable under normal conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Hazardous polymerization Hazardous polymerization may occur.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None known based on information supplied

11. Toxicological information

11.1. Information on toxicological effects

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause sensitization in susceptible persons. (based on components).
Eye contact	Based on available data, the classification criteria are not met.
Skin contact	Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). May cause sensitization by skin contact. Causes mild skin irritation.
Ingestion	Specific test data for the substance or mixture is not available. May cause additional affects as listed under "Inhalation".

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Coughing and/ or wheezing. Itching. Rashes. Hives. Prolonged contact may cause redness and irritation.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	>5000 mg/kg
ATEmix (dermal)	96,684.30 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	24.30 mg/l
ATEmix (inhalation-vapor)	>20 mg/l

SAFETY DATA SHEET

MULTIGRIP(TM)
Revision Number 2

Revision date 03-Apr-2024
Supersedes Date: 20-Oct-2016

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Naphtha (petroleum), hydrotreated heavy, <0.1% Benzene 64742-48-9	>6000 mg/kg (Rattus)	> 3160 mg/kg (Oryctolagus cuniculus)	>8500 mg/m ³ (Rattus) 4 h
4,4'-Methylenediphenyl diisocyanate 101-68-8	=31600 mg/kg (Rattus) = 9200 mg/kg (Rattus)	LD 50 > 9400 mg/kg (Oryctolagus cuniculus) OECD 402	1.5 mg/L (Rattus) 4 h
o-(p-isocyanatobenzyl)phenyl isocyanate 5873-54-1	LD50 >2000 mg/Kg (Rattus)	LD 50 > 9400 mg/kg (Oryctolagus cuniculus) OECD 402	1.5 mg/L (4h) Rat
Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer, isobutyl alcohol-blocked 201615-11-4	LD50 (Rat): Estimated > 2,500 mg/kg OECD 423	LD50 (Rattus): > 2,000 mg/kg OECD 402	ATE 1.5 mg/L
Quartz 14808-60-7	>2000 mg/kg (Rattus)	-	-
Benzenesulfonyl isocyanate, 4-methyl- 4083-64-1	=2234 mg/kg (Rattus)	LD 50 (Rattus) > 2000 mg/kg OECD 402	>640 ppm (Rattus) 1 h
N-(trichloromethylthio)phthalimide 133-07-3	=2636 mg/kg (Rattus)	> 22600 mg/kg (Oryctolagus cuniculus) > 5000 mg/kg (Rattus)	>0.48 g/m ³ (Rattus) 4 h > 5 g/m ³ (Rattus) 2 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes mild skin irritation.

o-(p-isocyanatobenzyl)phenyl isocyanate (5873-54-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit				irritant

Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer, isobutyl alcohol-blocked (201615-11-4)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			May cause transient irritation

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

4,4'-Methylenediphenyl diisocyanate (101-68-8)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye	0.1 mL	24 hours	Non-irritant

Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer, isobutyl alcohol-blocked (201615-11-4)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			May cause transient irritation

SAFETY DATA SHEET

MULTIGRIP(TM)
Revision Number 2

Revision date 03-Apr-2024
Supersedes Date: 20-Oct-2016

Respiratory or skin sensitization May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer, isobutyl alcohol-blocked (201615-11-4)

Method	Species	Results
OECD Test No. 471: Bacterial Reverse Mutation Test	Hamster, in vitro	Not mutagenic in AMES Test
OECD Test No. 475: Mammalian Bone Marrow Chromosome Aberration Test	Mouse, in vivo	Not mutagenic

Carcinogenicity Contains a known or suspected carcinogen. This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product. Classification based on data available for ingredients.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
4,4'-Methylenediphenyl diisocyanate 101-68-8	-	Group 3	-	-
Quartz 14808-60-7	A2	Group 1	Known	X
N-(trichloromethylthio)phthalimide 133-07-3	A3	-	-	-

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

4,4'-Methylenediphenyl diisocyanate (101-68-8)

Method	Species	Results
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat	Limited evidence of a carcinogenic effect

o-(p-isocyanatobenzyl)phenyl isocyanate (5873-54-1)

Method	Species	Results
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat	Carcinogenic

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

Other adverse effects No information available.

SAFETY DATA SHEET

MULTIGRIP(TM)
Revision Number 2

Revision date 03-Apr-2024
Supersedes Date: 20-Oct-2016

Interactive effects No information available.

12. Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Naphtha (petroleum), hydrotreated heavy, <0.1% Benzene 64742-48-9	-	LC50: =2200mg/L (96h, Pimephales promelas)	-	LC50: =2.6mg/L (96h, Chaetogammarus marinus)
4,4'-Methylenediphenyl diisocyanate 101-68-8	ErC50 (72h) >1640 mg/L Algae (scenedesmus subspicatus) (OECD 201)	>1000 mg/l Danio rerio	-	EC50 (24H) >1000 mg/L Daphnia magna
o-(p-isocyanatobenzyl)phenyl isocyanate 5873-54-1	ErC50 (72h) >1640 mg/L Algae (scenedesmus subspicatus) (OECD 201)	LC50 (96 h) > 1000 mg/l Danio rerio (OECD 203)	-	EC50 (24H) >1000 mg/L Daphnia magna
Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer, isobutyl alcohol-blocked 201615-11-4	EC50 72hr : > 1,000 mg/l (Desmodesmus subspicatus (green algae)) OECD 201	LC0 96hr : > 100 mg/l (Danio rerio (zebra fish)) OECD 203	-	EC0 48hr : > 100 mg/l (Daphnia magna (Water flea)) OECD 202

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
4,4'-Methylenediphenyl diisocyanate 101-68-8	4.51
Benzenesulfonyl isocyanate, 4-methyl- 4083-64-1	0.6

12.4. Mobility in soil

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

13. Disposal considerations

SAFETY DATA SHEET

MULTIGRIP(TM)
Revision Number 2

Revision date 03-Apr-2024
Supersedes Date: 20-Oct-2016

13.1. Waste treatment methods

Waste from residues/unused products

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Contaminated packaging

Dispose of in accordance with federal, state and local regulations.

14. Transport information

Note: DOT Ground - "Non-bulk shipments may be non-regulated per 49CFR 173.150(f)(2)".

DOT

UN number or ID number	NA1993
UN proper shipping name	Combustible liquid, n.o.s.
Transport hazard class(es)	Combustible liquid
Packing group	III
Reportable quantity (lbs)	Chlorobenzene: RQ (lb)= 1.00
Special Provisions	IB3, T1, TP1, 148
DOT Marine Pollutant	NP
Description	NA1993, Combustible liquid, n.o.s. (Naphtha (petroleum), hydrotreated heavy, <0.1% Benzene), III
Emergency Response Guide Number	128

IATA Not regulated

IMDG Not regulated

15. Regulatory information

International Inventories

TSCA	Listed
DSL	Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

Listed - The components of this product are either listed or exempt from listing on inventory.

Not Listed - One or more components of this product are not listed on inventory.

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	CAS No.	SARA 313 - Threshold Values %
4,4'-Methylenediphenyl diisocyanate	101-68-8	1.0
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	1.0
N-(trichloromethylthio)phthalimide	133-07-3	1.0

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate

SAFETY DATA SHEET

MULTIGRIP(TM)
Revision Number 2

Revision date 03-Apr-2024
Supersedes Date: 20-Oct-2016

classifications.

Europe

Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation. This document is based on the information given to us by our own suppliers at the date of this document.

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

16. Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	Sk*	Skin designation

Prepared By Product Safety & Regulatory Affairs.

Revision date 03-Apr-2024

Revision Note SDS sections updated. 2. 3.

Disclaimer

All information contained herein is believed to be accurate as of the date of publication, is provided "as-is" and is subject to change without notice. This is not a warranty, an agreement, or substitute for expert or professional advice. Bostik Inc. ("Company") expressly disclaims and assumes no liability for the use of the products or reliance on this information. It is the sole responsibility of the user to determine the suitability of any products for user's application(s). NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED (INCLUDING SUITABILITY FOR USE IN ANY MEDICAL DEVICE OR MEDICAL APPLICATION), IS MADE CONCERNING THE PRODUCTS OR THE INFORMATION PROVIDED HEREIN. The information provided relates only to the specific products designated herein and may not be valid where such products are used in combination with other materials or in any process. The performance of the product, its shelf life, and application characteristics depends on many variables, and changes in these variables can impact product performance. You are responsible to test the suitability of any product in advance for any intended use or application and before commercialization. Nothing herein shall be construed as a license for the use of any product in a manner that might infringe any patent and it should not be construed as an inducement to infringe any patent. Please carefully review the Safety Data Sheet for the product.

The Company adheres to a strict policy that applies to the use of any of its products in medical device applications. This policy can be found at <https://www.arkema.com/global/en/social-responsibility/innovation-and-sustainable-solutions/responsible-product-management/medical-device-policy/> which is incorporated herein by reference and made a part hereof. Except as expressly authorized, the Company (i) has designated specific medical grade compositions for products used in medical device applications and Company products not so designated are not authorized for use in medical device applications and (ii) strictly prohibits the use of any of its products in medical device applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. The Company does not design, manufacture and/or directly sell any medical devices. The Company does not co-design, or offer assistance to any purchaser of its products, in their design, manufacture and/or sale of products for medical devices. It is the sole responsibility of the manufacturer of medical

SAFETY DATA SHEET

MULTIGRIP(TM)
Revision Number 2

Revision date 03-Apr-2024
Supersedes Date: 20-Oct-2016

devices to determine the suitability of all raw material, products and components, including any medical grade products, in order to ensure that the medical device is safe for end-use and complies with all applicable legal and regulatory requirements and to conduct all necessary tests and inspections.

End of Safety Data Sheet