

## SAFETY DATA SHEET

Issue Date 04-May-2020 Revision Date 27-Jul-2020 Version 2

BR **Brickform Refresh** 

#### 1. IDENTIFICATION

Product identifier

**Product Name** Brickform Refresh

Other means of identification

**Product Code** BR

Recommended use of the chemical and restrictions on use

**Recommended Use** Restricted to professional users.

Consumer use Uses advised against

#### Details of the supplier of the safety data sheet

Manufacturer Address Solomon Colors, Inc. 4050 Color Plant Road Springfield, IL

62702

**Company Phone Number** 800-624-0261 (US & Canada); 217-522-3112 (Outside North America)

24 Hour Emergency Phone Number 800-373-7542

## 2. HAZARDS IDENTIFICATION

#### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single	Category 3
exposure)	
Flammable liquids	Category 2

#### Label elements

## **Emergency Overview**

## Danger

#### Hazard statements

Causes serious eye irritation

Suspected of damaging fertility or the unborn child

May cause respiratory irritation. May cause drowsiness or dizziness

Highly flammable liquid and vapor



Appearance Clear liquid Physical state Liquid Odor Aromatic

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Use explosion-proof electrical/ventilating/lighting/equipment

Keep cool

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

In case of fire: Use CO2, dry chemical, or foam for extinction

#### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Other Information

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Acetone	67-64-1	50-75	*
Dimethyl carbonate	616-38-6	10-25	*
Parachlorobenzotrifluoride	98-56-6	2-7	*
Toluene	108-88-3	< 0.5	*

This product also contains trace amounts of ethylbenzene, xylene, and ethanol (impurities).

#### 4. FIRST AID MEASURES

BR 2 / 11 Brickform Refresh

#### Description of first aid measures

General advice In case of accident or unwellness, seek medical advice immediately (show directions for

use or safety data sheet if possible).

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Skin Contact IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

**Inhalation** IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If breathing has stopped, give artificial respiration. Get medical attention

immediately.

Ingestion If swallowed, do not induce vomiting: seek medical advice immediately and show this

container or label.

#### Most important symptoms and effects, both acute and delayed

Symptoms Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May

cause irritation of the respiratory system, drowsiness, or dizziness.

#### Indication of any immediate medical attention and special treatment needed

#### 5. FIRE-FIGHTING MEASURES

#### Suitable extinguishing media

Water. Dry chemical, Carbon Dioxide, Foam, Sand. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

#### Specific hazards arising from the chemical

HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Keep product and empty container away from heat and sources of ignition.

Hazardous combustion products Thermal decomposition can lead to the release of irritating gases and vapors. Carbon monoxide. Carbon dioxide (CO2). Formaldehyde. Methanol.

**Explosion data** 

Sensitivity to Mechanical Impact No data available.

Sensitivity to Static Discharge May be ignited by heat, sparks or flames.

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

## Personal precautions, protective equipment and emergency procedures

Personal precautions Keep people away from and upwind of spill/leak. Wear protective gloves/protective clothing

and eye/face protection. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be

grounded.

**Environmental precautions** 

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or

sanitary sewer system. See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. Contain and collect spillage with

non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

Methods for cleaning up

Use clean non-sparking tools to collect absorbed material. Ground and bond containers

when transferring material. Dike to collect large liquid spills.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

#### 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Use personal

protective equipment as required. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be

grounded. Never pierce, drill, grind, cut, saw or weld any empty container.

#### Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity). Keep container tightly closed in a dry and well-ventilated place. Do not store near combustible materials. Use spark-proof tools and explosion-proof

equipment.

**Incompatible materials** Strong oxidizing agents.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

**Exposure Guidelines** 

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL: 500 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 250 ppm	TWA: 2400 mg/m <sup>3</sup>	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m <sup>3</sup>
		(vacated) TWA: 1800 mg/m <sup>3</sup>	
		(vacated) STEL: 2400 mg/m <sup>3</sup> The	
		acetone STEL does not apply to the	
		cellulose acetate fiber industry. It is	
		in effect for all other sectors.	
		(vacated) STEL: 1000 ppm	
Parachlorobenzotrifluoride	TWA: 2.5 mg/m <sup>3</sup> F	TWA: 2.5 mg/m <sup>3</sup> F	IDLH: 250 mg/m <sup>3</sup> F
98-56-6		(vacated) TWA: 2.5 mg/m <sup>3</sup>	
Toluene	TWA: 20 ppm	TWA: 200 ppm	IDLH: 500 ppm
108-88-3		(vacated) TWA: 100 ppm	TWA: 100 ppm
		(vacated) TWA: 375 mg/m <sup>3</sup>	TWA: 375 mg/m <sup>3</sup>
		(vacated) STEL: 150 ppm	STEL: 150 ppm
		(vacated) STEL: 560 mg/m <sup>3</sup>	STEL: 560 mg/m <sup>3</sup>
		Ceiling: 300 ppm	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d

962 (11th Cir., 1992).

Appropriate engineering controls

**Engineering Controls** Showers

> Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles. Avoid contact with eyes.

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, Skin and body protection

as appropriate, to prevent skin contact.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

**General Hygiene Considerations** Do not eat, drink or smoke when using this product. Handle in accordance with good

industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

Physical state Liquid

**Appearance** Clear liquid Aromatic Odor

Color Odor threshold No information available clear

Values Remarks • Method **Property** 

pН

No information available Melting point/freezing point No information available

54.2 °C / 129.6 °F 10.6 °C / 51 °F Boiling point / boiling range ASTM D86 ASTM D56 Flash point

**Evaporation rate** No information available Flammability (solid, gas) No information available

BR 5/11 **Brickform Refresh**  Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density
Specific Gravity

No information available
No information available
No information available
No information available

Water solubility Not Soluble

Solubility in other solvents No information available No information available Partition coefficient **Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available Dynamic viscosity No information available **Explosive properties** No information available No information available **Oxidizing properties** 

#### **Other Information**

Softening pointNo information availableMolecular weightNo information available

**VOC Content (%)** < 100 g/L **Density** 7-7.5 lbs/gal

Bulk density No information available

## 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

#### **Chemical stability**

Stable under recommended storage conditions.

## **Possibility of Hazardous Reactions**

None under normal processing.

## **Conditions to avoid**

Extremes of temperature and direct sunlight.

#### Incompatible materials

Strong oxidizing agents.

#### **Hazardous Decomposition Products**

Thermal decomposition can lead to release of irritating and toxic gases and vapors. Carbon oxides. Formaldehyde. Methanol.

#### 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

**Product Information**No acute toxicity information is available for this product The product is classified based on

the mixture components.

**Inhalation** May cause irritation of respiratory tract. May cause drowsiness or dizziness. Avoid

breathing vapors or mists.

**Eye contact** Avoid contact with eyes. Contact with eyes may cause irritation.

**Skin Contact** Avoid contact with skin. Substance may cause slight skin irritation.

**Ingestion** May be harmful if swallowed.

**Component Information** 

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg ( Rat )	> 15700 mg/kg (Rabbit)	= 50100 mg/m³(Rat)8 h
Dimethyl carbonate 616-38-6	= 13 g/kg ( Rat )	> 5 g/kg(Rabbit)	= 140 mg/L (Rat) 4 h
Parachlorobenzotrifluoride 98-56-6	= 13 g/kg ( Rat )	> 2 mL/kg(Rabbit)	= 33 mg/L (Rat) 4 h
Toluene 108-88-3	= 2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L (Rat) 4 h

#### Information on toxicological effects

Symptoms Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May

cause irritation of the respiratory system, drowsiness, or dizziness.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Not classified. (Based on mixture components.).

Serious eye damage/eye irritation Eye Irritation Cat 2. Causes serious eye irritation. (Classification based on mixture

components).

Sensitization Not Classified. This product does not contain known sensitizers at levels > or equal to

0.1%.

**Germ cell mutagenicity** Not classified. (Based on mixture components).

 Carcinogenicity
 The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Toluene	-	Group 3	-	-
108-88-3		,		

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

**Reproductive toxicity**Contains a known or suspected reproductive toxin.

**STOT - single exposure** Category 3. May cause irritation of respiratory tract. May cause dizziness or drowsiness.

STOT - repeated exposure Not classified. (Based on mixture components). Aspiration hazard Not classified. (Based on mixture components).

#### Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

 ATEmix (oral)
 6498.1 mg/kg

 ATEmix (dermal)
 9026.681 mg/kg

ATEmix (inhalation-dust/mist) 101 mg/l

## 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

This product has not been fully evaluated on the product level.

# Persistence and degradability No information available.

#### **Bioaccumulation**

No information available.

Chemical Name	Partition coefficient
Acetone	-0.24
67-64-1	
Parachlorobenzotrifluoride	3.7
98-56-6	
Toluene	2.7
108-88-3	

Other adverse effects No information available

## 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

Disposal should be in accordance with applicable regional, national and local laws and **Disposal of wastes** 

regulations.

Contaminated packaging Do not reuse container.

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
	Organic Compounds		<b>+</b>	
Toluene	-	-	Toxic waste	-
108-88-3			waste number F025	
			Waste description:	
			Condensed light ends, spent	
			filters and filter aids, and	
			spent desiccant wastes from	
			the production of certain	
			chlorinated aliphatic	
			hydrocarbons, by free	
			radical catalyzed processes.	
			These chlorinated aliphatic	
			hydrocarbons are those	
			having carbon chain lengths	
			, ,	
			ranging from one to and	
			including five, with varying	
			amounts and positions of	
			chlorine substitution.	

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Acetone 67-64-1	Ignitable
Toluene 108-88-3	Toxic Ignitable

## 14. TRANSPORT INFORMATION

DOT

**UN/ID no.** UN 1263

Proper shipping name Paint Related Material

Hazard Class 3
Packing Group II
Emergency Response Guide 128

Number

**TDG** 

**UN/ID no.** UN 1263

Proper shipping name Paint Related Material

Hazard Class 3
Packing Group ||

**MEX** 

**UN/ID no.** UN 1263

Proper shipping name Paint Related Material

Hazard Class 3
Packing Group ||

ICAO (air)

**UN/ID** no. UN 1263

Proper shipping name Paint Related Material

Hazard Class 3
Packing Group ||

**IATA** 

**UN/ID no.** UN 1263

Proper shipping name Paint Related Material

Hazard Class 3 Packing Group II

<u>IMDG</u>

**UN/ID no.** UN 1263

Proper shipping name Paint Related Material

Hazard Class 3
Packing Group ||

RID

**UN/ID no.** UN 1263

Proper shipping name Paint Related Material

Hazard Class 3
Packing Group ||

ADR

**UN/ID no.** UN 1263

Proper shipping name Paint Related Material

Hazard Class 3
Packing Group ||

#### 15. REGULATORY INFORMATION

#### **International Inventories**

**TSCA** Complies **DSL/NDSL** Complies **EINECS/ELINCS** Does not comply **ENCS** Complies Complies **IECSC** Complies **KECL PICCS** Complies **AICS** Complies

## Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

#### **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA): This product does not contain chemicals at levels that are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Toluene - 108-88-3	1.0
Xylene - 1330-20-7	1.0
Ethylbenzene - 100-41-4	0.1

#### SARA 311/312 Hazard Categories

See section 2 for more information

#### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene 108-88-3	1000 lb	X	X	Х

#### **CERCLA**

This material, as supplied, does not contain substances that would exceed the reportable quantity as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb	=	RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ
Toluene	1000 lb	<del>-</del>	RQ 1000 lb final RQ
108-88-3			RQ 454 kg final RQ

## **US State Regulations**

#### **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Parachlorobenzotrifluoride - 98-56-6	Carcinogen
Toluene - 108-88-3	Developmental
Ethanol - 64-17-5	Carcinogen

BR 10 / 11 Brickform Refresh

	Developmental
Ethylbenzene - 100-41-4	Carcinogen

#### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	Х	X	X
Dimethyl carbonate 616-38-6	Х	X	X
Parachlorobenzotrifluoride 98-56-6	X	-	-
Toluene 108-88-3	X	X	X
Ethanol 64-17-5	X	X	X
Butyl methacrylate 97-88-1	Х	X	X
Xylene 1330-20-7	Х	X	X
Ethylbenzene 100-41-4	Х	X	X

## 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 3 Flammability 3 Reactivity 0 Physical and Chemical

Properties -

HMIS Health hazards 3 Flammability 3 Physical hazards 0 Personal protection X

Prepared By Solomon Colors - Lab Technical Services

 Issue Date
 04-May-2020

 Revision Date
 27-Jul-2020

Revision Note Initial SDS

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**