

SAFETY DATA SHEET

Version 3

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200)

Revision Date 11-Feb-2021


1. Identification			
Product identifier			
Product Name	Brickform Gem-Seal 700		
Other means of identification			
Product Code	GS - 700		
Synonyms	None		
Recommended use of the chemical	and restrictions on use		
Recommended Use	Restricted to professional users		
Restrictions on use	Consumer use		
Details of the supplier of the safety	data sheet		
Supplier Address Solomon Colors, Inc. 4050 Color Plant Road Springfield, IL 62702	<u>Manufacturer Address</u> Solomon Colors, Inc. 4050 Color Plant Road Springfield, IL 62702		
Emergency telephone number			
Company Phone Number	800-624-0261 (US & Canada); 217-522-3112 (Outside North America)		
24 Hour Emergency Phone Number	800-373-7542		
Emergency Telephone	No information available		

2. Hazard(s) identification

Classification

Flammable liquids	Category 4
Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration hazard	Category 1

Hazards not otherwise classified (HNOC) Not applicable



Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Wear protective gloves/clothing and eye/face protection Use only outdoors or in a well-ventilated area Wash face, hands and any exposed skin thoroughly after handling Do not breathe dust/fume/gas/mist/vapors/spray Keep away from flames and hot surfaces. - No smoking Keep cool

Precautionary Statements - Response

Specific treatment see section 4 of the SDS. IF exposed or concerned: Get medical advice/attention IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of water and soap Call a POISON CENTER or doctor if you feel unwell Take off contaminated clothing and wash it before reuse If skin irritation occurs: Get medical advice/attention IF INHALED: Remove person to fresh air and keep comfortable for breathing IF SWALLOWED: Immediately call a POISON CENTER or doctor Do NOT induce vomiting In case of fire: Use CO2, dry chemical, or foam to extinguish

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Unknown acute toxicity

20.87 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity 63.87 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Other Information

No information available.

3. Composition/information on ingredients

Substance

Not applicable.

<u>Mixture</u>

Chemical name	CAS No	Weight-%	Trade secret
Petroleum naphtha, light aromatic	64742-95-6	40-45	*
Xylene	1330-20-7	20-30	*
Trimethylbenzene, Isomers	25551-13-7	< 25	*
1,2,4 Trimethylbenzene	95-63-6	< 13	*
Ethylbenzene	100-41-4	5-10	*
Cumene	98-82-8	< 1.5	*
Toluene	108-88-3	< 0.5	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. Immediate medical attention is required.	
Inhalation	Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical attention. Delayed pulmonary edema may occur.	
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.	
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.	
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical attention.	
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists. See section 8 for more information.	
Most important symptoms and effects, both acute and delayed		
Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause	

	symptoms like headache, dizziness, tiredness, nausea and vomiting.
Effects of Exposure	May cause cancer. May cause adverse reproductive effects - such as birth defect, miscarriages, or infertility. Mutagenic effects. May cause damage to organs through prolonged or repeated exposure.
Indication of any immediate m	edical attention and special treatment needed
Note to physicians	Because of the danger of aspiration, emesis or gastric lavage should not be employed

unless the risk is justified by the presence of additional toxic substances.

5. Fire-fighting measures

Suitable Extinguishing Media Large Fire	Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam. CAUTION: Use of water spray when fighting fire may be inefficient.	
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.	
Specific hazards arising from the chemical	Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray.	
Hazardous combustion products	Carbon oxides.	
Explosion data Sensitivity to mechanical impact None.		
Sensitivity to static discharge	Yes.	
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.	

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Take precautionary measures against static discharges. Do not touch or walk through spilled material. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Avoid breathing vapors or mists.		
Other information	Refer to protective measures listed in Sections 7 and 8.		
Methods and material for containment and cleaning up			
Methods for containment	Stop leak if you can do it without risk. Do not touch or walk through spilled material. Dike far ahead of liquid spill for later disposal.		
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.		

7. Handling and storage

Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Do not breathe vapor or mist. Keep away from heat, hot

surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Use with local exhaust ventilation. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

8. Exposure controls/personal protection

Control parameters

Exposure Limits

The following ingredients are the only ingredients of the product above the cut-off level (or level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other recommended limit. At this time, the other relevant constituents have no known exposure limits from the sources listed here.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Xylene 1330-20-7	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-
Trimethylbenzene, Isomers 25551-13-7	TWA: 10 ppm	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m ³	-
1,2,4 Trimethylbenzene 95-63-6	TWA: 10 ppm	-	TWA: 25 ppm TWA: 125 mg/m ³
Ethylbenzene 100-41-4	Ototoxicant - potential to cause hearing disorders TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
Cumene 98-82-8	TWA: 5 ppm	TWA: 50 ppm TWA: 245 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m ³ (vacated) S* S*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m ³
Toluene 108-88-3	Ototoxicant - potential to cause hearing disorders TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³

Biological occupational exposure limits

Chemical name

ACGIH

Xylene 1330-20-7	1.5 g/g creatinine - urine (Methylhippuric acids) - end of shift
Ethylbenzene 100-41-4	0.15 g/g creatinine - urine (Sum of mandelic acid and phenylglyoxylic acid) - end of shift
Toluene 108-88-3	0.02 mg/L - blood (Toluene) - prior to last shift of workweek 0.03 mg/L - urine (Toluene) - end of shift 0.3 mg/g creatinine - urine (o-Cresol with hydrolysis) - end of shift

Appropriate engineering controls

Engineering controls	Showers Eyewash stations Ventilation systems.
Individual protection measures, su	ch as personal protective equipment
Eye/face protection	Tight sealing safety goggles.
Hand protection	Wear suitable gloves. Impervious gloves.
Skin and body protection	Wear suitable protective clothing. Long sleeved clothing.
Respiratory protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
General hygiene considerations	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

9. Physical and chemical properties

Physical state	Liquid	
Appearance	Viscous	
Color	Colorless	
Odor	Solvent	
Odor threshold	No information available	
Property_	Values_	Remarks • Method
pH	No data available	None known
pH (as aqueous solution)		None known
Melting point/freezing point	No data available	None known
Boiling point / boiling range	132.11 °C / 269.8 °F	ASTM D86
Flash point	63.28 °C / 145.9 °F	ASTM D56
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit:	No data available	
Lower flammability limit:	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	No data available	None known
Water solubility	No data available	insoluble
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known

Kinematic viscosity Dynamic viscosity	No data available No data available	None known None known
Other information		
Explosive properties	No information available	
Oxidizing properties	No information available	
Softening point	No information available	
Molecular weight	No information available	
VOC Content (%)	<700 g/L	
Density	No information available	
Bulk density	No information available	
-		

10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Hazardous polymerization	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. Excessive heat.
Incompatible materials	Strong acids. Strong bases. Strong oxidizing agents.

Hazardous decomposition products None known based on information supplied.

44. Taula de ala al information	
11. Toxicological information	

Information on likely routes of exposure

Product Information				
Inhalation	Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness. Harmful by inhalation. (based on components).			
Eye contact	Specific test data for the substance or mixture is not available. May cause irritation. Causes serious eye irritation. May cause redness, itching, and pain. (based on components).			
Skin contact	Repeated exposure may cause skin dryness or cracking. Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).			
Ingestion	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.			
Symptoms related to the physical, chemical and toxicological characteristics				
Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.			
Acute toxicity	Harmful by skin contact. Harmful by inhalation.			
Numerical measures of toxicity				

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	4,683.70 mg/kg
ATEmix (dermal)	1,606.60 mg/kg
ATEmix (inhalation-gas)	> 5,000 ppm
ATEmix (inhalation-vapor)	1,656.60 mg/l
ATEmix (inhalation-dust/mist)	1.20 mg/l

Unknown acute toxicity

20.87 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

63.87 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum naphtha, light aromatic 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat)4 h
Xylene 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat)4 h
Trimethylbenzene, Isomers 25551-13-7	= 8970 mg/kg (Rat)	-	-
1,2,4 Trimethylbenzene 95-63-6	= 3280 mg/kg (Rat)	>3160 mg/kg (Rabbit)	= 18 g/m³ (Rat)4 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat)4 h
Cumene 98-82-8	= 1400 mg/kg (Rat)	= 12300 µL/kg (Rabbit)	> 3577 ppm (Rat)6 h
Toluene 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat)4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Classification based on data available for ingredients. Causes skin irritation. May cause skin irritation.	
Serious eye damage/eye irritation	Classification based on data available for ingredients. Causes serious eye irritation.	
Respiratory or skin sensitization	Based on available data, the classification criteria are not met.	
Germ cell mutagenicity	Contains a known or suspected mutagen. Classification based on data available for ingredients. May cause genetic defects.	

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

T I (I I I I I I I I (1 41 1		P 4 5
I he table below indicates	whether each agen	rv has listed anv ir	ngredient as a carcinogen.
	whole caon agon	by mas noted any n	igreaterit as a careinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7	-	Group 3	-	-
Ethylbenzene 100-41-4	A3	Group 2B	-	Х
Cumene 98-82-8	A3	Group 2B	Reasonably Anticipated	Х
Toluene 108-88-3	-	Group 3	-	-

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer) Group 2B - Possibly Carcinogenic to Humans Group 3 - Not Classifiable as to Carcinogenicity in Humans NTP (National Toxicology Program) Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen OSHA (Occupational Safety and Health Administration of the US Department of Labor) X - Present

Reproductive toxicity	Classification based on data available for ingredients. Suspected of damaging fertility or the unborn child.	
STOT - single exposure	May cause drowsiness or dizziness.	
STOT - repeated exposure	May cause damage to organs through prolonged or repeated exposure.	
Target organ effects	Central nervous system, Eyes, Respiratory system, Skin, Blood.	
Aspiration hazard	May be fatal if swallowed and enters airways.	
Other adverse effects	No information available.	
Interactive effects	No information available.	

12. Ecological information

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Petroleum naphtha, light aromatic 64742-95-6	-	LC50: =9.22mg/L (96h, Oncorhynchus mykiss)	-	EC50: =6.14mg/L (48h, Daphnia magna)
Xylene 1330-20-7	-	LC50: =13.4mg/L (96h, Pimephales promelas) LC50: 2.661 - 4.093mg/L (96h, Oncorhynchus mykiss) LC50: 13.5 - 17.3mg/L (96h, Oncorhynchus mykiss) LC50: 13.1 - 16.5mg/L (96h, Lepomis macrochirus) LC50: =19mg/L (96h, Lepomis macrochirus) LC50: 7.711 - 9.591mg/L (96h, Lepomis macrochirus) LC50: 23.53 - 29.97mg/L (96h, Pimephales promelas) LC50: =780mg/L (96h,	EC50 = 0.0084 mg/L 24 h	EC50: =3.82mg/L (48h, water flea) LC50: =0.6mg/L (48h, Gammarus lacustris)

rr		- · · · ·	1	
		Cyprinus carpio)		
		LC50: >780mg/L (96h,		
		Cyprinus carpio)		
		LC50: 30.26 - 40.75mg/L		
		(96h, Poecilia reticulata)		
Trimethylbenzene,	-	LC50: =7.72mg/L (96h,	-	-
Isomers		Pimephales promelas)		
25551-13-7		,		
1,2,4 Trimethylbenzene	_	LC50: 7.19 - 8.28mg/L	_	EC50: =6.14mg/L (48h,
95-63-6		(96h, Pimephales		Daphnia magna)
		promelas)		2 apraag
Ethylbenzene	EC50: =4.6mg/L (72h,	LC50: 11.0 - 18.0mg/L	EC50 = 9.68 mg/L 30 min	EC50: 1.8 - 2.4 mg/l (48h)
100-41-4	Pseudokirchneriella	(96h, Oncorhynchus	EC50 = 96 mg/L 24 h	Daphnia magna)
100 41 4	subcapitata)	mykiss)	2000 = 00 mg/2 24 m	Daprina magnay
	EC50: >438mg/L (96h,	LC50: =4.2mg/L (96h,		
	Pseudokirchneriella	Oncorhynchus mykiss)		
	subcapitata)	LC50: 7.55 - 11mg/L (96h,		
	EC50: 2.6 - 11.3mg/L	Pimephales promelas)		
	(72h, Pseudokirchneriella	LC50: =32mg/L (96h,		
	subcapitata)	Lepomis macrochirus)		
	EC50: 1.7 - 7.6mg/L (96h,	LC50: 9.1 - 15.6mg/L		
	Pseudokirchneriella	(96h, Pimephales		
	subcapitata)	promelas)		
		LC50: =9.6mg/L (96h,		
		Poecilia reticulata)		
Cumene	EC50: =2.6mg/L (72h,	LC50: 6.04 - 6.61mg/L	EC50 = 0.89 mg/L 5 min	EC50: =0.6mg/L (48h,
98-82-8	Pseudokirchneriella	(96h, Pimephales	EC50 = 1.10 mg/L 15 min	
	subcapitata)	promelas)	EC50 = 1.48 mg/L 30 min	EC50: 7.9 - 14.1mg/L
		LC50: =4.8mg/L (96h,	EC50 = 172 mg/L 24 h	(48h, Daphnia magna)
		Oncorhynchus mykiss)		
		LC50: =2.7mg/L (96h,		
		Oncorhynchus mykiss)		
		LC50: =5.1mg/L (96h,		
		Poecilia reticulata)		
Toluene	EC50: >433mg/L (96h,		EC50 = 19.7 mg/L 30 min	EC50: 5.46 - 9.83mg/L
108-88-3	Pseudokirchneriella	(96h, Pimephales		(48h, Daphnia magna)
100 00 0	subcapitata)	promelas)		EC50: =11.5mg/L (48h,
	EC50: =12.5mg/L (72h,	LC50: =12.6mg/L (96h,		Daphnia magna)
	Pseudokirchneriella	Pimephales promelas)		Dapinia magnay
	subcapitata)	LC50: 5.89 - 7.81mg/L		
	Subcapitata)	(96h, Oncorhynchus		
		mykiss)		
		LC50: 14.1 - 17.16mg/L		
		(96h, Oncorhynchus		
		mykiss)		
		LC50: =5.8mg/L (96h,		
		Oncorhynchus mykiss)		
		LC50: 11.0 - 15.0mg/L		
		(96h, Lepomis		
		macrochirus)		
		LC50: =54mg/L (96h,		
		Oryzias latipes)		
		LC50: =28.2mg/L (96h,		
		Poecilia reticulata)		
		Poecilia reticulata) LC50: 50.87 - 70.34mg/L (96h, Poecilia reticulata)		

Persistence and degradability

No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Xylene 1330-20-7	3.15
1,2,4 Trimethylbenzene 95-63-6	3.63
Ethylbenzene 100-41-4	3.6
Cumene 98-82-8	3.55
Toluene 108-88-3	3.93

Other adverse effects

No information available.

13. Disposal considerations			
Waste treatment methods			
Waste from residues/unused products	Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.		
Contaminated packaging	Do not reuse empty containers.		
California Hazardous Waste Status	This product contains one or more substances that are listed with the State of California as a hazardous waste.		

14. Transport information	
DOT	Not regulated in a container less than 119 gallons
TDG	

MEX

ICAO (air)

<u>IATA</u>

IMDG	
15. Regulatory informatio	n
International Inventories	
TSCA	Complies.
DSL/NDSL EINECS/ELINCS ENCS IECSC KECL PICCS AIIC	Complies. Complies. Complies. Complies. Complies. Complies. Complies.

NZIoC

Complies.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

- EINECS/ELINCS European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
- **ENCS** Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AIIC - Australian Inventory of Industrial Chemicals

NZIOC - New Zealand Inventory of Chemicals

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
Xylene - 1330-20-7	1.0
1,2,4 Trimethylbenzene - 95-63-6	1.0
Ethylbenzene - 100-41-4	0.1
Cumene - 98-82-8	0.1
Toluene - 108-88-3	1.0

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb	-	-	Х
Ethylbenzene 100-41-4	1000 lb	Х	Х	Х
Toluene 108-88-3	1000 lb	X	X	Х

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Xylene 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethylbenzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ
Cumene 98-82-8	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Toluene 108-88-3	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:.

Chemical name	California Proposition 65
Ethylbenzene - 100-41-4	Carcinogen
Cumene - 98-82-8	Carcinogen
Toluene - 108-88-3	Developmental
Benzene - 71-43-2	Carcinogen
	Developmental
	Male Reproductive

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Xylene 1330-20-7	Х	Х	Х
Trimethylbenzene, Isomers 25551-13-7	Х	Х	Х
1,2,4 Trimethylbenzene 95-63-6	Х	Х	Х
Ethylbenzene 100-41-4	Х	Х	Х
Cumene 98-82-8	Х	X	Х
Methyl Isopropyl Benzene 25155-15-1	Х	-	-
Toluene 108-88-3	Х	Х	Х
Benzene 71-43-2	Х	Х	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information				
NFPA HMIS Chronic Hazard Star Lege	Health hazards 3 Health hazards 2 * nd *= Chronic I	Flammability 2 Flammability 2 Health Hazard	Instability 0 Physical hazards 0	Special hazards - Personal protection G
Legend Section 8: EX TWA TWA	eviations and acronyms u (POSURE CONTROLS/PE A (time-weighted average) kimum limit value		stet STEL (Short Term Skin designation	n Exposure Limit)
Agency for Toxic Substa U.S. Environmental Pro European Food Safety EPA (Environmental Pro Acute Exposure Guideli U.S. Environmental Pro U.S. Environmental Pro Food Research Journal Hazardous Substance I International Uniform Cl National Institute of Tec	otection Agency) ne Level(s) (AEGL(s)) tection Agency Federal Ins tection Agency High Produ	y (ATSDR) Database ecticide, Fungicide, and Ro ction Volume Chemicals ase (IUCLID) ITE)	odenticide Act	

NIOSH (National Institute for Occupational Safety and Health) National Library of Medicine's ChemID Plus (NLM CIP) National Library of Medicine's PubMed database (NLM PUBMED) National Toxicology Program (NTP) New Zealand's Chemical Classification and Information Database (CCID) Organization for Economic Co-operation and Development Environment, Health, and Safety Publications Organization for Economic Co-operation and Development High Production Volume Chemicals Program Organization for Economic Co-operation and Development Screening Information Data Set World Health Organization

Revision Date	11-Feb-2021
Revision Note	Periodic Review.
<u>Disclaimer</u>	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.