

PRODUCT DESCRIPTION

BRICKFORM Overlay Liquid Colorants are specifically formulated for use with BRICKFORM overlay products. These colorants are UV-resistant and manufactured to strict standards to ensure color uniformity and consistency. BRICKFORM Overlay Liquid Colorants are non-hazardous, water-based formulations that allow for easy mixing with BRICKFORM overlay products. For a complete list of available colors, refer to the BRICKFORM Standard Color Selection Guide.

USE WITH THE FOLLOWING BRICKFORM OVERLAYS

- Cem-Coat Plus
- Micro-Topping
- SM Professional Grade
- SM Pro Plus
- SC-60 Stampable Overlay
- **Not for use with OL-60 Stampable Overlay**

PACKAGING

- 10 oz. bottle, 6 units per case.
- Available in 40 standard colors

STORAGE & SHELF LIFE

- Store in a dry, safe place with containers tightly Sealed. DO NOT allow product to freeze.
- Shelf life is approximately 36 months.

USE & APPLICATION

PRECAUTIONS:

Brickform strongly recommends jobsite samples or mockups with these products. Minimum ambient and surface temperature for application is 50°F (10°C) during application and for a minimum of 24 hours after application. Do not apply if rain is expected during application or within 24 hours after application. Variations in ambient and surface temperature, mixing techniques and finishing techniques will affect final appearance.

DIRECTIONS:

Overlay Liquid Colorants are formulated as a one-to one mixing ratio. Mix one bottle of Brickform Overlay Liquid Colorant with one unit of Brickform overlay. Empty the 10 ounce bottle of liquid color into your mixing vessel containing the specified amount of Brickform Polymer or water depending on the overlay directions. Then fill the color bottle half full with polymer (or water), replace the cap, and shake vigorously to loosen any settled pigment. Pour this material back into your mixing vessel and mix well prior to adding the dry powder.

RECOMMENDED TOOLS & CLEAN UP

CLEAN UP: Clean tools and equipment with water.

SAFETY & PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN. Before using or handling, read the Safety Data Sheet and Warranty. **DO NOT TAKE INTERNALLY.** Avoid contact with eyes and skin. When working with or near this product, all personnel must wear MSHA-NIOSH approved respirators (refer to OSHA standards in 29 CFR 1910.134). Prolonged, unprotected exposure may result in non-reversible Silicosis or Lung Cancer. Avoid inhalation and use local exhaust to keep exposures below OSHA PEL's for silica and nuisance dusts. Avoid contact with skin and eyes. Wear rubber gloves and aprons to protect skin and wear safety eye goggles. Wash splatters from skin immediately. Use good hygiene when handling this product and wash and bathe after each use. Close containers after each use. Be sure to wash clothing after each use.



WARRANTY

This product is not intended for public use and is intended for use by licensed contractors and installers, experienced and trained in the use of these products. It is warranted to be of uniform quality, within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the effects or results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.

For more information go to:

solomoncolors.com or brickform.com

