

Tips on BRICKFORM® Poly-Seal™ Application

This is abbreviated information taken from the BRICKFORM Poly-Seal Technical Information Sheet and MSDS. Read both references before attempting to use this product. BRICKFORM strongly recommends testing an area for results before total application. Poly-Seal is RESTRICTED in some states. Check with your local regulatory agency before using this product.

DO

PREPARATION

New concrete should be cured for at least 28 days.
Remove all deleterious materials.

APPLICATION

Always test a small area to verify appearance.
Apply only in very thin coats.
Allow 24 hours between coats.
Apply in temperatures between 55°-80°.

MAINTENANCE

Inspect annually for signs of worn sealer and reapply as necessary.

DO NOT

PREPARATION

Do not use on pre-sealed or dense surfaces.
Do not use where there is hydrostatic pressure.

APPLICATION

Do not apply more than 2 coats.
Do not apply on hot, windy days or in inclement weather.

MAINTENANCE

Do not reapply a sealer until all efflorescence and deleterious materials have been removed.

WARRANTY

This product is not intended for public use and is intended for use by licensed contractors and installers, experienced and trained in the use of these products. It is warranted to be of uniform quality, within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the affects or results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven to be defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.

SAFE HANDLING INSTRUCTIONS

DO NOT TAKE INTERNALLY. Use only with ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations of vapor in air. Use explosion-proof equipment. Never use a welding or cutting torch on or near drum (even empty) because residue can ignite explosively. Extreme temperatures may cause explosion. Avoid inhalation and use atmosphere supplying or air purifying respirators. Avoid contact with skin and eyes. Wear rubber gloves and aprons to protect skin and wear safety eye goggles. Use good hygiene when handling this product and wash and bathe after each use. Be sure to wash clothing after each use.