



SAFETY DATA SHEET

Issue Date 11-Feb-2021

Revision Date 11-Feb-2021

Version 1

MT-4001

Spray Mix Profession Grade Plus -White

1. IDENTIFICATION

Product identifier

Product Name Spray Mix Profession Grade Plus -White

Other means of identification

Product Code MT-4001

Recommended use of the chemical and restrictions on use

Recommended Use Restricted to professional users.

Uses advised against Consumer use

Details of the supplier of the safety data sheet

Supplier Address

Solomon Colors, Inc.
4050 Color Plant Road
Springfield, IL
62702

Manufacturer Address

Solomon Colors, Inc.
4050 Color Plant Road
Springfield, IL
62702

Company Phone Number 800-624-0261 (US & Canada); 217-522-3112 (Outside North America)

24 Hour Emergency Phone Number 800-373-7542 Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This product is classified as hazardous according to the criteria contained in the Hazard Communication Standard 29 CFR 1910.1200 (known as HCS 2012) and the Hazardous Products Regulations SOR/2015-17 (known as WHMIS 2015).

Skin corrosion/irritation	Category 1
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1A
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3 (Respiratory System)
Specific target organ toxicity (repeated exposure)	Category 1 (Lungs)

Label elements

Emergency Overview

Danger

Hazard statements

Causes severe skin burns and eye damage
May cause an allergic skin reaction
May cause cancer

May cause respiratory irritation
Causes damage to lungs through prolonged or repeated inhalation exposure.



Overexposure to dust can cause chronic lung injury. Acute silicosis may develop in a short timewith heavy exposure. Silicosis can be progressive and may cause death.

Appearance White Powder

Physical state Powder

Odor Odorless

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wear protective gloves/protective clothing/eye protection/face protection
Wash face, hands and any exposed skin thoroughly after handling
Contaminated work clothing must not be allowed out of the workplace
Do not breathe dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Immediately call a POISON CENTER or doctor
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower
Wash contaminated clothing before reuse
If skin irritation or rash occurs: Get medical advice/attention
IF INHALED: Remove person to fresh air and keep comfortable for breathing
Immediately call a POISON CENTER or doctor
IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable

Hazards not otherwise classified (HNOC)

Other Information

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature Mixture.

Chemical Name	CAS No.	Weight-%	Trade Secret
Quartz, Crystalline Silica	14808-60-7	65-70	*
Portland Cement	65997-15-1	20-25	*
Limestone	1317-65-3	4-5	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If symptoms persist, call a physician.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
Ingestion	Rinse mouth. Drink 1 or 2 glasses of water. Do not induce vomiting without medical advice. Call a physician immediately.

Most important symptoms and effects, both acute and delayed

Symptoms	General: Prolonged or repeated inhalation may damage lungs. Inhalation: May cause respiratory irritation, sneezing, coughing, burning sensation in the throat or constriction of the larynx, or difficulty breathing. Eye contact: Redness, irritation or pain. Skin: Prolonged contact with large amounts of this product may cause mechanical irritation. Dust may cause irritation in skin folds or by contact in combination with tight clothing. Ingestion: Abdominal pain. Chronic symptoms: Shortness of breath, wheezing, cough and sputum production. May cause cancer, silicosis, lung disease, autoimmune disease, tuberculosis, and nephrotoxicity.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

No information available.

Hazardous combustion products Thermal decomposition can lead to the release of irritating gases and vapors. Carbon oxides. Metal Oxides. Oxides of sulfur.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with skin, eyes or clothing. Use personal protection recommended in Section
-----------------------------	---

8. Ensure adequate ventilation, especially in confined areas. Avoid breathing dust/fume/gas/mist/vapors/spray.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers. For disposal see section 13.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible materials Cement is reactive or incompatible with oxidizing materials, acids, aluminum, and ammonium salt. Cement is highly alkaline and will react violently with acids that can produce toxic gases or vapors. Silica reacts violently with oxidizing agents. Silicates dissolve readily in hydrofluoric acid and produces corrosive gas.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Quartz, Crystalline Silica 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 µg/m ³ TWA: 50 µg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust
Portland Cement 65997-15-1	TWA: 1 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction TWA: 50 mppcf <1% Crystalline silica	IDLH: 5000 mg/m ³ TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Limestone 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust

Appropriate engineering controls

Engineering Controls Showers
 Eyewash stations
 Ventilation systems.

Individual protection measures, such as personal protective equipment

- Eye/face protection** Wear safety glasses with side shields (or goggles).
- Skin and body protection** Wear protective gloves and protective clothing.
- Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Powder	Odor	Odorless
Appearance	White Powder	Odor threshold	No information available
Color	White		
Property	Values	Remarks • Method	
pH	Expected to be basic		
Melting point/freezing point	> 1000 °C / 1832 °F		
Boiling point / boiling range	No information available		
Flash point	Not Flammable or Combustible		
Evaporation rate	No applicable		
Flammability (solid, gas)	No information available		

Flammability Limit in Air	
Upper flammability limit:	No information available
Lower flammability limit:	No information available
Vapor pressure	No information available
Vapor density	No information available
Specific Gravity	No information available
Water solubility	Slightly soluble in water
Solubility in other solvents	No information available
Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	Not applicable
Dynamic viscosity	Not applicable
Explosive properties	Not applicable
Oxidizing properties	Not applicable

Other Information

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	No information available
Density	No information available
Bulk density	No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Freezing conditions will damage product.

Incompatible materials

Cement is reactive or incompatible with oxidizing materials, acids, aluminum, and ammonium salt. Cement is highly alkaline and will react violently with acids that can produce toxic gases or vapors. Silica reacts violently with oxidizing agents. Silicates dissolve readily in hydrofluoric acid and produces corrosive gas.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating and toxic gases and vapors. Carbon oxides. Sulfur oxides. Metal Oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	No data available
Inhalation	Harmful by inhalation.
Eye contact	Avoid contact with eyes. Risk of serious damage to eyes.
Skin Contact	Irritating to skin. May cause burns in the presence of moisture. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.
Ingestion	May be harmful if swallowed. Can burn mouth, throat, and stomach.

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	May cause serious burns in the presence of moisture.
Serious eye damage/eye irritation	May cause serious burns in the presence of moisture.
Sensitization	Repeated or prolonged contact may cause allergic reactions in very susceptible persons.
Germ cell mutagenicity	Not classified. (Based on mixture components).
Carcinogenicity	May cause cancer by inhalation. The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Quartz, Crystalline Silica 14808-60-7	A2	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - *Suspected Human Carcinogen*

IARC (International Agency for Research on Cancer)

Group 1 - *Carcinogenic to Humans*

The International Agency for Research on Cancer ("IARC") concluded that there was "sufficient evidence in humans for the carcinogenicity of crystalline silica in the forms of quartz or cristobalite. Crystalline silica in the form of quartz or cristobalite dust causes cancer of the lung", and that there is "sufficient evidence in experimental animals for the carcinogenicity of quartz dust" The overall IARC evaluation was that "crystalline silica quartz or cristobalite dust is carcinogenic to humans (Group 1)."

NTP (National Toxicology Program)

Known - *Known Carcinogen*

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - *Present*

Reproductive toxicity	Not classified. (Based on mixture components).
STOT - single exposure	Target Organs. Respiratory system.
STOT - repeated exposure	Causes damage to lungs through prolonged or repeated exposure if inhaled. Overexposure to dust can cause chronic lung injury such as chronic silicosis, accelerated silicosis, and acute silicosis. Several studies have also reported excess cases of kidney diseases in silica exposed workers.
Aspiration hazard	Not classified. (Based on mixture components).

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	5071 mg/kg
ATEmix (dermal)	> 5000 mg/kg
ATEmix (inhalation-gas)	> 20,000 ppm
ATEmix (inhalation-dust/mist)	> 5 mg/l
ATEmix (inhalation-vapor)	> 20 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

This product has not been fully evaluated on the product level.

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

Slightly soluble in water.

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated packaging

Do not reuse container. Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. TRANSPORT INFORMATION

DOT

Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Does not comply
IECSC	Complies
KECL	Complies
PICCS	Does not comply
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

See section 2 for more information

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Quartz, Crystalline Silica - 14808-60-7	Carcinogen
Lead - 7439-92-1	Carcinogen Developmental Female Reproductive Male Reproductive
Nickel Compounds - RR-00800-4	Carcinogen
Hexavalent chromium - 18540-29-9	Carcinogen Developmental Female Reproductive Male Reproductive
Ethylbenzene - 100-41-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Quartz, Crystalline Silica 14808-60-7	X	X	X
Portland Cement	X	X	X

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

<u>NFPA</u>	Health hazards 3	Flammability 0	Reactivity 0	Physical and Chemical Properties -
<u>HMIS</u>	Health hazards 3	Flammability 0	Physical hazards 0	Personal protection X

Prepared By Solomon Colors - Lab Technical Services
Issue Date 11-Feb-2021
Revision Date 11-Feb-2021
Revision Note
 Initial SDS

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet