

Tips on BRICKFORM® Stampable Overlay™ Application

This is abbreviated information taken from the BRICKFORM Stampable Overlay Technical Information Sheet, BRICKFORM SO Primer Technical Information Sheet and corresponding MSDS. Read all references before attempting to use these products. BRICKFORM strongly recommends testing an area for results before total application.

DO

PREPARATION

The concrete surface **MUST BE** scarified or sandblasted.
Power wash and allow to partially dry.
Primer the surface with BRICKFORM SO Primer prior to application.

APPLICATION

Apply in temperatures between 50°-80°.
Mix in batches that can be used in 30 minutes.
Do a test area for desired results.

COLORING AND TEXTURING

Contact Rafco Products for more information.
Use overlay texture mats for texturing.

CURING

Allow STAMPCOAT to cure for 36 hours.

SEALING

Use a high-quality sealer such as BRICKFORM Gem-Seal, high-gloss sealer, Master-Seal, slip-resistant sealer, or Satin-Seal, water-based, semi-gloss sealer.

MAINTENANCE

Inspect annually for signs of worn sealer and reapply as necessary.

DO NOT

PREPARATION

Do not leave any contaminants such as moss dirt, or oil on the application area.
Do not leave any standing water on the surface.
Do not apply primer without reading the Brickform SO Primer Technical Information Sheet.

APPLICATION

Do not use in extreme temperatures or windy conditions.
Do not over-trowel.
Do not apply over surfaces that are not primed.

COLORING AND TEXTURING

Do not use regular texture mats with this product.

CURING

Do not use plastic sheeting, membrane paper, or water misting.

SEALING

Do not apply a sealer until Stampable Overlay has been allowed to cure for a period or 48 hours after the final rinse.

MAINTENANCE

Do not reapply a sealer until all efflorescence and deleterious materials have been removed.

WARRANTY

This product is not intended for public use and is intended for use by licensed contractors and installers, experienced and trained in the use of these products. It is warranted to be of uniform quality, within manufacturing tolerances. **Continue on pg. 2**

The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the affects or results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven to be defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.

SAFE HANDLING INSTRUCTIONS

KEEP OUT OF REACH OF CHILDREN. Before using or handling, read the Material Safety Data Sheet and Warranty. DO NOT TAKE INTERNALLY. All concrete finishers and all onsite personnel must wear an OSHA-NIOSH approved dust respirator while applying or working around Brickform STAMPCOAT. Avoid contact with skin and eyes. Wear rubber gloves to protect skin and safety eye goggles. Close containers after each use.

Tips on BRICKFORM SO Primer™ Application

This is abbreviated information taken from the BRICKFORM SO Primer Technical Information Sheet and MSDS. Read both references before attempting to use this product. BRICKFORM strongly recommends testing an area for results before total application.

DO

PREPARATION

The application area must be scarified or sandblasted.
Power wash and allow the surface to partially dry.

APPLICATION

Apply full strength.
Reapply if the primer dries prior to application of Stampable Overlay.

STORAGE

Keep from freezing.

DO NOT

PREPARATION

Do not use on surfaces that are not totally clean.
Don't leave any standing water on the surface.

APPLICATION

Do not let the primer dry before applying Stampable Overlay.

STORAGE

Do not store in temperatures higher than 90°.

WARRANTY

This product is not intended for public use and is intended for use by licensed contractors and installers, experienced and trained in the use of these products. It is warranted to be of uniform quality, within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the affects or results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven to be defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.

SAFE HANDLING INSTRUCTIONS

DO NOT TAKE INTERNALLY. Do not breathe vapors or mist. Use only with adequate ventilation and use a respirator when levels are above applicable limits. If using spray equipment, a painter's mask should be worn. Avoid contact with skin and eyes. Close container after each use.