



# SAFETY DATA SHEET

Issue Date 30-Jan-2018

Revision Date 10-Feb-2021

Version 4

SC-60

Stampable Overlay White

## 1. IDENTIFICATION

### Product identifier

**Product Name** Stampable Overlay White

### Other means of identification

**Product Code** SC-60

**Synonyms** Stampable Overlay White Mix

### Recommended use of the chemical and restrictions on use

**Recommended Use** Restricted to professional users.

**Uses advised against** Consumer use

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Solomon Colors, Inc.  
4050 Color Plant Road  
Springfield, IL  
62702

**Company Phone Number** 800-624-0261 (US & Canada);

**24 Hour Emergency Phone Number** 800-373-7542

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This product is classified as hazardous according to the criteria contained in the Hazard Communication Standard 29 CFR 1910.1200 (known as HCS 2012) and the Hazardous Products Regulations SOR/2015-17 (known as WHMIS 2015).

Skin corrosion/irritation	Category 1
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1A
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3 (Respiratory System)
Specific target organ toxicity (repeated exposure)	Category 1 (Lungs)

### Label elements

#### **Emergency Overview**

#### **Danger**

#### **Hazard statements**

Causes severe skin burns and eye damage

May cause an allergic skin reaction

May cause cancer

May cause respiratory irritation

Causes damage to lungs through prolonged or repeated inhalation exposure.



Overexposure to dust can cause chronic lung injury. Acute silicosis may develop in a short timewith heavy exposure. Silicosis can be progressive and may cause death.

**Appearance** White Powder

**Physical state** Powder

**Odor** Odorless

#### Precautionary Statements - Prevention

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Wear protective gloves/protective clothing/eye protection/face protection  
Wash face, hands and any exposed skin thoroughly after handling  
Contaminated work clothing must not be allowed out of the workplace  
Do not breathe dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area

#### Precautionary Statements - Response

Immediately call a POISON CENTER or doctor  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
Immediately call a POISON CENTER or doctor  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower  
Wash contaminated clothing before reuse  
If skin irritation or rash occurs: Get medical advice/attention  
IF INHALED: Remove person to fresh air and keep comfortable for breathing  
Immediately call a POISON CENTER or doctor  
IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

#### Precautionary Statements - Storage

Store locked up  
Store in a well-ventilated place. Keep container tightly closed

#### Precautionary Statements - Disposal

Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable

#### Hazards not otherwise classified (HNOC)

#### Other Information

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Synonyms** Stampable Overlay White Mix.

Chemical Name	CAS No.	Weight-%	Trade Secret
Quartz, Crystalline Silica	14808-60-7	60-70	*
Portland Cement	65997-15-1	20-30	*
Proprietary Mineral Filler	Proprietary	< 4	*
Silica (chemically prepared)	7631-86-9	< 5	*
Calcium hydroxide	1305-62-0	1-1.2	*
Formic acid, calcium salt	544-17-2	< 0.5	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. FIRST AID MEASURES

### Description of first aid measures

<b>General advice</b>	In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin Contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
<b>Ingestion</b>	Rinse mouth. Drink 1 or 2 glasses of water. Do not induce vomiting without medical advice. Call a physician immediately.

### Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	General: Prolonged or repeated inhalation may damage lungs. Inhalation: May cause respiratory irritation, sneezing, coughing, burning sensation in the throat or constriction of the larynx, or difficulty breathing. Eye contact: Redness, irritation or pain. Skin: Prolonged contact with large amounts of this product may cause mechanical irritation. Dust may cause irritation in skin folds or by contact in combination with tight clothing. Ingestion: Abdominal pain. Chronic symptoms: Shortness of breath, wheezing, cough and sputum production. May cause cancer, silicosis, lung disease, autoimmune disease, tuberculosis, and nephrotoxicity.
-----------------	---

### Indication of any immediate medical attention and special treatment needed

<b>Note to physicians</b>	Treat symptomatically.
---------------------------	------------------------

## 5. FIRE-FIGHTING MEASURES

### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media** Caution: Use of water spray when fighting fire may be inefficient.

### Specific hazards arising from the chemical

No information available.

**Hazardous combustion products** Thermal decomposition can lead to the release of irritating gases and vapors. Carbon oxides. Metal Oxides. Oxides of sulfur.

### Explosion data

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with skin, eyes or clothing. Use personal protection recommended in Section 8. Ensure adequate ventilation, especially in confined areas. Avoid breathing dust/fume/gas/mist/vapors/spray.

**Environmental precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. See Section 12 for additional ecological information.

**Methods and material for containment and cleaning up**

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labeled containers. For disposal see section 13.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on safe handling** Handle in accordance with good industrial hygiene and safety practice. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place.

**Incompatible materials** Cement is reactive or incompatible with oxidizing materials, acids, aluminum, and ammonium salt. Cement is highly alkaline and will react violently with acids that can produce toxic gases or vapors. Silica reacts violently with oxidizing agents. Silicates dissolve readily in hydrofluoric acid and produces corrosive gas.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Quartz, Crystalline Silica 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable particulate matter	TWA: 50 µg/m <sup>3</sup> TWA: 50 µg/m <sup>3</sup> excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m <sup>3</sup> respirable dust : (250)/(%SiO <sub>2</sub> + 5) mppcf TWA respirable fraction : (10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA respirable fraction	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust
Portland Cement 65997-15-1	TWA: 1 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction TWA: 50 mppcf <1% Crystalline silica	IDLH: 5000 mg/m <sup>3</sup> TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Proprietary Mineral Filler	-	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Silica (chemically prepared) 7631-86-9	-	TWA: 50 µg/m <sup>3</sup> excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 6 mg/m <sup>3</sup> <1% Crystalline silica TWA: 20 mppcf : (80)/(% SiO <sub>2</sub> ) mg/m <sup>3</sup> TWA	IDLH: 3000 mg/m <sup>3</sup> TWA: 6 mg/m <sup>3</sup>
Calcium hydroxide 1305-62-0	TWA: 5 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 5 mg/m <sup>3</sup> not in effect as a result of reconsideration	TWA: 5 mg/m <sup>3</sup>

#### **Appropriate engineering controls**

##### **Engineering Controls**

Showers  
Eyewash stations  
Ventilation systems.

#### **Individual protection measures, such as personal protective equipment**

##### **Eye/face protection**

Wear safety glasses with side shields (or goggles).

##### **Skin and body protection**

Wear protective gloves and protective clothing.

##### **Respiratory protection**

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

##### **General Hygiene Considerations**

Handle in accordance with good industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	Powder	<b>Odor</b>	Odorless
<b>Appearance</b>	White Powder	<b>Odor threshold</b>	No information available
<b>Color</b>	Off-White		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
<b>pH</b>	No information available	
<b>Melting point/freezing point</b>	> 1000 °C / 1832 °F	
<b>Boiling point / boiling range</b>	No information available	
<b>Flash point</b>	No information available	
<b>Evaporation rate</b>	Not Applicable	
<b>Flammability (solid, gas)</b>	No information available	
<b>Flammability Limit in Air</b>		
<b>Upper flammability limit:</b>	No information available	
<b>Lower flammability limit:</b>	No information available	
<b>Vapor pressure</b>	No information available	
<b>Vapor density</b>	No information available	
<b>Specific Gravity</b>	No information available	
<b>Water solubility</b>	No information available	
<b>Solubility in other solvents</b>	No information available	
<b>Partition coefficient</b>	No information available	
<b>Autoignition temperature</b>	No information available	
<b>Decomposition temperature</b>	No information available	
<b>Kinematic viscosity</b>	No information available	
<b>Dynamic viscosity</b>	No information available	
<b>Explosive properties</b>	No information available	
<b>Oxidizing properties</b>	No information available	

**Other Information**

<b>Softening point</b>	No information available
<b>Molecular weight</b>	No information available
<b>VOC Content (%)</b>	Not applicable
<b>Density</b>	No information available
<b>Bulk density</b>	No information available

**10. STABILITY AND REACTIVITY**

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Freezing conditions will damage product.

**Incompatible materials**

Cement is reactive or incompatible with oxidizing materials, acids, aluminum, and ammonium salt. Cement is highly alkaline and will react violently with acids that can produce toxic gases or vapors. Silica reacts violently with oxidizing agents. Silicates dissolve readily in hydrofluoric acid and produces corrosive gas.

**Hazardous Decomposition Products**

Thermal decomposition can lead to release of irritating and toxic gases and vapors. Carbon oxides. Sulfur oxides. Metal Oxides.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

<b>Product Information</b>	No data available
<b>Inhalation</b>	Harmful by inhalation.
<b>Eye contact</b>	Avoid contact with eyes. Risk of serious damage to eyes.
<b>Skin Contact</b>	Irritating to skin. May cause burns in the presence of moisture. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.
<b>Ingestion</b>	May be harmful if swallowed. Can burn mouth, throat, and stomach.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Silica (chemically prepared) 7631-86-9	= 7900 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 2.2 mg/L ( Rat ) 1 h
Calcium hydroxide 1305-62-0	= 7340 mg/kg ( Rat )	-	-
Formic acid, calcium salt 544-17-2	= 2650 mg/kg ( Rat )	-	-

### Information on toxicological effects

**Symptoms** No information available.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Skin corrosion/irritation</b>	May cause serious burns in the presence of moisture.
<b>Serious eye damage/eye irritation</b>	May cause serious burns in the presence of moisture.
<b>Sensitization</b>	Repeated or prolonged contact may cause allergic reactions in very susceptible persons.
<b>Germ cell mutagenicity</b>	Not classified. (Based on mixture components).
<b>Carcinogenicity</b>	May cause cancer by inhalation. The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Quartz, Crystalline Silica 14808-60-7	A2	Group 1	Known	X
Silica (chemically prepared) 7631-86-9	-	Group 3	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

*The International Agency for Research on Cancer ("IARC") concluded that there was "sufficient evidence in humans for the carcinogenicity of crystalline silica in the forms of quartz or cristobalite. Crystalline silica in the form of quartz or cristobalite dust causes cancer of the lung", and that there is "sufficient evidence in experimental animals for the carcinogenicity of quartz dust" The overall IARC evaluation was that "crystalline silica quartz or cristobalite dust is carcinogenic to humans (Group 1)."*

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

<b>Reproductive toxicity</b>	Not classified. (Based on mixture components).
<b>STOT - single exposure</b>	Target Organs. Respiratory system.
<b>STOT - repeated exposure</b>	Causes damage to lungs through prolonged or repeated exposure if inhaled. Overexposure to dust can cause chronic lung injury such as chronic silicosis, accelerated silicosis, and acute silicosis. Several studies have also reported excess cases of kidney diseases in silica exposed workers.
<b>Aspiration hazard</b>	Not classified. (Based on mixture components).

### Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

**ATEmix (oral)** > 5000 mg/kg

**ATEmix (dermal)** > 5000 mg/kg

ATEmix (inhalation-gas) > 20,000 ppm  
 ATEmix (inhalation-dust/mist) > 5 mg/l  
 ATEmix (inhalation-vapor) > 20 mg/l

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

This product has not been fully evaluated on the product level.

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility**

Slightly soluble in water.

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal of wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated packaging**

Do not reuse container. Disposal should be in accordance with applicable regional, national and local laws and regulations.

Chemical Name	California Hazardous Waste Status
Calcium hydroxide 1305-62-0	Corrosive

**14. TRANSPORT INFORMATION**

**DOT**

Not regulated



## 15. REGULATORY INFORMATION

### International Inventories

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Does not comply
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Does not comply
<b>AICS</b>	Complies

### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

### US Federal Regulations

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

#### SARA 311/312 Hazard Categories

See section 2 for more information

#### CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

### US State Regulations

#### California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Quartz, Crystalline Silica - 14808-60-7	Carcinogen
Silica (chemically prepared) - 7631-86-9	Carcinogen
Lead - 7439-92-1	Carcinogen Developmental Female Reproductive Male Reproductive
Hexavalent chromium - 18540-29-9	Carcinogen Developmental Female Reproductive Male Reproductive
Formaldehyde - 50-00-0	Carcinogen
Ethylbenzene - 100-41-4	Carcinogen
Acetaldehyde - 75-07-0	Carcinogen
Nickel Compounds - RR-00800-4	Carcinogen

#### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania

Quartz, Crystalline Silica 14808-60-7	X	X	X
Portland Cement 65997-15-1	X	X	X
Proprietary Mineral Filler	X	X	X
Silica (chemically prepared) 7631-86-9	-	X	X
Calcium hydroxide 1305-62-0	X	X	X

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

<b>NFPA</b>	Health hazards 3	Flammability 0	Reactivity 0	Physical and Chemical Properties -
<b>HMIS</b>	Health hazards 3	Flammability 0	Physical hazards 0	Personal protection X

<b>Prepared By</b>	Solomon Colors - Lab Technical Services
<b>Issue Date</b>	30-Jan-2018
<b>Revision Date</b>	10-Feb-2021
<b>Revision Note</b>	Periodic Review

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**