



BRICKFORM® Turtle Set™

Set Time Retardant

PRODUCT DESCRIPTION

Brickform Turtle Set is a retardant designed for use with Brickform SM Professional Grade, MicroTopping, OL-60 and SC-60 Stampable overlay products. Easily measured liquid form increases pot life and set times for greater control with resurfacing products in warm weather.

LIMITATIONS

Brickform Turtle Set is a set retarding material. Use only after testing to determine appropriate set times for jobsite conditions. Use with caution when temperatures are below 80 degrees (F) as curing is slowed dramatically in cooler temperatures.

Turtle set can affect coloration of overlay materials. Once a project is started with the product, continue using it throughout the project to ensure color uniformity.

Buckets mixed with Turtle Set will have subtle color differences to those mixed without the product.

Base Coats should be allowed to set longer prior to applying design tape or stencils in order to eliminate the possibility of the material lifting when the pattern is removed due to insufficient curing.

FIRST AID & EMERGENCY INFORMATION:

Emergency Telephone 800-373-7542.

Eyes: DO NOT RUB. Flush eyes with plenty of water for 15 minutes while holding eyelids open. If irritation persists, get medical attention.

Inhalation: Remove victim to fresh air. If irritation persists, get medical attention.

Ingestion: If symptoms develop, get medical attention.

Skin: Wash with soap and water. Remove contaminated clothing and shoes. Do not re-use until cleaned. If persistent irritation occurs, get medical attention.

In case of fire: Extinguishing media: use water fog, foam, dry chemical or CO₂. Wear self-contained breathing apparatus with full face-piece operated in pressure demand or other positive-pressure mode and full-body protective clothing when fighting fire.

In case of spills: Ventilate confined spaces. Open all windows and doors. Flush with water to a tank or an open well ventilated area. Control runoff and isolate discharge material for proper waste disposal method. Keep product out of sewers, watercourses, or extensive land areas. Absorb with sand or other suitable absorbent; use non-leaking containers, seal tightly and label properly. Dispose of in accordance with applicable local, county, state and Federal regulations.

PACKAGING

Brickform Turtle set is packaged in one gallon jugs, four to a case.

STORAGE

Store in a dry safe place. Protect from freezing. Shelf Life is 12 months if jugs are unopened and tightly sealed.

MIXING INSTRUCTIONS

Blend Brickform overlay product material per product TIS. Once the overlay product has been allowed to slake and product is ready for re-blending prior to application, add between 4-8 ounces of Turtle Set per bag of material and mix thoroughly. 4-8 ounces is designed to treat one full bag of overlay material. Additional Turtle Set can be added to bucket but do not exceed 16 ounces per bag.

WARRANTY

This product is not intended for public use and is intended for use by licensed contractors and installers, experienced and trained in the use of these products. It is warranted to be of uniform quality, within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the effects or results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.

BRICKFORM, A Division of Solomon Colors, Inc.
4050 Color Plant Rd
Springfield Il 62702

Toll Free 1-800-483-9628

www.brickform.com