CARLISLE COATINGS & WATERPROOFING

Safety Data Sheet acc. to OSHA HCS & WHMIS

Printing date 09/14/2018

Reviewed on 09/14/2018

1 Identification

- · Product identifier: 331311
- · Trade name: CCW 570 Resin
- · Item number(s): 331311
- MSDS Number: 502
- · Application of the substance / the mixture ROOF COATING
- **Manufacturer/Supplier:** Carlisle Coatings & Waterproofing 900 Hensley Lane Wylie, TX 75098
- Information department: 800-527-7092
 www.carlisleccw.com
 Emergency telephone number: ChemTrec (800) 424-9300 / 1-(703)-741-5970
 Canada only: CANUTEC (Call collect) (613) 996-6666

2 Hazard(s) identification

2 Hazard(S) identification	
• Classification of the substance or mixture:	
GHS02 Flame	
Flammable Liquids - Category 2	H225 Highly flammable liquid and vapour.
Skin Irritation - Category 2	H315 Causes skin irritation.
Skin Sensitizer - Category 1	H317 May cause an allergic skin reaction.
Specific Target Organ Toxicity - Single Exposure - I Category 3	H335 May cause respiratory irritation.
Eye Irritation - Category 2B I • Label elements • GHS label elements The product is classified and labeled according to the • Signal word: Danger	H320 Causes eye irritation. Globally Harmonized System (GHS).
 Hazard-determining components of labeling: methyl methacrylate 2-ethylhexyl acrylate Hazard statements: Highly flammable liquid and vapour. Causes skin and eye irritation. May cause an allergic skin reaction. May cause respiratory irritation. Precautionary statements: Keep away from heat, hot surfaces, sparks, open flam Keep cool. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting] equ Take actions to prevent static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray. 	

Printing date 09/14/2018

Reviewed on 09/14/2018

Trade name: CCW 570 Resin

(Contd. of page 1) Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water for shower]. IF INHALED: Call a doctor if you feel unwell. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use for extinction: CO2, sand, extinguishing powder. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · NFPA ratings (scale 0 - 4): Health = 1



Health = 1 Fire = 3 Reactivity = 0

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• **Description:** Mixture of the substances listed below with nonhazardous additions.

Dangerous	components:	
80-62-6	methyl methacrylate	10-30% w/w
	2-ethylhexyl acrylate	10-30% w/w
13463-67-7	Titanium Dioxide	≥10-≤13% w/w
7328-22-5	Diethylene glycol butyl ether methacrylate	≥10-≤13% w/w

· Additional information:

Exact concentrations and/or compositions are being withheld as trade secrets.

4 First-aid measures

• After inhalation:

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

• After skin contact:

If on skin (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a posion center or doctor if you feel unwell. If skin irritation or a rash occurs: Get medical advice/attention

· After eye contact:

Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If eye irritation persists get medical advice/attention.

- After swallowing: If symptoms persist consult doctor.
- Most important symptoms and effects, both acute and delayed: No further relevant information available.

(Contd. on page 3)

(Contd. of page 2)

Safety Data Sheet acc. to OSHA HCS & WHMIS

Printing date 09/14/2018

Reviewed on 09/14/2018

Trade name: CCW 570 Resin

• Indication of any immediate medical attention and special treatment needed: No further relevant information available.

5 Fire-fighting measures

- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture: No further relevant information available.
- Protective equipment: No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures:** Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Reference to other sections:
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

- · Handling
- **Precautions for safe handling:** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Storage
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• Specific end use(s): No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

CA –

Printing date 09/14/2018

Reviewed on 09/14/2018

Trade name: CCW 570 Resin

		(Contd. of page 3)		
-		quire monitoring at the workplace:		
	yl methacrylate			
EL (Canada)	Short-term value: 100 ppr Long-term value: 50 ppm			
	S(D)			
EV (Canada)	m			
PEL (USA)	Long-term value: 410 mg	/m³, 100 ppm		
REL (USA)				
TLV (USA)	TLV (USA) Short-term value: 410 mg/m ³ , 100 ppm Long-term value: 205 mg/m ³ , 50 ppm DSEN			
Avoid contact Avoid contact Breathing eq In case of bri exposure use Use suitable r Protection of Synthetic glov Pro Eye protection	with the eyes and skin. uipment: ef exposure or low polluti respiratory protective device f hands: res tective gloves	ion use respiratory filter device. In case of intensive or longer ice that is independent of circulating air. ce in case of insufficient ventilation.		
9 Physical a	nd chemical properti	es		
· Form:		Liquid		
Color:		According to product specification		
· Odor: · Odor thresho	Jd.	Characteristic Not determined.		
· pH-value:	Ju.	Not determined.		
Change in co Melting poi Boiling poi	ondition nt/Melting range: nt/Boiling range:	Undetermined. 101 °C		
· Flash point:		10 °C		

(Contd. on page 5)

Printing date 09/14/2018

Reviewed on 09/14/2018

Trade name: CCW 570 Resin

	(Contd. of page 4
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	245 °C
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
[.] Danger of explosion:	Product is not explosive. However, formation of explosive air vapor mixtures are possible.
· Explosion limits	
Lower:	0.8 Vol %
Upper:	12.5 Vol %
· Vapor pressure at 20 °C:	47 hPa
Density at 20 °C:	1.23 g/cm ³
· Relative density:	Not determined.
Vapor density:	Not determined.
· Evaporation rate:	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wa	ater): Not determined.
· Viscosity:	
Dynamic at 20 °C:	10,338 mPas
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	1.6 %
VOC content:	1.60 %
	19.7 g/l / 0.16 lb/gl
Other information	No further relevant information available.

10 Stability and reactivity

• **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

- Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects:
- · Acute toxicity
- Specific symptoms in biological assay: No further relevant information available.
- Primary irritant effect
- on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- Sensitization: Sensitization possible through skin contact.

(Contd. on page 6)

CA

(Contd. of page 5)

Safety Data Sheet acc. to OSHA HCS & WHMIS

Printing date 09/14/2018

Reviewed on 09/14/2018

Trade name: CCW 570 Resin

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (Inter	national Agency for Research on Cancer)	
80-62-6	methyl methacrylate	3
	2-ethylhexyl acrylate	3
13463-67-7	Titanium Dioxide	2B
128-37-0	Butylated hydroxytoluene	3
111-76-2	2-butoxyethanol	3
•	nal Toxicology Program)	
None of the ingredients is listed.		

12 Ecological information

- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability: No further relevant information available.
- · Behavior in environmental systems
- · Bioaccumulative potential: No further relevant information available.
- Mobility in soil: No further relevant information available.
- Additional ecological information
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

- Danger to drinking water if even small quantities leak into the ground.
- Other adverse effects: No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings

· Recommendation:

Place in a sealed container and label as waste. Place in a safe area, and comply with all federal, state, provincial and local regulations for disposal.

14 Transport information

- · UN-Number
- · DOT, TDG, IMDG, IATA

UN1993

(Contd. on page 7)

Printing date 09/14/2018

Reviewed on 09/14/2018

Trade name: CCW 570 Resin	Trade	name:	CCW	570	Resin
---------------------------	-------	-------	-----	-----	-------

	(Contd. of page 6
· UN proper shipping name · DOT	Flammable liquids, n.o.s. (Methyl methacrylate
TDG	monomer, stabilized) 1993 Flammable liquids, n.o.s. (Methyl methacrylate
· IMDG, IATA	monomer, stabilized) FLAMMABLE LIQUID, N.O.S. (METHYL
	METHACRYLATE MONOMER, STABILIZED)
 Transport hazard class(es) 	
DOT	
· Class	3 Flammable liquids
	3
· TDG, IMDG, IATA	
· Class	3 Flammable liquids
· Label	3
 Packing group DOT, TDG, IMDG, IATA 	II
· Environmental hazards:	Not applicable.
Special precautions for user:	Warning: Flammable liquids
· Danger code (Kemler): · EMS Number:	- F-E,S-E
· Stowage Category	A
· Transport in bulk according to Annex	ll of
MARPOL73/78 and the IBC Code:	Not applicable.
· Transport/Additional information:	
·DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L
	On cargo aircraft only: 220 L
 TDG Excepted quantities (EQ) 	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
·IMDG	
· Limited quantities (LQ)	5L Cada: F1
 Excepted quantities (EQ) 	Code: E1 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
	(Contd. on page 8

Printing date 09/14/2018

Reviewed on 09/14/2018

Trade name: CCW 570 Resin

(Contd. of page 7)

```
· UN "Model Regulation":
```

UN 1993 FLAMMABLE LIQUIDS, N.O.S. (METHYL METHACRYLATE MONOMER, STABILIZED), 3, II

15 Regulatory information

 $^{\cdot}$ Safety, health and environmental regulations/legislation specific for the substance or mixture $^{\cdot}$ Sara

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

80-62-6 methyl methacrylate

111-76-2 2-butoxyethanol

· TSCA (Toxic Substances Control Act):

All ingredients are listed or exempted

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Canadian substance listings

· Canadian Domestic Substances List (DSL/NDSL):

All ingredients are listed.

· Canadian Ingredient Disclosure list (limit 0.1%):

None of the ingredients is listed.

· Canadian Ingredient Disclosure list (limit 1%):

80-62-6 methyl methacrylate

103-11-7 2-ethylhexyl acrylate

109-16-0 Triethylene glycol dimethacrylate

· GHS label elements

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

• Hazard-determining components of labeling: methyl methacrylate

(Contd. on page 9)

CA

Printing date 09/14/2018

Reviewed on 09/14/2018

Trade name: CCW 570 Resin

(Contd. of page 8)
2-ethylhexyl acrylate
· Hazard statements
Highly flammable liquid and vapour.
Causes skin and eye irritation.
May cause an allergic skin reaction.
May cause respiratory irritation.
Precautionary statements
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep cool.
Ground and bond container and receiving equipment.
Use explosion-proof [electrical/ventilating/lighting] equipment.
Take actions to prevent static discharges.
Avoid breathing dust/fume/gas/mist/vapours/spray.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing should not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF INHALED: Call a doctor if you feel unwell.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
In case of fire: Use for extinction: CO2, sand, extinguishing powder.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

16 Other information

This SDS format meets ANSI Z400.1-1998 and OSHA 1910.1200 requirements. We provide the information contained herein in good faith but make no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Product use and conditions of use are beyond our control. Warranty of materials is limited to test results of product performance as detailed in certificates of compliance. Interpretation of test results is the responsibility of end-user. No other warranties, expressed or implied, are made.

- · Department issuing SDS: Product safety department
- · Contact: Stephen Nowicki

 Date of preparation / last revision 09/14/2018 / Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) VOC: Volatile Organic Compounds (USA, EU)