
Printing date 09/14/2018

Reviewed on 09/14/2018

1 Identification

- · Product identifier: 331313
- Trade name: CCW 570 Primer
- · Item number(s): 331313
- · MSDS Number: 503
- · Application of the substance / the mixture PRIMER
- · Manufacturer/Supplier: Carlisle Coatings & Waterproofing 900 Hensley Lane Wylie, TX 75098
- · Information department: 800-527-7092 www.carlisleccw.com · Emergency telephone number: ChemTrec (800) 424-9300 / 1-(703)-741-5970 Canada only: CANUTEC (Call collect) (613) 996-6666


2 Hazard(s) identification



Printing date 09/14/2018

Reviewed on 09/14/2018

Trade name: CCW 570 Primer



Fire = 3Reactivity = 0

3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description 80-62-6 methyl methacrylate
- · Identification number(s)
- · EC number: 201-297-1
- · Index number: 607-035-00-6
- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
80-62-6	methyl methacrylate	60-100% w/w	
2082-81-7	tetramethylene dimethacrylate	10% w/w	
3077-12-1	2,2'-[(4-methylphenyl)imino]bisethanol	1-5% w/w	
103-11-7	2-ethylhexyl acrylate	1-5% w/w	
Additional information:			

· Additional information:

Exact concentrations and/or compositions are being withheld as trade secrets.

4 First-aid measures

· After inhalation:

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

(Contd. on page 3)

CA

(Contd. of page 2)

Safety Data Sheet acc. to OSHA HCS & WHMIS

Printing date 09/14/2018

Reviewed on 09/14/2018

Trade name: CCW 570 Primer

• After skin contact:

Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation or a rash occurs: Get medical advice/attention.

- After eye contact: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If eye irritation persists get medical advice/attention.
- After swallowing: Do not induce vomiting, Immediately call a poison center/ doctor.
- **Most important symptoms and effects, both acute and delayed:** No further relevant information available.
- Indication of any immediate medical attention and special treatment needed: No further relevant information available.

5 Fire-fighting measures

· Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture: No further relevant information available.
- · Protective equipment: No special measures required.

6 Accidental release measures

 Personal precautions, protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away.
 Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
- · Reference to other sections:
- See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling
- Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

- Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- · Storage
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)

CA

(Contd. of page 3)

Safety Data Sheet acc. to OSHA HCS & WHMIS

Printing date 09/14/2018

Reviewed on 09/14/2018

Trade name: CCW 570 Primer

• **Specific end use(s):** No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

Components with limit values that require monitoring at the workplace:					
80-62-6 methyl methacrylate					
EL (Canada)	Short-term value: 100 ppm Long-term value: 50 ppm S(D)				
EV (Canada)	Short-term value: 100 ppm Long-term value: 50 ppm				
PEL (USA)	Long-term value: 410 mg/m³, 100 ppm				
REL (USA)	Long-term value: 410 mg/m³, 100 ppm				
TLV (USA)	Short-term value: 410 mg/m³, 100 ppm Long-term value: 205 mg/m³, 50 ppm DSEN				
 Additional information: The lists that were valid during the creation were used as basis. Personal protective equipment General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all solled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eyes and skin. Breathing equipment: Use suitable respiratory protective device in case of insufficient ventilation. Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Material of gloves: Nitrile rubber, NBR Natural rubber, NR Eye protection: 					
Tightly sealed goggles					
	nd abomical much outing				

· Form:	Liquid
· Color:	According to product specification
· Odor:	Acrid
· Odor threshold:	Not determined.

Printing date 09/14/2018

Reviewed on 09/14/2018

Trade name: CCW 570 Primer

	(Contd. of page
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	-48 °C
Boiling point/Boiling range:	101 °C
Flash point:	10 °C
· Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	430 °C
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive ai
	vapor mixtures are possible.
Explosion limits	
Lower:	2.1 Vol %
Upper:	12.5 Vol %
Vapor pressure at 20 °C:	47 hPa
Density at 20 °C:	0.944 g/cm ³
Relative density:	Not determined.
Vapor density:	Not determined.
Evaporation rate:	Not determined.
Solubility in / Miscibility with	
Water at 20 °C:	1.6 g/l
Partition coefficient (n-octanol/wa	ater): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
VOC content:	0.00 %
	0.0 g/l / 0.00 lb/gl
Other information	No further relevant information available.

10 Stability and reactivity

• Thermal decomposition / conditions to be avoided:

- No decomposition if used according to specifications. Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 6)

CA

Printing date 09/14/2018

Reviewed on 09/14/2018

Trade name: CCW 570 Primer

(Contd. of page 5)

3

3

11 Toxicological information

- · Information on toxicological effects:
- · Acute toxicity
- · LD/LC50 values that are relevant for classification:

80-62-6 methyl methacrylate

Oral LD50 7,872 mg/kg (rat)

- Specific symptoms in biological assay: No further relevant information available.
- Primary irritant effect
- · on the skin: Irritant to skin and mucous membranes.
- \cdot on the eye: No irritating effect.
- Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

80-62-6 methyl methacrylate

103-11-7 2-ethylhexyl acrylate

· NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

- Aquatic toxicity: No further relevant information available.
- Persistence and degradability: No further relevant information available.
- · Behavior in environmental systems
- · Bioaccumulative potential: No further relevant information available.
- Mobility in soil: No further relevant information available.
- Additional ecological information
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

• Other adverse effects: No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Reviewed on 09/14/2018

Trade name: CCW 570 Primer

Printing date 09/14/2018

(Contd. of page 6)

Uncleaned packagings Recommendation:

Place in a sealed container and label as waste. Place in a safe area, and comply with all federal, state, provincial and local regulations for disposal.

UN-Number	
DOT, TDG, IMDG, IATA	UN1993
UN proper shipping name	
DOT	Flammable liquids, n.o.s. (Methyl methacryla
TDG	monomer, stabilized) 1993 Flammable liquids, n.o.s. (Methyl methacryla
	monomer, stabilized)
IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (METHY METHACRYLATE MONOMER, STABILIZED)
Transport hazard class(es)	
DOT	
rumar uan	
Class	3 Flammable liquids
Label TDG, IMDG, IATA	3
Class Label	3 Flammable liquids 3
	5
Packing group DOT, TDG, IMDG, IATA	11
Environmental hazards:	
Marine pollutant:	No
Special precautions for user:	Warning: Flammable liquids
Danger code (Kemler): EMS Number:	339 E E S E
EMS Number: Stowage Category	F-E, <u>S-E</u> B
Transport in bulk according to Annex I	
MARPOL73/78 and the IBC Code:	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L

Printing date 09/14/2018

Reviewed on 09/14/2018

Trade name: CCW 570 Primer

	(Contd. of page 7
· Hazardous substance:	1000 lbs, 454 kg
 TDG Excepted quantities (EQ) 	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUIDS, N.O.S. (METHYL METHACRYLATE MONOMER, STABILIZED), 3, II

15 Regulatory information

 $^{\cdot}$ Safety, health and environmental regulations/legislation specific for the substance or mixture $^{\cdot}$ Sara

- Section 355 (extremely hazardous substances):
- None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

- 80-62-6 methyl methacrylate
- TSCA (Toxic Substances Control Act):

All ingredients are listed or exempted

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

• Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Canadian substance listings

· Canadian Domestic Substances List (DSL/NDSL):

All ingredients are listed.

· Canadian Ingredient Disclosure list (limit 0.1%):

None of the ingredients is listed.

· Canadian Ingredient Disclosure list (limit 1%):

80-62-6 methyl methacrylate

2082-81-7 tetramethylene dimethacrylate

103-11-7 2-ethylhexyl acrylate

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)

Printing date 09/14/2018

Reviewed on 09/14/2018

Trade name: CCW 570 Primer

(Contd. of page 8) · Hazard pictograms GHS02 GHS07 Signal word Danger · Hazard-determining components of labeling: methyl methacrylate 2-ethylhexyl acrylate tetramethylene dimethacrylate · Hazard statements Highly flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause respiratory irritation. **Precautionary statements** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting] equipment. Use non-sparking tools. Take actions to prevent static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

16 Other information

This SDS format meets ANSI Z400.1-1998 and OSHA 1910.1200 requirements. We provide the information contained herein in good faith but make no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Product use and conditions of use are beyond our control. Warranty of materials is limited to test results of product performance as detailed in certificates of compliance. Interpretation of test results is the responsibility of end-user. No other warranties, expressed or implied, are made.

(Contd. on page 10)

CA -

Printing date 09/14/2018

Reviewed on 09/14/2018

Trade name: CCW 570 Primer

	(Contd. of page 9)
· Department issuing SDS: Product safety department	
Contact: Stephen Nowicki	
Date of preparation / last revision 09/14/2018 / -	
Abbreviations and acronyms:	
IMDG: International Maritime Code for Dangerous Goods	
DOT: US Department of Transportation	
IATA: International Air Transport Association	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	