

Material Name: Barritech VP-LT Product #:323779-5 gal 324296-50 gal

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

Barritech VP-LT

Synonyms

Sealant

Chemical Family

Mastic

Product Use

Indoor, outdoor water based duct sealant

Restrictions on Use

For industrial use only.

Manufacturer Information

Carlisle Coatings and Waterproofing, Inc.

900 Hensley Lane Wylie, TX 75098

www.carlisleccw.com

Phone Numbers:

Medical Emergency

CHEMTREC (USA): 800-424-9300

MSDS Assistance; 972-442-6545 Technical Assistance: 888-229-2199

Customer Service: 888-229-0199

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Serious Eye Damage/Eye Irritation - Category 2A

Reproductive Toxicity - Category 1B

Specific Target Organ Toxicity - Single Exposure - Category 1 (body, central nervous system, systemic toxicity, eyes)

Specific Target Organ Toxicity - Single Exposure - Category 3

Specific Target Organ Toxicity - Repeated Exposure - Category 1 (eyes,central nervous system)

GHS Label Elements

Symbol(s)





Signal Word
Danger

Page 1 of 20 Issue date: 2018-06-01 Revision 3.0



Material Name: Barritech VP-LT Product #:323779-5 gal 324296-50 gal

Hazard Statement(s)

Causes serious eye irritation

May damage fertility or the unborn child

Causes damage to organs

May cause respiratory irritation

Causes damage to organs through prolonged or repeated exposure

Precautionary Statement(s)

Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use only outdoors or in a well-ventilated area

Wear eye protection/face protection

Do not breathe dust/fume/gas/mist/vapours/spray

Wash thoroughly after handling

Do not eat, drink or smoke when using this product

Response

If exposed: Call a POISON CENTER or doctor/physician

IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Specific treatment (see label)

Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations

Statement of Unknown Toxicity

2.121% of the mixture consists of ingredient(s) of unknown acute toxicity.

Other Hazards

No additional information available.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
Mixture	Polymer, ethyl acrylate and methacrylic acid	1-5
Trade Secret	De-foaming agent	0.1-1

Page 2 of 20 Issue date: 2018-06-01 Revision 3.0



Material Name: Barritech VP-LT Product #:323779-5 gal 324296-50 gal

Trade Secret	Nonylphenol polyethylene glycol ether	0.1-1
Trade Secret	Chlorinated paraffins	5-10
7664-41-7	Ammonia	0.1-1
107-21-1	Ethylene glycol	0.1-1
Mixture	Polymer, vinyl acetate and vinyl acetate-acrylic	15-40
Trade Secret	Plasticizer	5-10
Trade Secret	Clay compound	0.1-1
1317-65-3	Limestone	15-40
Trade Secret	Silica, amorphous, fumed	0.1-1
67-56-1	Methanol	7-13
Mixture	4,4-Dimethyloxazolidine	0.1-1
Mixture	Carbamic acid mixture	0.1-1
Mixture	Polycarboxylate salt	0.1-1
Mixture	Decanedioic acid ester	0.1-1

Section 4 - FIRST AID MEASURES

Description of Necessary Measures

If exposed: Call a POISON CENTER or doctor/physician.

Inhalation

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

Skin

Wash exposed skin with soap and water. Remove contaminated clothing and wash it before reuse. If skin irritation occurs, get medical advice/attention.

Eyes

Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Ingestion

Do NOT induce vomiting. If swallowed, get medical attention.

Page 3 of 20 Issue date: 2018-06-01 Revision 3.0



Material Name: Barritech VP-LT Product #:323779-5 gal 324296-50 gal

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

Most Important Symptoms/Effects

Acute

Causes serious eye irritation. Causes damage to central nervous system, body, eyes, systemic toxicity. May cause respiratory irritation.

Delayed

May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure: eyes, central nervous system.

Note to Physicians

Contains: ethylene glycol, ammonia, methanol.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Use carbon dioxide, regular dry chemical, regular foam or water.

Unsuitable Extinguishing Media

None known.

Special Hazards Arising from the Chemical

Slight fire hazard. Sealed containers may rupture or explode if exposed to heat.

Hazardous Combustion Products

oxides of carbon, oxides of nitrogen, hydrocarbons

Advice for firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Fire Fighting Measures

Remove product from area of fire. Stay upwind and keep out of low areas.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Absorb with earth, sand or other non-combustible material and transfer to container. Dike for later disposal. Dispose in accordance with all applicable regulations.

Environmental Precautions

Avoid release to the environment.

Page 4 of 20 Issue date: 2018-06-01 Revision 3.0



Material Name: Barritech VP-LT Product #:323779-5 gal 324296-50 gal

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

This product contains crystalline silica, which is a known carcinogen: Do not grind or sand. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. KEEP OUT OF REACH OF CHILDREN.

Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep container tightly closed Store locked up

Store above 0°C. Store below 45°C. Do not cut, puncture, or weld on or near this container. Avoid contact with incompatible materials.

Incompatible Materials

strong acids, strong oxidizing agents

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Ammonia	7664-41-7	
ACGIH:	25 ppm TWA 35 ppm STEL	
NIOSH:	25 ppm TWA; 18 mg/m3 TWA	35 ppm STEL; 27 mg/m3 STEL
	300 ppm IDLH	
Europe:	20 ppm TWA; 14 mg/m3 TWA	50 ppm STEL; 36 mg/m3 STEL
OSHA (US):	50 ppm TWA; 35 mg/m3 TWA	
Mexico:	25 ppm TWA LMPE-PPT; 18 mg/m3 TWA LMPE-PPT	
	35 ppm STEL [LMPE-CT]; 27 mg/m3 STEL [LMPE-CT]	
Ethylene glycol	107-21-1	
ACGIH:	100 mg/m3 Ceiling aerosol only	

Page 5 of 20 Issue date: 2018-06-01 Revision 3.0



Material Name: Barritech VP-LT Product #:323779-5 gal 324296-50 gal

		324296	
Europe:	20 ppm TWA; 52 mg/m3 TWA	40 ppm STEL; 104 mg/m3 STEL	
	Possibility of significant uptake through the skin		
Mexico:	100 mg/m3 Ceiling aerosol		
Clay compound	Trade Secret		
ACGIH:	0.025 mg/m3 TWA respirable fraction		
NIOSH:	0.05 mg/m3 TWA respirable dust	50 mg/m3 IDLH respirable dust	
OSHA (US):	((30)/(%SiO2 + 2) mg/m3 TWA) total dust; ((250)/(%SiO2 + 5) mppcf TWA) respirable fraction; ((10)/(%SiO2 + 2) mg/m3 TWA) respirable fraction		
Mexico:	0.1 mg/m3 TWA LMPE-PPT respirable fra	action	
Limestone	1317-65-3		
NIOSH:	10 mg/m3 TWA total dust; 5 mg/m3 TWA respirable dust		
OSHA (US):	15 mg/m3 TWA total dust; 5 mg/m3 TWA	respirable fraction	
Mexico:	10 mg/m3 TWA LMPE-PPT	20 mg/m3 STEL [LMPE-CT]	
Methanol	67-56-1		
ACGIH:	200 ppm TWA	250 ppm STEL	
	Skin - potential significant contribution to	overall exposure by the cutaneous route	
NIOSH:	200 ppm TWA; 260 mg/m3 TWA	250 ppm STEL; 325 mg/m3 STEL	
	Potential for dermal absorption		
	6000 ppm IDLH		
Europe:	200 ppm TWA; 260 mg/m3 TWA		
	Possibility of significant uptake through the skin		
OSHA (US):	200 ppm TWA; 260 mg/m3 TWA		
Mexico:	200 ppm TWA LMPE-PPT; 260 mg/m3 TV	200 ppm TWA LMPE-PPT; 260 mg/m3 TWA LMPE-PPT	
	250 ppm STEL [LMPE-CT]; 310 mg/m3 STEL [LMPE-CT]		
	Skin - potential for cutaneous absorption		

Page 6 of 20 Issue date: 2018-06-01 Revision 3.0



Material Name: Barritech VP-LT Product #:323779-5 gal 324296-50 gal

Phthalo blue	Mixture
ACGIH:	2 mg/m3 TWA particulate matter containing no asbestos and <1% crystalline silica, respirable fraction
NIOSH:	2 mg/m3 TWA (containing no Asbestos and <1% Quartz) respirable dust
	1000 mg/m3 IDLH (containing no Asbestos and <1% Quartz)
OSHA (US):	20 mppcf TWA (if 1% Quartz or more, use Quartz limit)
Mexico:	2 mg/m3 TWA LMPE-PPT respirable fraction

Biological limit value

There are no biological limit values for any of this product's components.

Engineering Controls

Provide adequate ventilation. Ensure compliance with applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment

Eve/face protection

Wear safety glasses or safety goggles, with a faceshield, as appropriate. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin Protection

Wear appropriate work clothing.

Respiratory Protection

A NIOSH approved respirator with a dust, mist, and fume filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits or when symptoms have been observed that are indicative of overexposure.

Glove Recommendations

Wear appropriate gloves. Recommended material: Hycron(R), neoprene, nitrile.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	blue liquid	Physical State	liquid
Odor	Slight,ammonia	Color	blue
Odor Threshold	Not available	рН	8 - 9
Melting Point	Not available	Boiling Point	212 °F
Freezing point	Not available	Evaporation Rate	30 - 34 % volatile
Boiling Point Range	Not available	Flammability (solid, gas)	Not available
Autoignition	Not available	Flash Point	Not available

Page 7 of 20 Issue date: 2018-06-01 Revision 3.0



Material Name: Barritech VP-LT Product #:323779-5 gal 324296-50 gal

Lower Explosive Limit	Not available	Decomposition	Not available
Upper Explosive Limit	Not available	Vapor Pressure	Not available
Vapor Density (air=1)	<1	Specific Gravity (water=1)	Not available
Water Solubility	Soluble	Partition coefficient: n-octanol/water	Not available
Viscosity	>50 Kcps	Solubility (Other)	Not available
Density	1.35 (relative)	voc	213 g/L (SCAQMD calculation method)

Other Information

No additional information available.

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal conditions of use.

Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

Incompatible Materials

Strong acids, strong oxidizing agents

Hazardous decomposition products

Oxides of carbon, oxides of nitrogen, hydrocarbons

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

May cause respiratory irritation. May cause adverse effects on the central nervous system.

Skin Contact

May cause mild skin irritation.

Eye Contact

Causes serious eye irritation.

Page 8 of 20 Issue date: 2018-06-01 Revision 3.0



Material Name: Barritech VP-LT Product #:323779-5 gal 324296-50 gal

Ingestion

Methanol can produce blindness with onset of symptoms being delayed for 18-24 hours.

Acute and Chronic Toxicity Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Polymer, ethyl acrylate and methacrylic acid (Mixture)

Oral LD50 Rat >5000 mg/kg Dermal LD50 Rabbit >5000 mg/kg

De-foaming agent (Trade Secret)

Oral LD50 > 2000 mg/kg

Nonylphenol polyethylene glycol ether (Trade Secret) Oral LD50 Rat 2780 mg/kg

Chlorinated paraffins (Trade Secret)
Oral LD50 Rat >4 g/kg

Ammonia (7664-41-7)

Oral LD50 Rat 350 mg/kg Inhalation LC50 Rat 2000 ppm 4 h

Ethylene glycol (107-21-1)

Oral LD50 Rat 4700 mg/kg Dermal LD50 Rat 10600 mg/kg Inhalation LC50 Rat >200 mg/m3 vapor 4 hr

Polymer, vinyl acetate and vinyl acetate-acrylic (Mixture)

Oral LD50 Rat >5000 mg/kg Dermal LD50 Rat >2000 mg/kg

Plasticizer (Trade Secret)

Oral LD50 Rat 20400 mg/kg Dermal LD50 Rat >10000 mg/kg Inhalation LC50 Rat >6.7 mg/L 4 h

Clay compound (Trade Secret)

Oral LD50 Rat 500 mg/kg

Limestone (1317-65-3)

Oral LD50 Rat 6450 mg/kg

Silica, amorphous, fumed (Trade Secret)

Oral LD50 Rat >5000 mg/kg Dermal LD50 Rabbit >5000 mg/kg Inhalation LC50 Rat >0.139 mg/L 4 hr

Page 9 of 20 Issue date: 2018-06-01 Revision 3.0



Material Name: Barritech VP-LT Product #:323779-5 gal 324296-50 gal

Methanol (67-56-1)

Oral LD50 Rat 6200 mg/kg Inhalation LC50 Rat 22500 ppm 8 h

4,4-Dimethyloxazolidine (Mixture)

Oral LD50 Rat 1037 mg/kg Dermal LD50 Rat >2000 mg/kg Inhalation LC50 Rat 1.1 mg/L 4 hr

Carbamic acid mixture (Mixture)

Oral LD50 Rat >2000 mg/kg Dermal LD50 Rabbit >2000 mg/kg Inhalation LC50 Rat >2.04 mg/L 4 hr

Polycarboxylate salt (Mixture)

Oral LD50 Rat >5000 mg/kg Dermal LD50 Rabbit >2000 mg/kg

Decanedioic acid ester (Mixture)

Oral LD50 Rat >2000 mg/kg

Immediate Effects

Causes serious eye irritation. Causes damage to central nervous system, body, eyes, systemic toxicity. May cause respiratory irritation.

Delayed Effects

May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure: eyes, central nervous system.

Irritation/Corrosivity Data

Causes serious eye irritation. May cause respiratory irritation. May cause mild skin irritation.

Respiratory Sensitization

No data available.

Dermal Sensitization

No data available.

Component Carcinogenicity

	· ·
Chlorinated paraffins	Trade Secret
IARC:	Monograph 48 [1990] (Group 2B (possibly carcinogenic to humans))
DFG:	Category 3B (could be carcinogenic for man)
OSHA:	Present

Page 10 of 20 Issue date: 2018-06-01 Revision 3.0



Material Name: Barritech VP-LT Product #:323779-5 gal 324296-50 gal

Ethylene glycol	107-21-1	
ACGIH:	A4 - Not Classifiable as a Human Carcinogen	
Plasticizer	Trade Secret	
IARC:	Monograph 73 [1999]; Supplement 7 [1987] (Group 3 (not classifiable))	
Clay compound	Trade Secret	
ACGIH:	A2 - Suspected Human Carcinogen	
IARC:	Monograph 100C [2012]; Monograph 68 [1997] (Group 1 (carcinogenic to humans))	
NTP:	Known Human Carcinogen (respirable size)	
DFG:	Category 1 (causes cancer in man, alveola fraction)	
OSHA:	Present (respirable size)	
Silica, amorphous, fumed	Trade Secret	
IARC:	Monograph 68 [1997] (Group 3 (not classifiable))	
Phthalo blue	Mixture	
ACGIH:	A4 - Not Classifiable as a Human Carcinogen (containing no asbestos fibers)	
IARC:	Monograph 93 [2010] (inhaled); Supplement 7 [1987]; Monograph 42 [1987] (Group 3 (not classifiable))	
DFG:	Category 3B (could be carcinogenic for man, free of asbestos fibers)	

Germ Cell Mutagenicity

No data available.

Reproductive Toxicity

May damage fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure

Central nervous system, body, systemic toxicity, eyes

Specific Target Organ Toxicity - Repeated Exposure

Central nervous system, eyes

Page 11 of 20 Issue date: 2018-06-01 Revision 3.0



Material Name: Barritech VP-LT Product #:323779-5 gal 324296-50 gal

Aspiration hazard

No data available.

Medical Conditions Aggravated by Exposure

No data available.

Additional Data

This product contains crystalline silica, which is a known carcinogen. However, this component is bound by the polymer portion of the sealant. The only way this component would be released is through incineration. Therefore, this product is not considered a carcinogen.

Section 12 - ECOLOGICAL INFORMATION

Ecotoxicity

Avoid release to the environment.

Component Analysis - Aquatic Toxicity

Component Analysis - Aquatic Toxicity		
Polymer, ethyl acrylate and methacrylic acid	Mixture	
Fish:	LC50 96 hr Pimephales promelas >1000 mg/L	
Invertebrate:	EC50 48 hr Daphnia magna >1000 mg/L	
Chlorinated paraffins	Trade Secret	
Fish:	LC50 96 h Lepomis macrochirus >300 mg/L [static]; LC50 96 h Oncorhynchus mykiss >0.0109 mg/L [flow-through]; LC50 96 h Oncorhynchus mykiss 94.5 - 271 mg/L [static]; LC50 96 h Lepomis macrochirus >0.1 mg/L [flow-through]; LC50 96 h Pimephales promelas >100 mg/L [static]	
Invertebrate:	EC50 48 hr Daphnia magna 0.0059 mg/L	
Ammonia	7664-41-7	
Fish:	LC50 96 h Cyprinus carpio 0.44 mg/L; LC50 96 h Lepomis macrochirus 0.26 - 4.6 mg/L; LC50 96 h Lepomis macrochirus 1.17 mg/L [flow-through]; LC50 96 h Pimephales promelas 0.73 - 2.35 mg/L; LC50 96 h Pimephales promelas 5.9 mg/L [static]; LC50 96 h Poecilia reticulata >1.5 mg/L; LC50 96 h Poecilia reticulata 1.19 mg/L [static]	
Invertebrate:	LC50 48 h Daphnia magna 25.4 mg/L IUCLID	

Page 12 of 20 Issue date: 2018-06-01 Revision 3.0



Material Name: Barritech VP-LT Product #:323779-5 gal 324296-50 gal

	324290
Algae:	EC50 72 h Desmodesmus subspicatus 15 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna 65 mg/L IUCLID
Ethylene glycol	107-21-1
Fish:	LC50 96 h Oncorhynchus mykiss 41000 mg/L; LC50 96 h Oncorhynchus mykiss 14 - 18 mL/L [static]; LC50 96 h Lepomis macrochirus 27540 mg/L [static]; LC50 96 h Oncorhynchus mykiss 40761 mg/L [static]; LC50 96 h Pimephales promelas 40000 - 60000 mg/L [static]; LC50 96 h Poecilia reticulata 16000 mg/L [static]
Algae:	EC50 96 h Pseudokirchneriella subcapitata 6500 - 13000 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna 46300 mg/L IUCLID
Polymer, vinyl acetate and vinyl acetate-acrylic	Mixture
Fish:	LC50 96 hr Oncorhynchis mykiss >1000 mg/L
Invertebrate:	EC50 48 hr Daphnia magna >100 mg/L
Plasticizer	Trade Secret
Fish:	LC50 96 h Oncorhynchus mykiss 1 - 10 mg/L [static]; LC50 96 h Oncorhynchus mykiss 0.82 mg/L [flow-through]; LC50 96 h Pimephales promelas 1.39 - 3.88 mg/L [flow-through]; LC50 96 h Pimephales promelas >0.78 mg/L [static]; LC50 96 h Lepomis macrochirus 1 - 10 mg/L [static]
Algae:	EC50 96 h Pseudokirchneriella subcapitata 0.02 - 0.25 mg/L EPA; EC50 72 h Pseudokirchneriella subcapitata 0.2 - 28.2 mg/L EPA
Invertebrate:	EC50 48 h Daphnia magna 0.9 - 1.1 mg/L [static] EPA; EC50 48 h Daphnia magna >0.76 mg/L [Flow through] EPA; EC50 48 h Daphnia magna 1.28 mg/L [semi-static] EPA; EC50 48 h Daphnia magna 0.97 mg/L IUCLID
Silica, amorphous, fumed	Trade Secret
Fish:	LC50 96 hr Danio rerio >10000 mg/L
Invertebrate:	EC50 24 hr Daphnia magna >10000 mg/L

Page 13 of 20 Issue date: 2018-06-01 Revision 3.0



Material Name: Barritech VP-LT Product #:323779-5 gal 324296-50 gal

Methanol	67-56-1
Fish:	LC50 96 h Pimephales promelas 28200 mg/L [flow-through]; LC50 96 h Pimephales promelas >100 mg/L [static]; LC50 96 h Oncorhynchus mykiss 19500 - 20700 mg/L [flow-through]; LC50 96 h Oncorhynchus mykiss 18 - 20 mL/L [static]; LC50 96 h Lepomis macrochirus 13500 - 17600 mg/L [flow-through]
4,4-Dimethyloxazolidine	Mixture
Fish:	LC50 96 hr Rainbow trout 95 mg/L [flow-through]
Phthalo blue	Mixture
Fish:	LC50 96 h Brachydanio rerio >100 g/L [semi-static]
Decanedioic acid ester	Mixture
Fish:	LC50 96 h Lepomis macrochirus 0.97 mg/L [static]

Persistence and Degradability

No information available for the product.

Bioaccumulative Potential

No information available for the product.

Mobility

No information available for the product.

Other Toxicity

No additional information available.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents/container in accordance with local/regional/national/international regulations.

Section 14 - TRANSPORT INFORMATION

US DOT Information:

UN/NA #: Not regulated

Page 14 of 20 Issue date: 2018-06-01 Revision 3.0



Material Name: Barritech VP-LT Product #:323779-5 gal 324296-50 gal

IATA Information: UN#: Not regulated

IMDG Information: UN#: Not regulated

TDG Information: UN#: Not regulated

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Ammonia	7664-41-7
SARA 302:	500 lb TPQ
SARA 313:	1 % de minimis concentration (includes anhydrous Ammonia and aqueous Ammonia from water dissociable Ammonium salts and other sources, 10% of total aqueous Ammonia is reportable under this listing)
CERCLA:	100 lb final RQ; 45.4 kg final RQ
OSHA (safety):	10000 lb TQ anhydrous); 15000 lb TQ solution, >44% Ammonia by weight)
SARA 304:	100 lb EPCRA RQ
Ethylene glycol	107-21-1
SARA 313:	1 % de minimis concentration
CERCLA:	5000 lb final RQ; 2270 kg final RQ
Plasticizer	Trade Secret
CERCLA:	100 lb final RQ; 45.4 kg final RQ
Methanol	67-56-1
SARA 313:	1 % de minimis concentration
CERCLA:	5000 lb final RQ; 2270 kg final RQ

Page 15 of 20 Issue date: 2018-06-01 Revision 3.0



Material Name: Barritech VP-LT Product #:323779-5 gal 324296-50 gal

Carbamic acid mixture	Mixture
CERCLA:	10 lb final RQ; 4.54 kg final RQ

SARA Section 311/312 (40 CFR 370 Subparts B and C)

Acute Health: Yes Chronic Health: Yes Fire: No Pressure: No Reactivity: No

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Chlorinated paraffins	Trade Secret	No	Yes	No	No	No
Ammonia	7664-41-7	Yes	Yes	Yes	Yes	Yes
Ethylene glycol	107-21-1	Yes	Yes	Yes	Yes	Yes
Plasticizer	Trade Secret	Yes	Yes	No	Yes	Yes
Clay compound	Trade Secret	No	Yes	Yes	Yes	Yes
Limestone	1317-65-3	No	Yes	Yes	Yes	Yes
Methanol	67-56-1	Yes	Yes	Yes	Yes	Yes
Carbamic acid mixture	Mixture	No	No	No	Yes	No
Phthalo blue	Mixture	Yes	Yes	Yes	Yes	Yes

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause cancer WARNING! This product contains a chemical known to the state of California to cause reproductive/developmental effects

Plasticizer	Trade Secret
Repro/Dev. Tox	developmental toxicity, 12/2/2005
Clay compound	Trade Secret
Carc:	carcinogen, 10/1/1988 (airborne particles of respirable size)
Methanol	67-56-1
Repro/Dev. Tox	developmental toxicity, 3/16/2012

Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

Page 16 of 20 Issue date: 2018-06-01 Revision 3.0



Material Name: Barritech VP-LT Product #:323779-5 gal 324296-50 gal

Ammonia	7664-41-7
	1 %
Ethylene glycol	107-21-1
	1 %
Plasticizer	Trade Secret
	1 %
Clay compound	Trade Secret
	1 %
Methanol	67-56-1
	1 %

Component Analysis - Inventory

Polymer, ethyl acrylate and methacrylic acid (Mixture)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Nonylphenol polyethylene glycol ether (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	No

Chlorinated paraffins (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Ammonia (7664-41-7)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Ethylene glycol (107-21-1)

Page 17 of 20 Issue date: 2018-06-01 Revision 3.0



Material Name: Barritech VP-LT Product #:323779-5 gal 324296-50 gal

										3	2429
US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes
Plasti	cizer (T	Γrade	Secre	t)							
US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes
Clay o	compo	und (Гrade	Secre	t)						
US	CA	EU	AU	PH	ID	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes
Limes	stone (1317-	65-3)								
US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	NSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes
Silion	omor	ahous	fum	od (Tr	ade Secret	1	1	1	'		
US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
No	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes
Math	anol (6	7 56	1)								
US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes
1 / D	imethy	lovez	alidin	_ (M:	vtura)		1	1			
us	CA	EU	AU	PH	IP -	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes

Carbamic acid mixture (Mixture)

Page 18 of 20 Issue date: 2018-06-01 Revision 3.0



Material Name: Barritech VP-LT Product #:323779-5 gal 324296-50 gal

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes

Phthalo blue (Mixture)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Decanedioic acid ester (Mixture)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes

Section 16 - OTHER INFORMATION

HMIS Rating

Health: 2* Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

NFPA Ratings

Health: 2 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes Revision Date: June 1, 2018 Revision Note: General Update

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts ™

Page 19 of 20 Issue date: 2018-06-01 Revision 3.0



Material Name: Barritech VP-LT Product #:323779-5 gal 324296-50 gal

- ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

Other Information

Disclaimer:

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, CCWI Company must rely upon the hazard evaluation of such components submitted by that product's manufacturer or importer. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.

Page 20 of 20 Issue date: 2018-06-01 Revision 3.0