

CARLISLE COATINGS & WATERPROOFING INCORPORATED

900 Hensley Lane • Wylie, TX 75098 • (972) 442-6545

CCW MiraSEAL Watermark Material Warranty Guidelines

Application	Watermark Material Warranty	MiraSEAL	Fabric Reinforced	Protection Course	MiraDRAIN Drainage Composite	CCW-Root Barrier
Backfilled Walls	5	60 mils	no	PB-V or 200V		
	10	60 mils	no	PB-V or 200V		
	15	90 mils	no		6200	
	20	120 mils	yes		6200XL	
Split Slab	5	60 mils	no	PB-H		
	10	60 mils	no	PB-H		
	15	90 mils	yes	PB-HS	9000/9900	
	20	120 mils	yes	PB-HS	9000/9900	
Mud-Set Pavers	5	60 mils	no	PB-H		
	10	60 mils	no	PB-H		
	15	90 mils	yes	PB-HS	9000/9900	
	20	120 mils	yes	PB-HS	9000/9900	
Pedestrian Pavers - Sand-Set	5	60 mils	no	PB-H		
	10	60 mils	no	PB-H		
	15	90 mils	yes	PB-HS	9000	
	20	120 mils	yes	PB-HS	9000	
Vehicular Pavers - Sand-Set	5	60 mils	no	PB-H		
	10	60 mils	no	PB-H		
	15	90 mils	yes	PB-HS	9900	
	20	120 mils	yes	PB-HS	9900	
Pedestal & Pavers	5	60 mils	no	PB-H		
	10	60 mils	no	PB-H		
	15	90 mils	yes	PB-HS	9000	
	20	120 mils	yes	PB-HS	9000	
Planters	5	90 mils	yes	PB-H	9800	yes
	10	90 mils	yes	PB-H	9800	yes
	15	120 mils	yes	PB-HS	9800	yes
	20	120 mils	yes	PB-HS	9800	yes
Roof Garden	5	90 mils	yes	PB-H	9800	yes
	10	90 mils	yes	PB-H	9800	yes
	15	120 mils	yes	PB-HS	9800	yes
	20	120 mils	yes	PB-HS	9800	yes

ALL WARRANTIES MUST BE APPROVED BY CCW PRIOR TO APPLICATION
 ALL WARRANTY MODIFICATIONS MUST BE APPROVED BY CCW PRIOR TO APPLICATION
 Reinforce all detail areas including inside / outside corners, cracks and penetrations.
 All applications in the water table must be 120 mils reinforced
 CCW-201 is the approved / required sealant
 CMU substrates may require a parge coat.

CARLISLE COATINGS & WATERPROOFING INCORPORATED

900 Hensley Lane • Wylie, TX 75098 • (972) 442-6545

CCW MiraSEAL Watermark Ultra Warranty Guidelines

Application	Watermark Ultra Warranty	MiraSEAL	Fabric Reinforced	Protection Course	MiraDRAIN Drainage Composite	CCW-Root Barrier
Backfilled Walls	5	60 mils	no		6200	
	10	60 mils	no		6200	
	15	90 mils	no	PB-HS	6200XL	
	20	120 mils	yes	PB-HS	6200XL	
Split Slab	5	90 mils	yes	PB-H	9000/9900	
	10	90 mils	yes	PB-H	9000/9900	
	15	120 mils	yes	PB-HS	9000/9900	
	20	120 mils	yes	PB-HS	9000/9900	
Mud-Set Pavers	5	90 mils	yes	PB-H	9000/9900	
	10	90 mils	yes	PB-H	9000/9900	
	15	120 mils	yes	PB-HS	9000/9900	
	20	120 mils	yes	PB-HS	9000/9900	
Pedestrian Pavers - Sand-Set	5	90 mils	yes	PB-H	9000	
	10	90 mils	yes	PB-H	9000	
	15	120 mils	yes	PB-HS	9000	
	20	120 mils	yes	PB-HS	9000	
Vehicular Pavers - Sand-Set	5	90 mils	yes	PB-H	9900	
	10	90 mils	yes	PB-H	9900	
	15	120 mils	yes	PB-HS	9900	
	20	120 mils	yes	PB-HS	9900	
Pedestal & Pavers	5	60 mils	no	PB-H		
	10	60 mils	no	PB-H		
	15	90 mils	yes	PB-HS	9000	
	20	120 mils	yes	PB-HS	9000	
Planters	5	90 mils	yes	PB-H	9800	yes
	10	90 mils	yes	PB-H	9800	yes
	15	120 mils	yes	PB-HS	9800	yes
	20	120 mils	yes	PB-HS	9800	yes
Roof Garden	5	90 mils	yes	PB-H	9800	yes
	10	90 mils	yes	PB-H	9800	yes
	15	120 mils	yes	PB-HS	9800	yes
	20	120 mils	yes	PB-HS	9800	yes

All WARRANTIES MUST BE APPROVED BY CCW PRIOR TO APPLICATION

ALL WARRANTY MODIFICATIONS MUST BE APPROVED BY CCW PRIOR TO APPLICATION

Ultra Warranties issued to Authorized Applicators ONLY

Flood test is required for 5, 10, 15 Ultra warranties and EFVM required for 20 year Ultra Warranty

Reference "Warranty Pricing" document for fees concerning warranty cost

Reinforce all detail areas including inside / outside corners, cracks and penetrations.

All applications in the water table must be 120 mils reinforced

CCW-201 is the approved required sealant

CMU substrates may require a parge coat