

2" Seam Fastening Plates



Overview

Carlisle's 2" Seam Fastening Plates are specifically designed for use with RUSS or membrane securement for reinforced EPDM. When specified in the current Carlisle specifications and details, the plates can be used at angle changes with reinforced EPDM, TPO, or PVC membranes.

Features and Benefits

- » Compatible with Carlisle's HP Fasteners, Purlin Fastener, HP-X Fasteners, HD 14-10 Fasteners, and CD-10 Fasteners
- » Symmetrical load distribution

Installation

1. Position 2" Seam Fastening Plates as indicated by Carlisle specifications and details
2. Secure 2" Seam Fastening Plates using the appropriate Carlisle fastener

Review Carlisle specifications and details for complete installation information.

Precautions

- » Eye protection is recommended during drilling and installation of plates and fasteners
- » Use care to avoid over driving the fastener

Typical Properties and Characteristics

Size	2" Diameter (50mm)
Weight/ Carton	22 lbs. (10 kg)
Quantity	1,000/ Carton
Material	Galvalume® Coated Steel
Thickness	22 Gauge
Pull Through Resistance	500 lb./min (225 kg/min)
Corrosion Resistance	Galvalume coated steel meets FM 4470 Corrosion Test
Compatibility	Accepts Carlisle's HP Fasteners, Purlin Fastener, HP-X Fasteners, HD 14-10 Fasteners, and CD-10 Fasteners

Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.