

CAV-GRIP™ III Low-VOC Adhesive/Primer Accessories

Spray Guns & Replacement Tips



Overview

Carlisle's CAV-GRIP Spray Gun is an industrial grade spray gun for use with CAV-GRIP III Adhesive. The ergonomic handle makes it easy to apply bonding adhesive to vertical surfaces. The CAV-GRIP Spray Gun should be used to apply CAV-GRIP III Low-VOC Adhesive/Primer to various vertical surfaces. The CAV-GRIP Spray Gun with Extension is designed to be used to apply CAV-GRIP III to horizontal surfaces without the need to bend over.

Features and Benefits

- » Ergonomic 4-finger trigger and comfortable handle
- » Strong aluminum alloy frame
- » Interchangeable spray tip

Installation

1. Use the adjustment wheel to close the valve until ready to use
2. Ensure all fittings are tight and leak free
3. Position the gun tip 12 to 14 inches from the surface. This allows for maximum pattern width.
4. Try to hold the gun at a 90 degree angle to the surface by locking your wrist. Try not to move your wrist as that will cause an irregular spray pattern.
5. When you are done spraying, turn the adjustment wheel to the closed position. This will lock the gun.
6. When you want to resume spraying, turn the adjustment when to the open position. No cleaning should be needed if the hose and gun remain pressurized.
7. To clean the CAV-GRIP spray gun, turn the cylinder off at the valve. Ensure there is no adhesive left in the hose and gun. Hook the hose up to a cylinder of Low-VOC UN-TACK™ to clean the system. Turn cylinder off and drain Low-VOC UN-TACK from the hose.
8. Use an adjustable wrench to remove and replace spray tips as necessary.

Specifications

Specifications	
Spray Gun	
Tip	6501
Spray Angle	65°
GPM	1
Weight	1 lb
Spray Gun with Extension	
Tip	9502
Spray Angle	95°
GPM	2
Weight	1.5 lbs

Product Codes

Description	Product Code
Spray Gun	307490
Spray Gun w/ Extension	330912
Replacement Tips	332774

CAV-GRIP III Low-VOC Adhesive/Primer Accessories

Hose & Splitter



Specifications

Nominal Bore	0.25"
Nominal O.D.	0.50"
Maximum Working Pressure	750psi
Bend Radius	2.50"

Product Codes

Description	Product Code
6' Hose	304302
12' Hose	304303
18' Hose	304304
Splitter	332680

Overview

Nylon lined with a braided synthetic yarn reinforcement and synthetic rubber cover, the CAV-GRIP Hose should be used in conjunction with CAV-GRIP III and a CAV-GRIP Spray Gun. The CAV-GRIP Hose is available in 6-foot, 12-foot and 18-foot lengths. Two hoses can be attached to one CAV-GRIP III cylinder by using the Splitter.

Features and Benefits

- » Wide range of operating temperatures 0°F to 190°
- » Low change in length at operating pressure
- » Lightweight

Installation

1. Ensure all fittings are tight and leak free
2. No cleaning should be needed if the hose and gun remain pressurized.
3. To clean the CAV-GRIP spray gun, turn the cylinder off at the valve. Ensure there is no adhesive left in the hose and gun. Hook the hose up to a cylinder of Low-VOC UN-TACK to clean the system. Turn cylinder off and drain Low-VOC UN-TACK from the hose.
4. Use an adjustable wrench to attach the splitter to the CAV-GRIP cylinder.
5. Attach hoses to both ends of the splitter using an adjustable wrench.