

ROOF GARDEN

CCW Reinforcing Fabric



Overview

CCW Reinforcing Fabric is a 1.18 oz/square yard spunbonded polyester fabric used as the reinforcing layer in the CCW-500R Hot-Applied Liquid Membrane System. It is installed between layers of CCW-500R Hot Rubber to reinforce the system, adding rigidity and strength. Additionally, Carlisle's CCW Reinforcing Fabric helps to eliminate leaks by preventing the vertical passage of air bubbles through the system during the curing process.

Features and Benefits

- » Composed of 100% continuous filament polyester
- » Adds reinforcement
- » Fast and easy to install

Installation

Install the CCW Reinforcing Fabric while the first layer of CCW-500 is warm and tacky. The reinforcing fabric shall be applied without wrinkles and broomed to maximize adhesion to the first layer. Edges shall be overlapped a maximum of ½" and spliced with CCW-500. The reinforcing fabric shall be dry and free of dust prior to applying the second layer of CCW-500.

Review Carlisle specifications and details for complete application information.

Packaging

- » 36" by 667' (2000 ft²/roll)
 - 16 lb/roll
 - 15 rolls/pallet

Typical Properties and Characteristics

Physical Property	Typical Value
Weight	1.18 oz/yd ²
Thickness	9 mils
Grab Tensile MD	29 lbs
Grab Tensile XD	24 lbs
Trapezoidal Tear MD	11 lbs
Trapezoidal Tear XD	12 lbs
Mullen Burst	36 psi

Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.

LEED® Information

Pre-consumer Recycled Content	0%
Post-consumer Recycled Content	0%
Manufacturing Location	Raleigh/Durham, NC
Solar Reflectance Index (SRI)	N/A