Product Data

CARLISLE

COATING-READY

COVER TAPE



Overview

Coating-Ready Cover Tape is a polyester fabric-backed seam sealing tape for sealing seams on roofs before coating with Carlisle's X-Tenda Coat™ system. Coating-Ready Cover Tape has aggressive tack, forming a watertight seal when applied, and has excellent long-term adhesion. It remains flexible after application to accommodate joint movement. Using Coating-Ready Cover Tape can save up to 50% of the cost of traditional seam sealing techniques.

Installation

Clean the surface to which the tape is being applied. Peel off a few inches of the release liner and carefully position the Coating-Ready Cover Tape before applying. Any attempt to reposition the tape after application will damage the material. Apply pressure starting at the center of the tape and working towards the outside edges, removing any bubbles as you go. When finished, the edges shall have no tunnels, openings, or fishmouths. Only apply Coating-Ready Cover Tape to areas that are to be coated the same day.

Precautions

- 1. Surfaces must be clean and dry prior to adhering Coating-Ready Cover Tape.
- Coating-Ready Cover Tape is not meant to be left exposed to the elements without coating with X-Tenda Coat.
- 3. Do not apply this product where temperatures will exceed 200° F.
- 4. Do not stretch this product during application.
- 5. Do not use this product where it may come into contact with solvents, acids, or bases.
- 6. Shelf life is 24 months when material is stored between 30° F and 110° F.

Typical Properties & Characteristics

Appearance	Grayish self-adhesive layer with white fabric backing.
Bonding Time	Watertight upon application. Full strength after 24 hours.
Thickness	25 mils
Adhesive	Elastomeric modified butyl rubber.
Operating Temperature	-20° F to 200° F
Low Temperature Flexibility	Passes, no cracking
Tensile Strength	790 psi.
Peel strength	17 pli.

