

# SecurEdge™ 200 Drip Edge



## Overview

Carlisle's SecurEdge 200 Drip Edge features an "L" shaped continuous cleat with pre-slotted fastening holes for ease of locating and installing. It is manufactured in 12' lengths that provide fewer joints/seams and fewer sections to handle for faster installations.

## Features and Benefits

- » Variety of face heights available with or without cleat
- » Interlocking, concealed splice plates prevents moisture migration
- » Manufactured in convenient 12' lengths with pre-punched fastening holes to ensure correct fastener placement
- » Factory fabricated miters eliminates the need for field fabrication and provides a cleaner appearance
- » ANSI/SPRI ES-1 tested to comply with International Building Code (IBC)

## Installation

For complete installation instructions, refer to Carlisle specifications and details or visit [www.carlislesyntec.com](http://www.carlislesyntec.com).

## Finishes

- » Natural Mill Finish aluminum
- » Pre-coat Kynar 500 – from Carlisle's standard color chart
- » Premium Metallic Kynar
- » Anodized aluminum – clear, bronze, and black
- » Custom post-painted Kynar finishes available upon request

## Quality Assurance

Tested per ANSI/SPRI Test Method RE-2 Pull-Off test for fascia. Fascia shall be certified by Carlisle to design pressures as indicated in current edition of SPRI's Wind Resistance Standard for Edge Systems Used with Low Slope Roofing Systems. Meets International Building Code.

## Technical Services

Engineering and shop drawings, as well as long-form specifications and CAD details, are available from Carlisle. Product samples, detail sheets, color chips, and color charts are also available for submittal packages. For personal assistance with questions or submittals, contact Carlisle or your local manufacturer's representative.