

CARLISLE SURE-SEAL® SECUREDGE™ 2000 FASCIA SYSTEM**GENERAL:**

Carlisle's SecurEdge 2000 is an advanced roof edge fascia specifically designed for use with Carlisle Roofing Systems. Its unique engineered design provides maximum protection against roof edge damage caused by high wind velocities. The fascia system consists of a heavy extruded aluminum anchor bar, corrosion resistant fasteners and a snap-on fascia cover. SecurEdge 2000 is available in two versions, one for Fully-Adhered and Mechanically-Fastened Roofing Systems and one for Ballasted Roofing Systems. SecurEdge 2000 is an FM 1-90 approved edging system.

TYPICAL PROPERTIES AND CHARACTERISTICS:

STANDARD			BALLASTED		
Style	Face	Coverage	Style	Face	Coverage
2040	4" (102 mm)	2 3/4" (70 mm)			
2055	5 1/2" (140 mm)	4 1/4" (108 mm)	B*2050	5" (127 mm)	3" (76 mm)
2070	7" (178 mm)	5 3/4" (146 mm)	B*2065	6 1/2" (165 mm)	4.5" (114 mm)
2085	8 1/2" (216 mm)	7 1/4" (184 mm)	B*2080	8" (203 mm)	6" (152 mm)

Color/Metal Options:

23 Colors in 24 Ga. (.6 mm) Kynar Coated Steel
 15 Colors in .040 (1 mm) Kynar Coated Aluminum
 6 Colors in .040 (1 mm) Anodized Aluminum
 .040 (1 mm) Mill Finish Aluminum
 .040 (1 mm) Clear Anodized Aluminum

Accessories:

Factory Welded Inside & Outside Corners
 Overflow Scuppers (A or B) 1/2" Extension
 Spillout Scuppers (A or B) 4" Extension
 Downspout Scuppers (A or B)
 (A: Tapered) or (B: Regular)
 Fascia Extenders

Packaging:Anchor Bar (per carton)

120 LF [36.5 m] (10 pieces 12' lengths [3.65 m])

11 pieces anchor bar splice plates

125 pieces #12 X 1 5/8" (41 mm) Corrosion Resistant Hex Head Fasteners (with EPDM washers) for 2040, 2055, B*2050

190 pieces #12 X 1 5/8" (41 mm) Corrosion Resistant Hex Head Fasteners (with EPDM washers) for 2070, 2085, B*2065, B*2080

1 piece Hex Head Driver Bit

Fascia Cover (per carton)

120 LF [36.5 m] (10 pieces 12' lengths [3.65 m])

CAUTIONS AND WARNINGS:

1. Material must be kept clean and dry during storage. A protective poly film is laminated to the Kynar fascia and must be removed after installation.
2. SecurEdge 2000 should be installed above the potential ponded water level on the roof.

INSTALLATION:

See appropriate installation guide.

Carlisle, SecurEdge and Sure-Seal are trademarks of Carlisle Corporation.

Kynar is a registered trademark of Pennwalt.

©1999 Carlisle Corporation

7/99