

SecurEdge™ 300 Fascia System



Overview

Carlisle's SecurEdge 300 is a decorative metal fascia with a continuous galvanized steel spring clip designed to terminate single-ply roofing at perimeters. This watertight system features concealed joint splice plates and no exposed fasteners. Standard SecurEdge 300 Fascia is formed from .063" (1.60 mm) or .050" (1.25 mm) aluminum and 24-gauge Kynar 500® -coated galvanized steel. Extruded aluminum SecurEdge 300 is available in a slightly different fascia profile.

Features and Benefits

- » Up to 200 lbs/ft (300 kg/m) clamping strength
- » Easy snap-on installation with no need to crimp the drip edge
- » FM Global approved for up to FM 1-195 wind uplift protection
- » Tested, certified, and warranted to resist wind speeds up to 110 mph
- » Covered by 20-year warranty

Installation

Review Carlisle specifications and details or visit www.carlisesyntec.com for complete installation information.

Finishes

- » Natural mill finish aluminum
- » Pre-coat Kynar 500 – from Carlisle's standard color chart
- » Post-coat Kynar 500 – two-coat colors from Carlisle's standard color chart
- » Non-standard Kynar 500 – colors requiring multiple coatings or protective clear coats
- » Anodized aluminum – clear, bronze, and black

Quality Assurance

Tested per SPRI Test Method RE-1 for roof edge termination of single-ply roofing membranes. The fascia system is tested to secure the membrane to a minimum of 100lbs/ft. SPRI Test Method RE-2 Pull-Off test for fascia. Fascia is certified to design pressures as indicated in current edition of Wind Resistance Standard for Edge Systems Used with Low-Slope Roofing Systems. The fascia product shall be listed in the current RoofNav approved for FM 1-195.

Technical Services

Engineering and shop drawings, as well as long-form specifications and CAD details, are available from Carlisle. Product samples, detail sheets, color chips, and color charts are also available for submittal packages. For assistance with questions or submittals, contact Carlisle or a Carlisle Manufacturer's Representative.

Specifications

Fascia Model	Fascia Height	Minimum Gauge	Max. Nailer Thickness	Springclip Gauge	Springclip Height
SE300-550	5.5"	.050"	2.25"	24 ga.	2.5"
SE300-700	7.0"	.050"	3.75"	24 ga.	2.5"
SE300-850	8.5"	.050"	5.25"	24 ga.	2.5"
SE300-1000	10.0"	.050"	6.75"	22 ga.	2.5"

Minimum and maximum sizes and minimum gauges are indicated. Intermediate sizes may be specified within these ranges with slightly longer lead time. Note: Extruded fascia available in different fascia profile.