

SecurEdge™ 3000 Roof Edge System



Overview

Carlisle's SecurEdge 3000 is a two-part assembly with a rigid terminator base plate and a decorative snap-on fascia cover for single-ply roofs. The fascia is fabricated from formed aluminum, .040" (1.00 mm), .050" (1.25 mm), or .063" (1.60 mm), or 24-gauge Kynar 500®-coated galvanized steel and features concealed splice plates. The 10' (3048 mm)-long retainer base plate is 20-gauge galvanized steel with 9/32" pre-punched holes for fasteners at 12" (304.8 mm) on center. Optional retainers are available in .050" or .063" aluminum.

Features and Benefits

- » Clamps membrane against the building's perimeter like a termination bar
- » Allows for the use of high-torque screws without penetrating the membrane's top surface
- » ANSI/SPRI/FM-4435 ES-1 Approved to comply with International Building Code.
- » FM Approved
- » Eligible for coverage under the Carlisle total roof system warranty.

Installation

Review Carlisle specifications and details or visit www.carlisesyntec.com for complete installation information.

Finishes

- » Natural mill finish aluminum
- » Pre-coat Kynar 500 – from Carlisle's standard color chart
- » Post-coat Kynar 500 – two-coat colors from Carlisle's standard color chart
- » Non-standard Kynar 500 – colors requiring multiple coatings or protective clear coats
- » Anodized aluminum – clear, bronze and black

Quality Assurance

SecurEdge 3000 is tested per SPRI Test Method RE-2 Pull-Off test for fascia. Fascia is certified to design pressures as indicated in the current edition of ANSI/SPRI/FM 4435/ES-1 Wind Resistance Standard for Edge Systems used with Low-Slope Roofing Systems.

Technical Services

Engineering and shop drawings, as well as long-form specifications and CAD details, are available from Carlisle. Product samples, detail sheets, color chips, and color charts are also available for submittal packages. For assistance with questions or submittals, contact Carlisle or a Carlisle Manufacturer's Representative.

Specifications

Fascia Model	Fascia Height "A"	Nailer Thickness Covered "C"
SE3-375	3.75" / 95 mm	2.25" / 57 mm
SE3-525	5.25" / 133 mm	3.75" / 95 mm
SE3-675	6.75" / 171 mm	5.25" / 133 mm
SE3-825	8.25" / 210 mm	6.75" / 171 mm