

# SecurWeld® 200/300 PVC-Coated Drip Edge



## Overview

Carlisle's SecurWeld 200 and 300 PVC-Coated Drip Edge features an L-shaped continuous cleat with pre-slotted fastening holes for ease of installation. SecurWeld 200 is manufactured in 12' lengths and SecurWeld 300 is manufactured in 10' lengths.

## Features and Benefits

- » Carlisle's PVC coating is 30-50% thicker than the competition's
- » Coated with Carlisle PVC to ensure compatibility
- » Variety of face heights are available, with or without cleat
- » Interlocking, concealed splice plates prevent moisture and water migration
- » Florida Building Code approved (with cleat)
- » ANSI/SPRI ES-1 tested to comply with the International Building Code (with cleat)

## Installation

For complete installation instructions, refer to Carlisle specifications and details or visit [www.carlisesyntec.com](http://www.carlisesyntec.com)

## Finishes

- » White, gray, or tan PVC coating

## Quality Assurance

Tested per ANSI/SPRI Test Method RE-2 Pull-Off Test for Fascia. Fascia shall be certified by Carlisle to design pressures as indicated in current edition of SPRI's Wind Resistance Standard for Edge Systems Used with Low-Slope Roofing Systems. Meets International Building Code. Florida Building Code approved (with cleat).

## Technical Services

Engineering and shop drawings, as well as long-form specifications and CAD details, are available from Carlisle. Product samples, detail sheets, color chips, and color charts are also available for submittal packages. For assistance with questions or submittals, contact Carlisle or your local manufacturer's representative.

