

Sure-Seal 200 TPO-Coated Drip Edge



Overview

Carlisle's Sure-Seal 200 TPO-Coated Drip Edge features an L-shaped continuous cleat with pre-slotted fastening holes for ease of locating and installing. It is manufactured in 12' lengths that provide fewer joints/seams and fewer pieces to handle for faster installations.

Features and Benefits

- » Carlisle's TPO Coating is 30-50% thicker than competition
- » Variety of face heights available with or without cleat
- » Interlocking, concealed splice plates prevent migration
- » Heat-weldable TPO for reduced callbacks
- » Manufactured in convenient 12' lengths with pre-punched fastening holes to ensure correct fastener placement
- » Coated with Carlisle TPO to ensure compatibility
- » Florida Building Code approved
- » ANSI/SPRI ES-1 tested to comply with the International Building Code

Installation

For complete installation instructions, refer to Carlisle specifications and details, or visit www.carlislesyntec.com

Finishes

- » White TPO Coating

Quality Assurance

Tested per ANSI/SPRI Test Method RE-2 Pull-Off test for fascia. Fascia shall be certified by Carlisle to design pressures as indicated in current edition of SPRI's Wind Resistance Standard for Edge Systems Used with Low Slope Roofing Systems. Meets International Building Code. Florida Building Code approved.

Technical Services

Engineering and shop drawings, as well as long-form specifications and CAD details, are available from Carlisle. Product samples, detail sheets, color chips, and color charts are also available for submittal packages. For personal assistance with questions or submittals, contact Carlisle or your local manufacturer's representative.

Sure-Seal 200 TPO Coated Drip Edge

