

Material Name: Pourable Sealer- Part A Product #:302084

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

Pourable Sealer-Part A

Synonyms

Liquiseal

Chemical Family

Sealant

Product Use

Waterproofing sealant

Restrictions on Use

For industrial use only.

Manufacturer Information

Carlisle SynTec 1285 Ritner Highway Carlisle, PA 17013 USA

UDA Di 1

Phone: +1-800-479-6832

Emergency Phone #: +1-800-424-9300 (CHEMTREC)

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Carcinogenicity - Category 2

GHS Label Elements

Symbol(s)



Signal Word

Warning

Hazard Statement(s)

Suspected of causing cancer

Precautionary Statement(s)

Prevention



Product #:302084

Material Name: Pourable Sealer- Part A

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood Wear protective gloves/protective clothing/eye protection/face protection

Response

IF exposed or concerned: Get medical advice/attention

Storage

Store locked up

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
Trade Secret	Hydroxyl terminated Polybutadiene	10-30
Trade Secret	Dihydroxypropyl aniline	1-5
1333-86-4	Carbon black	1-5
Mixture	Ground coal	1-5
1317-65-3	Limestone	10-30
Trade Secret	Petroleum distillates	10-30
112926-00-8	Silica, amorphous, precipitated and gel	1-5

Section 4 - FIRST AID MEASURES

Description of Necessary Measures

IF exposed or concerned: Get medical advice/attention.

Inhalation

Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.

Skin

Take off immediately all contaminated clothing. Wash exposed skin with soap and water. Get medical attention, if needed.

Eves

Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention, if needed.

Ingestion

Do NOT induce vomiting. Get medical attention immediately.

Page 2 of 11 Issue date: 2018-03-22 Revision 2.0 Print date: 2018-03-22



Material Name: Pourable Sealer- Part A

Product #:302084

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

Most Important Symptoms/Effects

Acute

May cause mild skin irritation. May cause mild eye irritation.

Delayed

Suspected of causing cancer.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Dry chemical, foam or carbon dioxide. Water may be ineffective. Use water spray to keep containers cool.

Unsuitable Extinguishing Media

Do not use high-pressure water streams.

Special Hazards Arising from the Chemical

Can burn and explode easily when exposed to open flames or high heat. Vapors are heavier than air and may travel a considerable distance to a source of ignition and flashback.

Hazardous Combustion Products

butadiene, oxides of carbon.

Fire Fighting Measures

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Absorb with earth, sand or other non-combustible material and transfer to container. Dike for later disposal. Dispose in accordance with all applicable regulations.

Environmental Precautions

Avoid release to the environment.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not eat, drink

Page 3 of 11 Issue date: 2018-03-22 Revision 2.0 Print date: 2018-03-22



Material Name: Pourable Sealer- Part A

Product #:302084

or smoke when using this product. Wash contaminated clothing before reuse. Avoid contact with skin and eyes. KEEP OUT OF REACH OF CHILDREN.

Conditions for Safe Storage, Including any Incompatibilities

Store locked up

Keep away from incompatible materials. Store between 32 F and 90 F. Protect from freezing.

Incompatible Materials

Strong oxidizing agents, strong acids, strong bases

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Carbon black	1333-86-4					
ACGIH:	3 mg/m³ TWA inhalable fraction					
NIOSH:	3.5 mg/m³ TWA; 0.1 mg/m3 TWA (Polycyclic aromatic hydrocarbons) a	· •				
	1750 mg/m ³ IDLH					
OSHA (US):	3.5 mg/m³ TWA					
Mexico:	3.5 mg/m ³ TWA LMPE-PPT	7 mg/m ³ STEL [LMPE-CT]				
	1015 65 0					
Limestone	1317-65-3					
NIOSH:	10 mg/m ³ TWA total dust; 5 mg/m ³	TWA respirable dust				
OSHA (US):	15 mg/m ³ TWA total dust; 5 mg/m ³	TWA respirable fraction				
Mexico:	10 mg/m³ TWA LMPE-PPT	20 mg/m ³ STEL [LMPE-CT]				
Silica, amorphous, precipitated and gel						
OSHA (US):	20 mppcf TWA; ((80)/(% SiO2) mg/m³ TWA)					
Mexico:	10 mg/m³ TWA LMPE-PPT					

Biological limit value

There are no biological limit values for any of this product's components.

Engineering Controls

If necessary, use appropriate local exhaust ventilation to keep exposures below the regulated limits.

Page 4 of 11 Issue date: 2018-03-22 Revision 2.0 Print date: 2018-03-22



Material Name: Pourable Sealer- Part A Product #:302084

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Safety glasses or goggles are recommended when there is a potential for eye contact. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin Protection

Wear appropriate work clothing. Wear protective shoes. Recommended material: protective skin cream.

Respiratory Protection

If engineering controls do not maintain airborne concentrations to a negligible level, an approved respirator must be worn.

Glove Recommendations

Wear impermeable gloves.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	black viscous liquid	Physical State	liquid
Odor	Slight, aromatic	Color	black
Odor Threshold	Not available	рН	Not available
Melting Point	Not available	Boiling Point	>260 °C (500 °F)
Freezing point	Not available	Evaporation Rate	Not available
Boiling Point Range	Not available	Flammability (solid, gas)	Not available
Autoignition	Not available	Flash Point	254 °C (490 °F)
Lower Explosive Limit	Not available	Decomposition	Not available
Upper Explosive Limit	Not available	Vapor Pressure	<0.001 mmHg
Vapor Density (air=1)	Not available	Specific Gravity (water=1)	Not available
Water Solubility	negligible	Partition coefficient: n-octanol/water	Not available
Viscosity	250000 cps	Solubility (Other)	Not available
Density	1.23 (relative)	voc	<15 g/L

Other Information

No additional information available.

Page 5 of 11 Issue date: 2018-03-22 Revision 2.0 Print date: 2018-03-22



Material Name: Pourable Sealer- Part A Product #:302084

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal conditions of use.

Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

Conditions to Avoid

Avoid formation of vapors and extreme temperatures. Avoid contact with incompatible materials.

Incompatible Materials

Strong oxidizing agents, strong acids, strong bases

Hazardous decomposition products

Butadiene, oxides of carbon

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

May cause irritation of mucous membranes.

Skin Contact

May cause mild skin irritation.

Eye Contact

May cause mild eye irritation.

Ingestion

May cause irritation of mucous membranes.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Hydroxyl terminated Polybutadiene (Trade Secret)

Oral LD50 Rat >34600 mg/kg

Dihydroxypropyl aniline (Trade Secret)

Oral LD50 Rat 3763 mg/kg

Dermal LD50 Rabbit >2000 mg/kg

Carbon black (1333-86-4)

Oral LD50 Rat >8000 mg/kg

Immediate Effects

May cause mild skin irritation. May cause mild eye irritation.

Page 6 of 11 Issue date: 2018-03-22 Revision 2.0 Print date: 2018-03-22



Material Name: Pourable Sealer- Part A Product #:302084

Delayed Effects

Suspected of causing cancer.

Irritation/Corrosivity Data

May cause mild skin irritation. May cause mild eye irritation.

Respiratory Sensitization

No data available.

Dermal Sensitization

No data available.

Component Carcinogenicity

Carbon black	1333-86-4
ACGIH:	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
IARC:	Monograph 93 [2010]; Monograph 65 [1996] (Group 2B (possibly carcinogenic to humans))
DFG:	Category 3B (could be carcinogenic for man, inhalable fraction)
OSHA:	Present
Silica, amorphous, precipitated and gel	112926-00-8
IARC:	Monograph 68 [1997] (Group 3 (not classifiable))

Germ Cell Mutagenicity

No data available.

Reproductive Toxicity

No data available.

Specific Target Organ Toxicity - Single Exposure

No target organs identified.

Specific Target Organ Toxicity - Repeated Exposure

No target organs identified.

Aspiration hazard

No data available.

Medical Conditions Aggravated by Exposure

No data available.

Additional Data

No additional information available.

Page 7 of 11 Issue date: 2018-03-22 Revision 2.0 Print date: 2018-03-22



Material Name: Pourable Sealer- Part A Product #:302084

Section 12 - ECOLOGICAL INFORMATION

Ecotoxicity

Avoid release to the environment.

Component Analysis - Aquatic Toxicity

Carbon black	1333-86-4
Fish:	Fish LC50 96 hr Brachydanio rerio >1000 mg/L
Petroleum distillates	Trade Secret
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID

Persistence and Degradability

No information available for the product.

Bioaccumulative Potential

No information available for the product.

Mobility

No information available for the product.

Other Toxicity

No additional information available.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents/container in accordance with local/regional/national/international regulations. This material and its container must be disposed of as hazardous waste.

Section 14 - TRANSPORT INFORMATION

US DOT Information:

UN/NA #: Not regulated

IATA Information:

UN#: Not regulated

TDG Information:

UN#: Not regulated

Page 8 of 11 Issue date: 2018-03-22 Revision 2.0 Print date: 2018-03-22



Material Name: Pourable Sealer- Part A Product #:302084

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

None of this products components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C)

Acute Health: Yes Chronic Health: Yes Fire: No Pressure: No Reactivity: No

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Carbon black	1333-86-4	Yes	Yes	Yes	Yes	Yes
Limestone	1317-65-3	No	Yes	Yes	Yes	Yes
Silica, amorphous, precipitated and gel	112926-00-8	No	Yes	Yes	Yes	Yes

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause cancer

(Carbon black	1333-86-4
	Carc:	carcinogen, initial date 2/21/03 (airborne, unbound particles of respirable size)

Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

Carbon black	1333-86-4
	1 %

Component Analysis - Inventory

Hydroxyl terminated Polybutadiene (Trade Secret)

US	CA	EU	AU	РН	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Dihydroxypropyl aniline (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	No

Page 9 of 11 Issue date: 2018-03-22 Revision 2.0 Print date: 2018-03-22



Material Name: Pourable Sealer- Part A Product #:302084

Carbon black (1333-86-4)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX	
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes	

Ground coal (Mixture)

Į	IJS	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
1	Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	No	No

Limestone (1317-65-3)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	NSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Petroleum distillates (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

Silica, amorphous, precipitated and gel (112926-00-8)

US	CA	EU	AU	РН	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
No	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Section 16 - OTHER INFORMATION

HMIS Rating

Health: 1 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

NFPA Ratings

Health: 1 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes New SDS: April 18, 2015

Page 10 of 11 Issue date: 2018-03-22 Revision 2.0 Print date: 2018-03-22



Material Name: Pourable Sealer- Part A Product #:302084

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD -Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA -Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer: IATA - International Air Transport Association: ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH -Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

Other Information

Disclaimer:

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.

Page 11 of 11 Issue date: 2018-03-22 Revision 2.0 Print date: 2018-03-22