

Material Name: Sure-White Lap Sealant Product #: 302172

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name: Sure-White Lap Sealant

Synonym: Sealant

Chemical Family: Solvent Based Sealant

Product Use: Sealant for EPDM Single-Ply Roofing Membranes

Restrictions on Use: For industrial use only.

Manufacturer Information

Carlisle SynTec 1285 Ritner Highway Carlisle, PA 17013

USA

Phone: +1-800-479-6832

Emergency Phone #: +1-800-424-9300 (CHEMTREC)

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Flammable Solid - Category 1 Skin Corrosion/Irritation - Category 2 Serious Eye Damage/Eye Irritation - Category 2A Carcinogen- Category 1B

GHS Label Elements

Symbol(s)







Signal Word

Danger

Hazard Statement(s)

Flammable solid Causes skin irritation.

Causes serious eye irritation.

May cause cancer.

Precautionary Statement(s)

Prevention

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Page 1 of 14 Issue date: 2015-03-17 Revision 1.0 Print date: 2016-04-26



Product #: 302172

Material Name: Sure-White Lap Sealant

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Wear protective gloves / eye protection / face protection.

Wear protective gloves.

Wear eye protection / face protection.

Ground/bond container and receiving equipment.

Wash thoroughly after handling.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

Specific treatment (see on this label).

IF exposed or concerned: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

If on skin: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
64742-89-8	Solvent naphtha (petroleum), light aliph.(VM&P)	25-50
1317-65-3	Limestone	5-20
13463-67-7	titanium dioxide	2.5-10
68953-58-2	organoclay [containing 0-3% quartz CAS 14808-60-7]	2.5-10
112945-52-5	Amorphous Silica	1.0
1305-78-8	calcium oxide	1.0
57-11-4	stearic acid, pure	0.5

Page 2 of 14 Issue date: 2015-03-17 Revision 1.0 Print date: 2016-04-26



Material Name: Sure-White Lap Sealant

14808-60-7	Quartz (SiO2)	0.1
------------	---------------	-----

Additional information:

It is highly unlikely the powders and pigments compounded within this product would pose a hazardous risk from inhalation as they are no longer a respirable particulate. Exposure to these ingredients as used in sealants, putties, bedding compounds and other non-sprayable products is highly unlikely. The concentrations listed in the composition section are percent by weight unless a gas. Gas concentrations are expressed in percent by volume.

Product #: 302172

Section 4 - FIRST AID MEASURES

Description of Necessary Measures

If exposed or concerned: Get medical advice/attention.

Inhalation

Remove to fresh air and seek medical attention.

Skin

Immediately wash with water and soap and rinse thoroughly

Eyes

Rinse opened eye for 20 minutes under running water. If eye becomes irritated, obtain medical treatment

Ingestion

If swallowed, get medical attention.

Information for doctor:

- · Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

CO2, extinguishing powder or water spray. Fight larger fires with water spray

Special Hazards Arising from the Chemical

Formation of toxic gases is possible during heating or in case of fire.

Fire Fighting Measures

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Page 3 of 14 Issue date: 2015-03-17 Revision 1.0 Print date: 2016-04-26



Material Name: Sure-White Lap Sealant Product #: 302172

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Ensure adequate ventilation.

Methods and Materials for Containment and Cleaning Up

Dispose of contaminated material as waste in accordance with federal state and local regulations. Ensure adequate ventilation..

Environmental Precautions

Do not allow to enter sewers/ surface or ground water.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Avoid prolonged or repeated contact with skin. Avoid contact with eyes. Wash thoroughly after handling. Open and handle receptacle with care

Information about protection against explosions and fires:

Keep container closed when not in use

Conditions for Safe Storage, Including any Incompatibilities

Storage

Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility:

Store away from oxidizing agents.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Specific end use(s) No further relevant information available.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

titanium dioxide	13463-67-7
PEL	Long-term value: 15* mg/m³ *total dust
REL	See Pocket Guide App. A

Page 4 of 14 Issue date: 2015-03-17 Revision 1.0 Print date: 2016-04-26



Material Name: Sure-White Lap Sealant Product #: 302172

TLV	Long-term value: 10 mg/m³ withdrawn from NIC		
calcium oxide	1305-78-8		
PEL	Long-term value: 5 mg/m ³		
REL	Long-term value: 2 mg/m³		
TLV	Long-term value: 2 mg/m³		
Quartz	14808-60-7		
PEL	See quartz listing		
REL	Long-term value: 0.05* mg/m³ *respirable dust; See Pocket Guide App. A		
TVL	Long-term value: 0.025* mg/m³ *as respirable fraction		
Mexico:	3 mg/m3 TWA LMPE-PPT respirable fraction		
Silica, crystalline	14808-60-7		
ACGIH:	0.025 mg/m ³ TWA respirable fraction		
NIOSH:	0.05 mg/m³ TWA respirable dust 50 mg/m³ IDLH respirable dust		
OSHA (US):	((30)/(%SiO2 + 2) mg/m³ TWA) total dust; ((250)/(%SiO2 + 5) mppcf TWA) respirable fraction; ((10)/(%SiO2 + 2) mg/m³ TWA) respirable fraction		
Mexico:	0.1 mg/m ³ TWA LMPE-PPT respirable fraction		

Additional information:

The lists that were valid during the creation were used as basis.

- Exposure controls
- · Personal protective equipment (see listings below)
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· Breathing equipment:

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Safety glasses with side shields. Tightly sealed goggles.

Page 5 of 14 Issue date: 2015-03-17 Revision 1.0 Print date: 2016-04-26



Material Name: Sure-White Lap Sealant Product #: 302172

Skin Protection Body Protection

Protective work clothing.

Glove Recommendations

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR

Chloroprene rubber, CR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed..

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Pasty solid	Physical State	Solid
Odor	Petroleum-like	Color	White
Odor Threshold	Not determined	рН	Not determined
Melting Point	Undetermined	Boiling Point	104 °C (219 °F)
Boiling Point Range	Not available	Flammability (solid, gas)	Not determined
Autoignition	Product is not selfigniting	Flash Point	18 °C (64 °F)
Upper Flammability limit	6.7%	Decomposition Not determined	
Lower Flammability limit	0.9 %	Vapor Pressure	Not determined
Vapor Density (air=1)	Not determined	Specific Gravity at 20 °C (68 °F):	1.04 g/cm³ (8.679 lbs/gal)
Water Solubility	negligible	Partition coefficient: n-octanol/water	Not determined
Kinematic Viscosity	>20.5 cSt	Solubility / Miscibility with Water:	Not soluble

Page 6 of 14 Issue date: 2015-03-17 Revision 1.0 Print date: 2016-04-26



Material Name: Sure-White Lap Sealant Product #: 302172

Relative/Vapor Density	Not determined	voc	<450 g/L
---------------------------	----------------	-----	----------

Other Information

No additional information available.

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal conditions of use.

Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

Incompatible Materials

Strong oxidizing agents, acids, bases

Hazardous decomposition products

Oxides of carbon, oxides of nitrogen

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

May cause respiratory irritation.

Skin Contact

Causes skin irritation.

Eve Contact

Causes serious eye irritation.

Ingestion

May cause gastrointestinal irritation.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Severely hydrotreated paraffinic oil (Trade Secret)

Oral LD50 Rat >5000 mg/kg

Dermal LD50 Rabbit >2000 mg/kg

Carbon compound (Trade Secret)

Page 7 of 14 Issue date: 2015-03-17 Revision 1.0 Print date: 2016-04-26



Material Name: Sure-White Lap Sealant Product #: 302172

Oral LD50 Rat >15400 mg/kg

Polyphenol antioxidant (Trade Secret) Oral LD50 Rat >200 mg/kg Dermal LD50 Rabbit >5010 mg/kg

Naphtha, petroleum, light aliphatic (64742-89-8) Oral LD50 Mouse 5000 mg/kg Dermal LD50 Rabbit 3000 mg/kg

Solvent naphtha, petroleum, medium aliphatic (64742-88-7)

Oral LD50 Rat >5000 mg/kg Dermal LD50 Rabbit 3000 mg/kg

Silica, crystalline (14808-60-7) Oral LD50 Rat 500 mg/kg

Immediate Effects

Cause skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May cause gastrointestinal irritation.

Delayed Effects

Causes damage to organs through prolonged or repeated exposure: lungs, central nervous system.

Irritation/Corrosivity Data

Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation.

Respiratory Sensitization

No data available.

Dermal Sensitization

It may cause sensitization in some individuals.

Component Carcinogenicity

component curem		
Silica compound	Trade Secret	
IARC:	Monograph 68 [1997] (Group 3 (not classifiable))	
Carbon compound	Trade Secret	
ACGIH:	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans	
IARC:	Monograph 93 [2010]; Monograph 65 [1996] (Group 2B (possibly carcinogenic to humans))	
DFG:	Category 3B (could be carcinogenic for man, inhalable fraction)	
OSHA:	Present	

Page 8 of 14 Issue date: 2015-03-17 Revision 1.0 Print date: 2016-04-26



Material Name: Sure-White Lap Sealant Product #: 302172

Silica, crystalline	14808-60-7
ACGIH:	A2 - Suspected Human Carcinogen
IARC:	Monograph 100C [2012]; Monograph 68 [1997] (Group 1 (carcinogenic to humans))
NTP:	Known Human Carcinogen (respirable size)
DFG:	Category 1 (causes cancer in man, alveola fraction)
OSHA:	Present (respirable size)

Germ Cell Mutagenicity

No data available.

Reproductive Toxicity

No data available.

Specific Target Organ Toxicity - Single Exposure

May affect the central nervous nervous system: drowsiness, dizziness.

Specific Target Organ Toxicity - Repeated Exposure

May cause damage to organs through prolonged or repeated exposure: lungs, central nervous system.

Aspiration hazard

May cause aspiration hazard.

Medical Conditions Aggravated by Exposure

May cause allergic skin reaction. Aspiration into the lungs may cause chemical pneumonitis.

Additional Data

This product contains crystalline silica, which is a known carcinogen. However, this component is bound by the polymer portion of the sealant. The only way this component would be released is through incineration. Therefore, this product is not considered a carcinogen.

Section 12 - ECOLOGICAL INFORMATION

Ecotoxicity

Avoid release to the environment.

Component Analysis - Aquatic Toxicity

Severely hydrotreated paraffinic oil	Trade Secret
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L
Invertebrate: EC50 48 h Daphnia magna >1000 mg/L IUCLID	
Polyphenol antioxidant	Trade Secret

Page 9 of 14 Issue date: 2015-03-17 Revision 1.0 Print date: 2016-04-26



Material Name: Sure-White Lap Sealant Product #: 302172

Fish:	LC50 96 h Oncorhynchus mykiss >0.2 mg/L [semistatic]
Algae:	EC50 72 h Pseudokirchneriella subcapitata >0.2 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna >0.2 mg/L IUCLID
Naphtha, petroleum, light aliphatic	64742-89-8
Algae:	EC50 72 h Pseudokirchneriella subcapitata 4700 mg/L IUCLID
Solvent naphtha, petroleum, medium aliphatic	64742-88-7
Fish:	LC50 96 h Pimephales promelas 800 mg/L [static]
Algae:	EC50 96 h Pseudokirchneriella subcapitata 450 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna >100 mg/L IUCLID

Persistence and Degradability

No information available for the product.

Bioaccumulative Potential

No information available for the product.

Mobility

No information available for the product.

Other Toxicity

No additional information available.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents/container in accordance with local/regional/national/international regulations.

Section 14 - TRANSPORT INFORMATION

US DOT Information:

Shipping Name:ADHESIVES

Hazard Class: 3

Page 10 of 14 Issue date: 2015-03-17 Revision 1.0 Print date: 2016-04-26



Product #: 302172

Material Name: Sure-White Lap Sealant

UN/NA #: UN1133 Packing Group: II

Required Label(s): < 0.3 gal (limited quantity)

IATA Information:

Shipping Name:ADHESIVES

Hazard Class: 3 UN#: UN1133 Packing Group: II

Required Label(s): < 0.3 gal (limited quantity)

TDG Information:

Shipping Name:ADHESIVES

Hazard Class: 3 UN#: UN1133 Packing Group: II Required Label(s):

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

None of this products components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C)

Acute Health: Yes Chronic Health: Yes Fire: Yes Pressure: No Reactivity: No

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

	CAC	CA	3.6.4	MAT	NIT	DA
Component	CAS	CA	MA	MN	NJ	PA
Silica compound	Trade Secret	No	Yes	Yes	Yes	Yes
Limestone	1317-65-3	No	Yes	Yes	Yes	Yes
Carbon compound	Trade Secret	Yes	Yes	Yes	Yes	Yes
Mica	12001-26-2	Yes	Yes	Yes	Yes	Yes
Solvent naphtha, petroleum, medium aliphatic	64742-88-7	No	No	No	Yes	No
Silica, crystalline	14808-60-7	No	Yes	Yes	Yes	Yes

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause cancer

Carbon compound	Trade Secret

Page 11 of 14 Issue date: 2015-03-17 Revision 1.0 Print date: 2016-04-26



Material Name: Sure-White Lap Sealant

Care:	carcinogen, initial date 2/21/03 (airborne, unbound particles of respirable size)
Silica, crystalline	14808-60-7
Care:	carcinogen, initial date 10/1/88 (airborne particles of respirable size)

Product #: 302172

Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

Carbon compound	Trade Secret
	1 %
Mica	12001-26-2
	1 %
Silica, crystalline	14808-60-7
	1 %

Component Analysis - Inventory

Silica compound (Trade Secret)

US	CA	EU	AU	РН	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
No	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Severely hydrotreated paraffinic oil (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	No

Limestone (1317-65-3)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	NSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Carbon compound (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Page 12 of 14 Issue date: 2015-03-17 Revision 1.0 Print date: 2016-04-26



Material Name: Sure-White Lap Sealant Product #: 302172

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Ye	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	No

Naphtha, petroleum, light aliphatic (64742-89-8)

US	CA	EU	AU	РН	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

Polybutene (Trade Secrret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Mica (12001-26-2)

US	CA	EU	AU	РН	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
No	DSL	No	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

Solvent naphtha, petroleum, medium aliphatic (64742-88-7)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

Silica, crystalline (14808-60-7)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Section 16 - OTHER INFORMATION

HMIS Rating

Page 13 of 14 Issue date: 2015-03-17 Revision 1.0 Print date: 2016-04-26



Material Name: Sure-White Lap Sealant Product #: 302172

Health: 1 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

NFPA Ratings

Health: 1 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes

Updated Product code number: April 26, 2016

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD -Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA -Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database: MAK - Maximum Concentration Value in the Workplace: MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH -Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

Other Information

Disclaimer:

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.

Page 14 of 14 Issue date: 2015-03-17 Revision 1.0 Print date: 2016-04-26