



The Innovators of Quality Framing and Lath Systems

Standard Angle Specification



| Steel Thickness | Size | Length | Pcs. / Bdl. | Bdl. / Pallet | Pcs. / Pallet |
|-----------------|-------------|--------|-------------|---------------|---------------|
| 25GA | 1 ½" X 1 ½" | 10' | 10 | 100 | 1000 |
| 20GA | 1 ½" X 1 ½" | 10' | 10 | 50 | 500 |
| 25GA | 2" x 2" | 10' | 10 | 50 | 500 |
| 20GA | 2" X 2" | 10' | 10 | 50 | 500 |

CEMCO's angles are fabricated from hot-dipped galvanized steel complying with ASTM A653 with a G40 coating meeting ASTM A924. The angles are rolled-formed from minimum 25 gauge (0.0179-inch-thick steel, uncoated). The standard angles are manufactured in 25 and 20 gauge steel thickness and legs lengths 1½" and 2" in.

CALIFORNIA EXPANDED METAL LATH PRODUCTS CO.

Corporate Office
263 N. Covina Lane,
City of Industry, CA 91744
Phone (800) 775-2362
Fax (626) 330-7598

1001-A Pittsburg Antioch Hwy,
Pittsburg, CA 94565
Phone (925) 473-9340
Fax (925) 473-9341

490 Osage Street,
Denver, CO 80204
Phone (303) 572-3626
Fax (303) 572-3627

www.cemcsteel.com