

800.775.2362 | www.cemcosteel.com

Structural Engineering/Design: 925.473.9340 Technical Services: 800.416.2278

FAS°-093X[™]-V (VINYL) FIRE RATED CONTROL JOINT

Product Description

CEMCO FAS-093X-V is an extruded flexible PVC control joint with an integrated intumescent strip that provides fire, smoke, and sound rated solutions in vertical control joints.

- Can be used in INTERIOR drywall partitions.
- C Has integrated mud legs for attachment and adhesion of joint compounds.
- C Provides an aesthetically pleasing reveal with integrated groove.
- C Installs fully cured, unaffected by water/moisture/temperature.
- C Easily installs using spray adhesive and staples.
- Pink in color for identification in the inspection process.
- C Does not require drywall rips, fire sealant or mineral wool backing within the wall cavity.
- C Tear away mud guide strip to protect the v-groove during installation.
- Can be used in metal or wood stud wall assemblies.
- C Provides 1 and 2 hour fire rating from the same profile.
- C Paintable.

Ordering / Packaging

Description	Part #	Length	Pcs/Ctn	Submitted for Review/Use	~
FAS-093X-V	093XV	10'	20	093X-V	

Storage / Warranty

- 🌔 When stored indoors and kept dry in its original package and condition, FAS-093X-V has an unlimited shelf life.
- C 25 Year Limited Warranty see CEMCO Standard Fire, Smoke & Acoustic Product Warranty for details.

ASTM & Code Standards

- C ASTM C1047-99
- C ASTM D1784-03
- **C** ASTM D3678-97
- C ASTM E84
- ASTM E1966
- 🕐 UL 2079 5th Edition
- C L-Rating (air leakage) testing for compliance with International Building Code (IBC) and Canadian Building Code (CBC).
- C UL listings/approvals include: HW-D-0596; HW-D-0621; WW-D-0172
- 🕐 U.S. Patent No. 8,671,632

















800.775.2362 | www.cemcosteel.com

Structural Engineering/Design: 925.473.9340 Technical Services: 800.416.2278

FAS°-093X[™]-V (VINYL) FIRE RATED CONTROL JOINT







← View the installation video!





