

STRIPITE

Corporate Headquarters 13191 Crossroads Pkwy N., Ste 325 City of Industry, CA 91746 Phone: 800.775.2362 Fax: 626.330.7598

Manufacturing Facilities City of Industry, CA Denver, CO

Ft. Worth, TX

Pittsburg, CA

Pittsburg, CA 94565

Structural Engineering/Design 1001-A Pittsburgh Antioch Hwy Phone: 800.775.2362 Fax: 626.330.7598

Technical Services

13191 Crossroads Pkwy N., Ste 325 City of Industry, CA 91746 Phone: 800.416.2278 Fax: 626.249.5004





Properties

CEMCO's Stripite product is a general purpose expanded metal lath for plaster reinforcement. Stripite is a perfect addition to doors, windows, and other areas where cracking will most likely occur. Stripite is also used as a grout stop in cement block construction. Stripite is fabricated from 26 gauge galvanized steel in standard G60 coating. G90 coating is available upon request.

Packaging

Size (X × Y)	Weight / Mlf.	Foot / Carton	Piece / Carton	Carton / Pallet
4" x 96"	78 lbs.	600'	75	18
6" x 96"	115 lbs.	600'	75	18

ASTM & Code Standards:

- ASTM A653
- ASTM A924
- ASTM C841
- ASTM C1063

■ IBC: 2012, 2015, 2018 CBC: 2013, 2016

- AISI: S100-07, S100-12,
 - S100-16, S220-11, S220-15

Technical Services Technical Services: 800.416.2278 Structural Engineering/Design: 925.473.9340 www.cemcosteel.com







This technical information reflects the most current information available and supersedes any and all previous publications effective December 21, 2018. 12-21-18 AT

LEED v4 for Building and Design Construction

- MR Prerequisite: Construction and Demolition Waste Management Planning.
- MR Credit: Construction and Demolition Waste Management. MR Credit: Building Product Disclosure and Optimization -
- Sourcing of Raw Materials, Option 2.
- MR Credit: Building Product Disclosure and Optimization -Environmental Product Declarations, Options 1 & 2.
- MR Credit: Building Product Disclosure and Optimization -Material Ingredients, Option 1.
- MR Credit: Building Life-Cycle Impact Reduction, Option 4.

CEMCO cold-formed steel framing products contain 30% to 37% recycled steel.

- Total Recycled Content: 36.9%
- Post-Consumer: 19.8%
- Pre-Consumer: 14.4%