



<u>Insulation Type</u>	<u>Insulation Photo</u>	<u>Max/Min Temperature Rating</u>	<u>UV Test Conditions (1-Year Miami)</u>	<u>UV Test Result Per Insulation MFG.</u>	<u>R-Value 1/2" Tube Size</u>	<u>R-Value 3/4" Tube Size</u>	<u>R-Value 1" Tube Size</u>
Standard NBR/PVC Black Elastomeric.		220°F/92°C -297°F/-128°C	Not Tested. Use additional Protection	N/A	1/4">3.8 , 3/8">3.3 , 1/2">3.3 , 5/8">3.3 , 3/4">3.3 , 7/8">3.3 , 1-1/8">3.3	1/4">6.4 , 3/8">5.9 , 1/2">6.4 , 5/8">5.5 , 3/4">5.5, 7/8">5.9 , 1-1/8">5.4	1/4">9.0 , 3/8">8.0 , 1/2">7.2 , 5/8">7.2 , 3/4">7.0 , 7/8">7.0 , 1-1/8">7.0
Jacketed NBR/PVC Black Shield		220°F/92°C -297°F/-128°C	ASTM G154 Cycle 1 for 5,000 Hours	Excellent: No Deteriorations			
*Per Armacell							



314-429-1556 • cerroset.com
email: sales@cerroset.com