






15/16" Classic Stab System


The Classic Stab System features the ever-popular 15/16" (24mm) face width that is widely used in interior designs today. Strong staked-on end tabs are incorporated into the cross tee design to provide quick and easy installation with optimal tightness among installed components.

Classic Stab System

- · Double web design for durability and strength.
- Cross tees feature staked-on end tabs for optimal tightness and ease of installation.
- · Intermediate and heavy duty load bearing capabilities.
- · Stepped-end design featured on cross tees.
- Grid features G30 hot-dipped galvanized steel web construction for corrosion resistance.
- 25% recycled content (20% post-consumer, 5% pre-consumer).
- · Available in standard white and black



15/16" Grid



Classic Stab System

					Allowable Load (lbs./lin.ft (kg/m) Hanger Spacing)
MAIN RUNNER ITEM #	LENGTH	HEIGHT	FACE	METAL THICKNESS	ASTM C635 4' (1220mm)
CS12-12-15	12' (3660mm)	1-1/2" (38mm)	15/16" (24mm)	0.015" (0.38mm)	Intermediate Duty 12.00 (17.90)
CS12-12-20	12' (3660mm)	1-1/2" (38mm)	15/16" (24mm)	0.020" (0.51mm)	Heavy Duty 16.00 (23.80)

15/16" Grid

Slotted 6" o.c.

CROSS TEE ITEM #	LENGTH	HEIGHT	FACE	METAL THICKNESS
CS1-12-12	1' (305mm)	1-1/2" (38mm)	15/16" (24mm)	0.012" (0.30mm)
CS2-12-12	2' (610mm)	1-1/2" (38mm)	15/16" (24mm)	0.012" (0.30mm)
CS4-12-12*	4' (1220mm)	1-1/2" (38mm)	15/16" (24mm)	0.012" (0.30mm)
CS5-12-12*	5' (1524mm)	1-1/2" (38mm)	15/16" (24mm)	0.015" (0.38mm)
CS8-12-12*	8' (2440mm)	1-1/2" (38mm)	15/16" (24mm)	0.015" (0.38mm)

*Slotted 12" o.c.

TRADITIONAL WALL ANGLE ITEM #	LENGTH	HEIGHT	FACE	METAL THICKNESS
WA15-15	12' (3660mm)	15/16" (24mm)	15/16" (24mm)	0.018" (0.46mm)
WA15-9	12' (3660mm)	15/16" (24mm)	9/16" (15mm)	0.018" (0.46mm)

SHADOW MOLDING ITEM #	METAL DIMENSIONS	THICKNESS
SM1000	10' x 15/16" x 3/8" x 3/8" x 9/16" (3050 x 24 x 10 x 10 x 15mm)	0.018" (0.46mm)
SM1020	10' x 3/4" x 3/8" x 3/8" x 3/4" (3050 x 19 x 10 x 10 x 19mm)	0.018" (0.46mm)

